

Procedure B.—The hydrocarbon, the chloroalkane and di-*t*-butyl peroxide were weighed into a glass liner (cooled in a bath at -78° when the gaseous hydrocarbons were employed). The liner was sealed into an Ipatieff-type rotating autoclave of 850-cc. capacity, nitrogen was charged to a pressure of 50 atm., and the autoclave was then heated, the temperature being raised gradually during four hours from 130 – 140° . The autoclave was permitted to stand overnight, after which the gas was discharged to the atmosphere, and the liquid product was washed, dried and distilled.

Identification of Products.—The chlorinated products were identified by means of their boiling points and refractive indices and in many cases by comparison of their infrared spectra with those of authentic samples (see Table I).

Hexachloroethane was isolated from the higher boiling product of a number of experiments and identified by means of its melting point as well as that of a mixture of the material with an authentic sample of hexachloroethane. Thus, for example, in expt. 13, there was obtained 1.5 cc. of the product boiling at 78 – 90° at 26 mm. (175 – 193° at 760 mm.). This became partially crystalline on standing and filtration yielded 0.9 cc. of liquid and 0.8 g. of crystals,

which were recrystallized from methanol; m. p. and mixed m. p. 184 – 185° (sealed tube).

Summary

When a saturated hydrocarbon is treated with certain polyhaloalkanes in the presence of a catalytic amount of a decomposing organic peroxide, hydrogen-halogen exchange occurs and the hydrocarbon is converted to a monohaloalkane. Straight chain paraffins of at least three carbon atoms as well as branched chain and cyclic hydrocarbons may be used.

When hexachloroethane is used as the halogen donor, alkyl chloride is obtained in excellent yield, but the other anticipated product, namely, pentachloroethane, is not formed. Instead, tetrachloroethylene and hydrogen chloride are produced.

RIVERSIDE, ILL.

RECEIVED DECEMBER 27, 1949

[CONTRIBUTION FROM THE RESEARCH DEPARTMENT OF THE GREAT WESTERN DIVISION, THE DOW CHEMICAL COMPANY]

A New Synthesis of Ethyl Trifluoroacetate

By T. R. NORTON

Various methods have been described for the preparation of trifluoroacetic acid and the esters thereof. According to the method of Swarts,¹ *m*-aminobenzotrifluoride was oxidized with chromic acid. Chlorinated derivatives of $\text{CF}_3\text{-CH=CH}_2$ have been oxidized with a permanganate and caustic alkali.^{2,3} The oxidation of fluorochlorobutenes, such as $\text{CF}_3\text{CCl=CClCF}_3$, with caustic alkali and a permanganate was described by Babcock.⁴

It has been found that trifluoroacetic acid can be prepared in high yield by a less costly and much less drastic type of reaction involving the simple hydrolysis of 2,4,6-tris-(trifluoromethyl)-1,3,5-triazine (III) with dilute aqueous mineral acid at atmospheric pressure.

The method is made practical by an improved synthesis of the previously described compound (III).⁵

Acetonitrile was chlorinated by one of several known methods^{6,7} to give trichloroacetonitrile (I).

The trimerization of trichloroacetonitrile was heretofore carried out by contact with anhydrous halogen acids such as hydrogen chloride or hydrogen bromide.^{8,9} In contrast to aromatic nitriles,

which are readily trimerized,¹⁰ the reaction with trichloroacetonitrile is extremely slow, the time required for completion being on the order of about 100 hours. It has been found that the addition of a small amount of anhydrous aluminum halide to the reaction mixture of trichloroacetonitrile and hydrogen halides greatly activates the latter in causing trimerization of the trichloroacetonitrile, reducing the time required for completion of the reaction to only a few hours and in many cases to less than one hour. The aluminum halides alone are substantially ineffective to cause the trimerization. Their function appears to be solely to serve as an activator for the hydrogen halide. If either (or both) the aluminum halide or hydrogen halide contains bromine as the halide, the reaction rate is increased and pressure is not required as is the case when aluminum chloride and anhydrous hydrogen chloride are used as catalysts. With increasing proportions of aluminum halide the reaction rate increases, although the yield is decreased slightly. The optimum conditions are described in the two examples in the Experimental Section.

The fluorination of 2,4,6-tris-(trichloromethyl)-1,3,5-triazine has been previously described,⁵ using anhydrous hydrogen fluoride and a small amount of antimony pentachloride as catalyst. However, the yield of the completely fluorinated product, 2,4,6-tris-(trifluoromethyl)-1,3,5-triazine, was not given but is assumed to be small in view of the drastic conditions employed. It has now been found that the Swarts reaction using antimony

- (1) Swarts, *Bull. Acad. Roy. Belg.*, **8**, 343 (1922).
- (2) A. L. Henne, *THIS JOURNAL*, **67**, 918 (1945).
- (3) A. L. Henne, U. S. Patent 2,371,757 (Mar. 20, 1945).
- (4) J. H. Babcock and A. D. Kischitz, U. S. Patent 2,414,706 (Jan. 21, 1947).
- (5) E. T. McBee, *et al.*, *Ind. Eng. Chem.*, **39**, 391 (1947).
- (6) K. Dachlauer, German Patent 694,479 (Aug. 18, 1942).
- (7) J. J. Gray and F. Burgess, U. S. Patent 2,426,091 (Aug. 19, 1947).
- (8) K. Dachlauer, German Patent 682,391 (Oct. 13, 1939).
- (9) K. Dachlauer, German Patent 699,493 (Nov. 30, 1940).

- (10) M. A. Kunz, *et al.*, U. S. Patent 1,989,042 (Jan. 22, 1935).

