SAFETY DATA SHEET

PU RESIN

Huangshan Zhongze New Material Co., Ltd.

• According to GHS (Sixth Revised Edition)



See	ction 1 Product and Company Identification
> Product Identifier	
Product Name	Polyurethane Resin
Synonyms	_
CAS No.	9009-54-5
EC No.	_
Molecular Formula	_
	Jses of the Substance or Mixture and Uses Advised Against
Relevant Identified Uses	Please consult manufacturer.
Uses Advised Against	Please consult manufacturer.
> Details of the Suppli	er of the Safety Data Sheet
Applicant Name	Huangshan Zhongze New Material Co., Ltd.
Application Address	No.15 Changsheng Rd., Huizhou Circular Economy Zone, Huizhou District, Huangshan City, Anhui Province
Applicant Post Code	245000
Applicant Telephone	+86-559-3517758
Applicant Fax	+86-559-3517261
Applicant E-mail	hszz1209@163.com
Manufacturer Name Manufacturer Address	Huangshan Zhongze New Material Co., Ltd. No.15 Changsheng Rd., Huizhou Circular Economy Zone, Huizhou District Huangshan City, Anhui Province
Manufacturer Post Code Manufacturer	245000
Telephone	+86-559-3517758
Manufacturer Fax	+86-559-3517261
Manufacturer E-mail	hszz1209@163.com
> Emergency Phone Nun	nber
Emergency Phone Number	+86-559-3517758

Section 2 Hazards Identification

Hazard class and label elements of the product according to GHS (the sixth revised edition):

> GHS Hazard Class

Flammable Liquids	Category 2
Eye Damage/Irritation	Category 2A
Specific Target Organ Toxicity (Single Exposure)	Category 3

> GHS Label Elements

Pictogram



Signal Word

Danger

> Hazard Statements

H225	Highly flammable liquid and vapour
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness

> Precautionary Statements

Prevention	
P210	Keep away from heat, hot surfaces, sparks,open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof [electrical/ventilating/lighting] equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
Response	
P312	Call a POISON CENTER/doctor, if you feel unwell.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Storage	
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
Disposal	
P501	Dispose of contents/container in accordance with local/regional/national/ international regulations.

Section 3 Composition/Information on Ingredients

Component

Concentration (weight percent, %)

CAS No.

EC No.

Ethyl acetate	Commercial secrets	141-78-6	205-500-4
Propan-2-ol	Commercial secrets	67-63-0	200-661-7
PU	Commercial secrets	-	-

Section 4 First Aid Measures

> Description of First Aid Measures

General Advice	Immediate medical attention is required. Show this safety data sheet (SDS) to the doctor in attendance.
Eye Contact	Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician if feel uncomfortable.
Skin Contact	Take off contaminated clothing and shoes immediately. Wash off with plenty of water for at least 15 minutes and consult a physician if feel uncomfortable.
Ingestion	Do not induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or Poison Control Center immediately.
Inhalation	Move victim into fresh air. If breathing is difficult, give oxygen. Do not use mouth to mouth resuscitation if victim ingested or inhaled the substance. If not breathing, give artificial respiration and consult a physician immediately.
Protecting of First-aiders	Ensure that medical personnel are aware of the substance involved. Take precautions to protect themselves and prevent spread of contamination.

> Most Important Symptoms and Effects, both Acute and Delayed

1 Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.

> Indication of Any Immediate Medical Attention and Special Treatment Needed

- 1 Treat symptomatically.
- 2 Symptoms may be delayed.

Section 5 Fire Fighting Measures

> Extinguishing Media

Suitable Extinguishing
MediaDry chemical, carbon dioxide or alcohol-resistant foam.Unsuitable
Extinguishing MediaDo not use a solid water stream as it may scatter or spread fire.

> Specific Hazards Arising from the Substance or Mixture

- **1** Will form explosive mixtures with air.
- 2 Fire exposed containers may vent contents through pressure relief valves thereby increasing fire intensity and/ or vapour concentration.
- 3 Vapours may travel to source of ignition and flash back.
- **4** Liquid and vapour are flammable.
- **5** Containers may explode when heated.
- 6 Fire exposed containers may vent contents through pressure relief valves.
- 7 May expansion or decompose explosively when heated or involved in fire.

> Advice for Firefighters

- **1** As in any fire, wear self-contained breathing apparatus (MSHA/NIOSH approved or equivalent) and full protective gear.
- 2 Fight fire from a safe distance, with adequate cover.
- 3 Prevent fire extinguishing water from contaminating surface water or the ground water system.

> Personal Precautions, Protective Equipment and Emergency Procedures

Section 6 Accidental Release Measure

- 1 Avoid breathing vapors and contacting with skin and eye.
- 2 Beware of vapours accumulating to form explosive concentrations.
- 3 Vapours can accumulate in low areas.
- **4** Emergency personnel wear positive pressure self-contained breathing apparatus. Wear protective and anti-static clothing. Wear chemical impermeable gloves.
- 5 Ensure adequate ventilation. Remove all sources of ignition.
- 6 Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.
- 7 Use personal protective equipment. Avoid breathing vapours, mist, gas or dust.

> Environmental Precautions

- 1 Prevent further leakage or spillage if safe to do so.
- **2** Discharge into the environment must be avoided.

> Methods and Materials for Containment and Cleaning Up

- 1 Absorb spilled material in dry sand or inert absorbent. In case of large amount of spillage, contain a spill by bunding.
- 2 Adhered or collected material should be promptly disposed of, in accordance with appropriate laws and regulations.
- 3 Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

Section 7 Handling and Storage

> Precautions for Handling

- **1** Avoid inhalation of vapors.
- **2** Use only non-sparking tools.
- **3** To prevent fire caused by electrostatic discharge steam, equipment on all metal parts should be grounded.
- **4** Use explosion proof equipment.
- 5 Handling is performed in a well ventilated place.
- 6 Wear suitable protective equipment.
- 7 Avoid contact with skin and eyes.
- 8 Keep away from heat/sparks/open flames/ hot surfaces.
- 9 Take precautionary measures against static discharges.

> Precautions for Storage

- **1** Keep containers tightly closed.
- 2 Keep containers in a dry, cool and well-ventilated place.
- 3 Keep away from heat/sparks/open flames/ hot surfaces.
- **4** Store away from incompatible materials and foodstuff containers.

Section 8 Exposure Controls/Personal Protection

> Control Parameters Occupational Exposure Limit Values

Component	Country/Dogion	Limit Value - Eight Hours		Limit Value - Short Term	
Component	Country/Region	ppm	mg/m³	ppm	mg/m³
	USA - OSHA	400	1400	-	-
	South Korea	400	1400	-	-
Ethyl acetate	Ireland	200	-	400	-
141-78-6	Germany (AGS)	400	1500	800	3000
	Denmark	150	540	300	1080
	Australia	200	720	400	1440
	USA - OSHA	400	980	-	-
	South Korea	200	480	400	980
Propan-2-ol 67-63-0	Ireland	200	-	400	-
	Germany (AGS)	200	500	400	1000
	Denmark	200	490	400	980
	Australia	400	983	500	1230

Biological Limit Values

No information available

Monitoring Methods

- 1 EN 14042 Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.
- 2 GBZ/T 160.1~GBZ/T 160.81-2004 Determination of toxic substances in workplace air (Series standard).

> Engineering Controls

- 1 Ensure adequate ventilation, especially in confined areas.
- 2 Ensure that eyewash stations and safety showers are close to the workstation location.
- **3** Use explosion-proof electrical/ventilating/lighting/equipment.
- **4** Set up emergency exit and necessary risk-elimination area.

> Personal Protection Equipment

Eye Protection	Tightly fitting safety goggles (approved by EN 166(EU) or NIOSH (US).
Hand Protection	Wear protective gloves (such as butyl rubber) , passing the tests according to EN 374(EU), US F739 or AS/NZS 2161.1 standard.
Respiratory protection	If exposure limits are exceeded or if irritation or other symptoms are experienced, use a full-face respirator with multi-purpose combination (US) or type AXBEK (EN 14387) respirator cartridges.
Skin and Body Protection	Wear fire/flame resistant/retardant clothing and antistatic boots.

Section 9 Physical and Chemical Properties

Appearance: Pale yellow transparent viscous liquic	Odor: No information available
Odor Threshold: No information available	pH: No information available
Melting Point/Freezing Point (°C): No information available	¹ Initial Boiling Point and Boiling Range (°C): > 35
Flash Point (°C)(Closed Cup): < 20	Evaporation Rate: No information available
Flammability: Not applicable	Upper/lower explosive limits[%(v/v)]: Upper limit : No information available ;Lower limit :No information available
Vapor Pressure (MPa): No information available	Vapor Density (g/mL): No information available

Relative Density (g/cm ³): No information available Solubility: No information available			
n-Octanol/Water Partition Coefficient: No information available Auto-Ignition Temperature(°C): No informatio available			
Decomposition Temperature (°C): No information available			
Particle characteristics: Not applicable			

Section 10 Stability and Reactivity

Reactivity	Contact with incompatible substances can cause decomposition or other chemical reactions.
Chemical Stability	Stable under proper operation and storage conditions.
Possibility of	In contact with metal alkoxides may cause a fire. In contact with oxidants causes
Hazardous Reactions	severe reactions, and may cause a fire or explosion.
Conditions to Avoid	Incompatible materials, heat, flame and spark.
Incompatible Materials	Metal alkyl oxide, metal hydride, inorganic peroxide, nitrate and halogens oxyacid salts. Oxidants, alkali metals, alkaline earth metals and aluminum.
Hazardous Decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Toxicological Information Section 11

> Acute Toxicity

Component	CAS No.	LD ₅₀ (Oral)	LD ₅₀ (Dermal)	LC ₅₀ (Inhalation, 4h)
Ethyl acetate	141-78-6	5620mg/kg(Rat)	No information	No information
		5020mg/kg(hat)	available	available
Propan-2-ol	67-63-0	5045mg/kg(Rat)	12800mg/kg(Rabbit)	No information
	07 05 0 50 4 5mg/kg(kat)		12000mg/kg(Rabbit)	available

> Skin Corrosion/Irritation

No information available

> Serious Eye Damage/Irritation

Causes serious eye irritation(Category 2A)

> Skin Sensitization

No information available

> Respiratory Sensitization

No information available

> Germ Cell Mutagenicity

No information available

> Carcinogenicity

ID	CAS No.	Component	IARC	NTP
1	141-78-6	Ethyl acetate	Not Listed	Not Listed
2	67-63-0	Propan-2-ol	Category 3	Not Listed
3	-	PU	Not Listed	Not Listed

> Reproductive Toxicity

No information available

> Reproductive Toxicity (Additional)

No information available

> STOT-Single Exposure

May cause drowsiness or dizziness(Category 3)

> STOT-Repeated Exposure

No information available

> Aspiration Hazard

No information available

Section 12 Ecological Information

> Acute Aquatic Toxicity


Component	CAS No.	Fish	Crustaceans	Algae
Ethyl acetate	141-78-6	LC₅₀ : 328mg/L (96h)(Fish)	No information available	ErC ₅₀ : 2500mg/L (96h)
Propan-2-ol	67-63-0	LC ₅₀ : 9640mg/L (96h)(Fish)	EC ₅₀ : >1000mg/L (48h)	ErC ₅₀ :>1000mg/L (72h)

> Chronic Aquatic Toxicity

Component	CAS No.	Fish	Crustaceans	Algae
Propan-2-ol	67-63-0	No information available	NOEC : >100mg/L	NOEC : 1000mg/L

> Others

Persistence and Degradability Bioaccumulative Potential	No information available No information available
Mobility in Soil	No information available
Results of PBT and vPvB Assessment	Ethyl acetate does not meet the criteria for PBT and vPvB according to Regulation (EC) No 1907/2006, annex XIII. Propan-2-ol does not meet the criteria for PBT and vPvB according to Regulation (EC) No 1907/2006, annex XIII.



	Section 14 mansport
Transporting Label	
Marine pollutant	None
UN Number	1866
UN Proper Shipping Name	RESIN SOLUTION, flammable
Transport Hazard Class	3
Transport Subsidiary Hazard Class	None
Packing Group	Π

Section 15 Regulatory Information

> International Chemical Inventory

Component	EINECS	TSCA	DSL	IECSC	NZIoC	PICCS	KECI	AICS	ENCS
Ethyl acetate	√	√	√	√	√	√	√	√	√
Propan-2-ol	√	√	√	√	√	√	√	√	√
PU	×	×	×	×	×	×	×	×	×

[EINECS] European Inventory of Existing Commercial Chemical Substances.

[TSCA] United States Toxic Substances Control Act Inventory.

[DSL] Canadian Domestic Substances List.

[IECSC] China Inventory of Existing Chemical Substances.

New Zealand Inventory of Chemicals. [NZIoC]

[PICCS] Philippines Inventory of Chemicals and Chemical Substances.

Existing and Evaluated Chemical Substances. 【KECI】

[AICS] Australia Inventory of Chemical Substances.

Existing And New Chemical Substances. [ENCS]

Note

" $\sqrt{}$ " Indicates that the substance included in the regulations

"×" That no data or included in the regulations

Creation Date	2017/01/06
Revision Date	2017/01/06
Reason for Revision	-

> Disclaimer

This Safety Data Sheet (SDS) was prepared according to UN GHS (the 6th revised edition). The data included was derived from international authoritative database and provided by the enterprise. Other information was based on the present state of our knowledge. We try to ensure the correctness of all information. However, due to the diversity of information sources and the limitations of our knowledge, this document is only for user's reference. Users should make their independent judgment of suitability of this information for their particular purposes. We do not assume responsibility for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product.