

View Article Online View Journal

RSC Advances

This article can be cited before page numbers have been issued, to do this please use: P. J. Wrigstedt, J. Keskiväli and T. Repo, *RSC Adv.*, 2016, DOI: 10.1039/C5RA25564C.



This is an *Accepted Manuscript*, which has been through the Royal Society of Chemistry peer review process and has been accepted for publication.

Accepted Manuscripts are published online shortly after acceptance, before technical editing, formatting and proof reading. Using this free service, authors can make their results available to the community, in citable form, before we publish the edited article. This Accepted Manuscript will be replaced by the edited, formatted and paginated article as soon as this is available.

You can find more information about *Accepted Manuscripts* in the **Information for Authors**.

Please note that technical editing may introduce minor changes to the text and/or graphics, which may alter content. The journal's standard <u>Terms & Conditions</u> and the <u>Ethical guidelines</u> still apply. In no event shall the Royal Society of Chemistry be held responsible for any errors or omissions in this *Accepted Manuscript* or any consequences arising from the use of any information it contains.



www.rsc.org/advances

Published on 04 February 2016. Downloaded by New York University on 05/02/2016 06:48:30

COPAL SOCIETY OF CHEMISTRY

Journal Name

ARTICLE

Received 00th January 20xx, Accepted 00th January 20xx

DOI: 10.1039/x0xx00000x

www.rsc.org/

Microwave-Enhanced Aqueous Biphasic Dehydration of Carbohydrates to 5-Hydroxymethylfurfural

P. Wrigstedt, J. Keskiväli and T. Repo *

RSC Advances Accepted Manuscript

We describe herein an efficient microwave-assisted aqueous biphasic dehydration of carbohydrates to 5hydroxymethylfurfural (HMF). The effects of several alkali metal salts in aqueous phase, organic solvents as extractive phase and Lewis acids are evaluated on the reaction. Specifically, starting from fructose, the use of bromide salts in aqueous phase and common organic solvent MeCN or lignocellulose-derived γ -valerolactone (GVL) as organic extractors are highly beneficial, leading to excellent HMF yields of up to 91% with HCl as Brønsted acid catalyst. In conjunction with an isomerization catalyst, the method was applicable to glucose as well as various disaccharides and cellulose, affording HMF in notably good yields, particularly with GVL as an extractor and reusable Amberlyst-38(wet) as an acid catalyst. The exceptionally high HMF yields obtained in aqueous solutions is attributed to the combined effect of the biphasic reaction system and the application of microwaves, which ensures short reaction times and minimized by-products formation thereof

Introduction

Over the last decade the dehydration of carbohydrates to 5-hydroxymethylfurfural (HMF) has attracted increasing attention for the sustainable production of chemicals (Scheme 1).^[1] For instance, HMF can be oxidized to 2,5-furandicarboxylic acid as a potential replacement for terephthalic acid in the production of polyesters,^[2] or converted to high energy density biofuel dimethylfuran.^[3]

Dehydration of fructose to HMF using both homogeneous and heterogeneous catalytic systems has been investigated extensively.^[4] Moderate to excellent yields of HMF have been achieved using mineral acids,^[5] ion exchange resins,^[6] oxides^[7] and zeolites^[8] as catalysts in monophasic ionic liquids,^[9] highboiling organic solvents (e.g. dimethylacetamide^[5] and DMSO^[10]) and their mixtures.^[11] However, the high cost of the solvents, and high downstream separation costs limits their economic feasibility. In this respect, aqueous processes are favored yet unfortunately inefficient (HMF yields < 50%) because side reactions, such as polymer formation and HMF rehydration into levulinic acid and formic acid, are promoted in water (Scheme 1).^[12] Consequently, the challenge is to make aqueous processes more efficient, that is, to increase the HMF selectivity by reducing the formation of by-products during the reaction. The development of various water-organic biphasic reaction systems, such as water-MIBK,^[13] and water-(MIBK+2-BuOH)^[14] systems, resulted in fair HMF yields of 69% and 60%, respectively. Systems with additional modifiers in aqueous phase, such as DMSO,^[15] NMP^[16] or PVP^[15] resulted in very good HMF yields of up to 83%. However, contamination of the organic phase by the modifier can lead to complex separation of solvent and product at the end of the process.

Recently, the presence of alkali metal salts, such as NaCl and KBr. has been reported to improve the HMF vields in glucose dehydration in organic solvents^[5] and aqueous biphasic systems^[17]. This was ascribed to the Cl⁻ and Br⁻ anions influencing the reaction by enhancing the fructose dehydration step (the reaction proceeds through fructose intermediate).^[5] Also, in aqueous biphasic systems the addition of an excess of salt is beneficial in increasing the HMF distribution to organic phase during the reaction (salting-out effect), and enabling the use of water-miscible solvents as the organic phase, such as THF and MeCN, which are expected to dissolve HMF better than common water-immiscible solvents. Exploiting this strategy with fructose, Hansen and co-workers reported an increase in HMF yield from 28% to 45% by the addition of NaCl into the H₃BO_{3(aq)}-MIBK biphasic system.^[18] Cao et al. described the use of NaHSO4(aq)-THF biphasic solvent system with tetraethyl ammonium salts, obtaining HMF yield of 81%.^[19] Recently, high HMF yield of 88% was reported for (IL- $\mathsf{HSO}_4)_{\mathsf{aq}}\text{-}\mathsf{MeCN}$ system with acidic ionic liquid (IL) as excess salt.^[20]

In general, aqueous acid-catalyzed dehydration reaction is fairly slow process and high temperature is commonly required for high product yield. In contrast to conventional heating, microwave irradiation generates high input of energy, thus rapidly overcoming the energy barrier necessary for

P. Wrigstedt, J. Keskiväli and Prof. T. Repo

Laboratory of Inorganic Chemistry

Department of Chemistry, P.O. Box 55 (A. I. Virtasen aukio 1)

FI-00014 University of Helsinki, Finland

E-mail: timo.repo@helsinki.fi

Electronic Supplementary Information (ESI) available: Experimental procedures and detailed results. See DOI: 10.1039/x0xx00000x

ARTICLE

product formation. In many occasions, microwave processing has been shown to dramatically reduce reaction times and to increase product yields and purities compared to conventionally heated experiments.^[21] In this respect, the implementation of microwaves appears to be a method of choice for accelerating the fructose dehydration reaction. To this date, only few reports^[4] describe the microwave-assisted synthesis of HMF from fructose or glucose employing aqueous mono^[22] or biphasic^[22c, 23] conditions.

Herein, we report high-yield transformation of carbohydrates to HMF applying the combination of microwaves and biphasic reaction systems.



Scheme 1. Fructose conversion to HMF and its transformation to valuable products.

Results and Discussion

Published on 04 February 2016. Downloaded by New York University on 05/02/2016 06:48:30.

The role of alkali metal salts in the fructose dehydration to HMF is well-established in organic solvents, in which bromide anions (NaBr or KBr) in place of chlorides (NaCl or KCl) enhance the reaction resulting in higher HMF yields.^[5, 24] This was ascribed to bromide anions promoting 1,2-enol formation from fructofuranosyl oxocarbenium ion, generated by Brønsted acid-catalyzed dehydration of C2 in fructose, more efficiently than the corresponding chlorides.^[5] However, in aqueous mono or biphasic media the results of the impact of salts are not consistent.^[4, 17] For example, chlorides performed better in the fructose dehydration to HMF using (Boric acid+salt)_{aa}-MIBK^[18] or HCl_{aq}-nBuOH biphasic system,^[25] whereas better HMF yields were reported with bromides in $(CrCl_3 \times 6H_2O + salt)_{aq}$ -(acetone+toluene) system.^[17] Therefore, we initiated the studies by investigating the effect of different sodium and potassium salts in an aqueous phase and microwave-compatible organic solvents as an extractive phase on the fructose conversion to HMF at 160 °C in the presence of 0.1 M HCl catalyst (Table 1).

In comparison to NaCl and KCl, the reactions with NaBr and KBr clearly resulted in faster fructose conversion and 6-8% higher HMF yields, regardless of the extractive solvent. The use of NaI and KI reduced the HMF yields further and no reaction occurred with the corresponding fluorides. The positive effect of halide ions on HMF yields decreased in the order Br > Cl > I \neq F, which is in agreement with previous results using organic solvents or comparable biphasic system under conventional heating.^[5, 17] Notably, the use of MeCN or

biomass-derived y-valerolactone (GVL), the latter of which has been extensively studied as a renewable solvent for biomass conversion,^[26] in place of traditionally used MIBK/2-BuOH, THF, DMF or alcoholic solvents, such as 2-BuOH and i-PrOH, as an organic phase resulted in faster fructose conversion rate and better HMF selectivity and yields. The high HMF yield of 85% and 84% obtained with KBr/MeCN and KBr/GVL systems are comparable to those of obtained in ionic liquids and highboiling organic solvents,^[4] and considerably better than monophasic solutions.^[22a, 22b] obtained in aqueous Importantly, the use of those solvents as extractors prevented the formation of insoluble humins and the most common byproducts levulinic acid and formic acid due to HMF rehydration (HPLC), ascribed to short reaction time and mild conditions. Also, we did not observe the presence of acetamide or acetic acid (HPLC) caused by an acid-catalyzed acetonitrile hydrolysis. It is noteworthy that after the reaction the aqueous and organic phases were fully separated, consequently allowing an easy separation of HMF. For example, the low boiling point of MeCN could be advantageous in the distillation process described by Dumesic et al. with 2-BuOH-MiBK as an extraction solvent.^[15] The addition of aldose-to-ketose isomerization catalyst (CrCl₃×6H₂O) decreased HMF yields from 85% to 79% (Entry 15). Hence, the use of isomerization catalysts, such as AI^{III} , Cr^{III} and La^{III} halides, in the fructose dehydration is not beneficial because the metal cations converts fructose to glucose or mannose (equilibrium), which are significantly more difficult to dehydrate to HMF.^[4a]

Table 1. The influence of alkali metal salts and organic solvents in the microwave-assisted aqueous biphasic fructose dehydration to HMF. $^{\rm [a]}$

Entry	Salt ^[b]	Organic phase	Conversion (%)	Yield (%)
1 ^[c]	KBr	MeCN	1	<1
2	NaBr	MeCN	>99	82
3	KBr	MeCN	>99	85
4	NaCl	MeCN	98	77
5	KCI	MeCN	97	78
6	Nal	MeCN	94	68
7	KI	MeCN	96	67
8	KF	MeCN	99	-
9	KBr	GVL ^[d]	>99	84
10	NaCl	GVL	96	79
11	KBr	THF	95	76
12	NaCl	THF	83	68
13	KBr	DMF	11	6
14	KBr	i-PrOH	n.d ^{.[e]}	73
15	KBr	2-BuOH	79	61
16	KBr	MIBK/2-BuOH	98	74
17 ^[f]	KBr	MeCN	96	79

[a] Reaction conditions: ~10 wt% fructose in (0.1 M HCI-salt)_{(aq}-solvent 1:2 v/v, MW 160 °C, 1 min.; [b] saturated solution; [c] without HCI; [d] GVL= γ -valerolactone; [e] Fructose and *i*-PrOH peak overlapped (HPLC); [f] with 5 mol% CrCl₃×6H₂O.

We next explored the impact of HCl concentration (0.025 M, 0.05 M and 0.1 M) on the reaction outcome using

2 | J. Name., 2012, 00, 1-3

This journal is © The Royal Society of Chemistry 20xx

Journal Name

 $(HCl+KBr)_{(aq)}$ -MeCN system at 160 °C, shown in Figure 1. It should be noted that with MW instrument (Biotage Initiator) the heating from r.t. to 160 °C took 80 sec, after which the reaction time was measured. For example, the total heating time for 1 and 60 sec reactions were therefore 81 and 140 sec, respectively (see Figure S1 and S2 in Supporting Info for MW heating profiles).

The initial fructose conversion rate was surprisingly fast, accelerating with increasing acid concentration, and high 82%, 96% and 98% conversions were recorded in only 1 second reaction time at 160 °C. Full fructose conversions were reached with 0.025 M HCl in 75 seconds, with 0.05 M HCl in 30 seconds and with 0.1 M HCl in 15 seconds. The maximum HMF yields were linked to HCl concentration, exhibiting a tradeoff between accelerating the formation rate of HMF and increasing formation rate of the by-products (Figure 1). Albeit the formation rate of HMF was accelerated with 0.1M HCl in respect to 0.05M HCl, the concurrent increase in the byproduct formation rate led to lower HMF yields. Correspondingly, the deceleration in the HMF formation rate with 0.025M HCl increased the reaction time and thus, in comparison to the reaction in 0.05M HCl, exposed the formed HMF to by-product formation resulting in lower yields. The decomposition rate of HMF was markedly fast with 0.1 M HCl, HMF yield decreasing from 88% to 83% in 60 second time interval (see Table S2 in Supporting info). After 300 seconds the HMF yield decreased to 76%, demonstrating that the acidpromoted undesired products formation was indeed very rapid under MW conditions. In the case of 0.05M HCl the presence of intermediate dehydration products was evident as the maximum HMF yield was recorded approximately 30 seconds after the full conversion of fructose. However, we were not able to identify these intermediates by HPLC analysis.



Figure 1. The effect of HCl concentration on fructose conversion and HMF yields in the fructose dehydration to HMF (*reaction conditions:* ~10 wt% fructose in (0.025-0.1 M HCl+KBr)_(aq)-MeCN 1:2, MW 160 °C, 1 to 90 sec).

By conducting the reaction in a single-phase manner, using catalytic amount of KBr in place of saturated solution in a 0.1M HCI-MeCN (1:4 v/v) system for 1 min at 160 °C, afforded HMF in surprisingly good 82% yield (see Table S1 in Supporting info). Without KBr only 30% HMF yield was recorded, showing that the presence of bromide anions was crucial for good

product yields. It is worth adding that the short reaction time and high yield experienced in the single phasic dehydration of fructose to HMF makes the process applicable for continuous flow manufacturing where short residence times are essential to achieve a high throughput.^[27] Particularly, industrial continuous flow microwave process, recently described by Morschhäuser *et al.*, which operates under hightemperature/high-pressure conditions with throughput of 20L/h, could be ideal for this type of reaction. ^[28] Obviously, the throughput of the system can be readily increased by parallel reactors.

In view of the ample reports describing the reaction with different acids,^[4] we further attempted to improve the HMF yields by assessing the effect of different homogenous (H_2SO_4 , HCl, HNO_3, H_3PO_4 , TFA and ammonium salts) and heterogeneous (Dowex-50 and Amberlyst-38) acid catalysts on the reaction. The experiments were performed in (acid+KBr)_(aq)-MeCN system at 160 °C for 1 minute reaction time (Figure 2). The acid concentration was set to 0.05 M except with Amberlyst-38 and Dowex-50, the amounts of which were optimized in separate experiments (see Table S4 in Supporting Info).



Figure 2. The effect of various acids on HMF yields (*conditions:* ~10 wt% fructose in (0.05 M acid+KBr)_(aq)-MeCN 1:2 v/v, MW 160 °C, 1 min, except with ammonium halides 2 min). (a) GVL used as an organic phase (b) PBS=phosphate buffer pH 2.1 using (PBS+KBr)_(aq)-MeCN and (c) (PBS+KBr)_(aq)-MIBK-2-BuOH.

From Figure 2, HCl was the most efficient acid, affording HMF in 91% yield with >99% fructose conversion. However, almost comparable HMF yields of 85%, 87%, 86% and 88% were recorded with H₂SO₄, HNO₃, TFA and Amberlyst-38 catalysts, respectively. The effect of the homogeneous Brønsted acids on HMF yields decreased in order HCl > HNO₃ \geq TFA \geq H₂SO₄ >> H₃PO₄. To our surprise, by replacing KBr with weakly acidic ammonium halides (NH₄Cl, NH₄Br and NH₄I, saturated solution), the reaction gave relatively high HMF yields of up to 81% (with NH₄Br) and without additional strong Brønsted The solid heterogeneous acids, Dowex-50WX4 and acids. Amberlyst-38(wet), readily dehydrated fructose furnishing HMF in very good 83% and 88% yields, respectively. The application of phosphate buffer solution (PBS, pH 2.1) as a reactive phase resulted in low HMF selectivity and yields,

DOI: 10.1039/C5RA25564C Journal Name

ARTICLE

contrary to an earlier report employing PBS/MIBK-2-BuOH biphasic system,^[22c] wherein very high HMF yield of 88% were reported under microwave conditions.

The main advantage in the microwave-assisted synthesis is an increase in reaction rate,^[29] reducing exposure time of the product to decomposition and increasing space-time-yield, which is an important feature in potential industrial applications. To assess the extent of the effect of MW irradiation on the reaction, we conducted experiments under conventional oil-bath heating at 160 °C applying biphasic (HCl+KBr)_(aq)-MeCN system (Figure 3).



Figure 3. Fructose dehydration to HMF under conventional oil-bath heating (*conditions:* ~10 wt% fructose (0.05 M HCl+KBr)_(aq)-MeCN 1:2 v/v, 160 °C, 10-40 min).

In comparison to MW irradiation, the conversion rate of fructose was considerably slower, agreeing with the previous report on fructose dehydration to HMF.^[30] After 10 min of the reaction the fructose conversion was only 62% with an HMF yield of 38%, which then gradually increased to 94% and 79% at 40 min, respectively. Likewise with MW irradiation, the presence of unidentified intermediates was obvious as the HMF selectivity increased with increasing reaction time from 64% (10 min) to 85% (30 min). Thereafter the selectivity decreased due to the governing formation rate of sideproducts such as humins. Similarly to the reactions conducted under MW heating, the yield of levulinic acid was negligible (<1%) in all experiments and, as a result, can be attributed to the biphasic system (MeCN). In contrast to microwave heated experiments, the presence of visible insoluble humins, the amount of which increased with time, were observed after the reaction. According to the results above, we may deduce that in comparison to conventional heating, a short-term reaction under MW irradiation is more efficient in promoting the dehydration of fructose to HMF by greatly reducing the reaction time, and consequently, the formation of by-products such as soluble and insoluble humins resulting in higher HMF selectivity and yield.

In the dehydration of fructose to HMF one of the major challenges is the acid-catalyzed by-product formation, which can be reduced by using dilute solutions.^[22a] However, from the industrial and economical viewpoints, higher initial fructose concentrations are desirable due to the small reactor volumes, and more efficient separation and purification steps.^[31] Moreover, several reports have shown that

microwave heating become more energy efficient as the scale increases, partly due to efficient transfer of microwave energy to a larger reaction mass.^[32] Therefore, we performed scale-up experiments using higher initial fructose concentrations from 10 to 50 wt%. As Figure 4 illustrates, the fructose conversion was very high (>98%) in all experiments. In accordance with the previous reports the best HMF yield of 90% was obtained with the lowest fructose concentration.^[22a, 22b] Small decrease in HMF yield and selectivity was then observed with increasing fructose concentration gradually by 10 wt%, and the lowest HMF yield of 77% was obtained with the highest fructose concentration of 50 wt%. The HMF yield of 84% obtained with fructose concentration of 30 wt% is noticeably better than reported earlier for aqueous mono^[22a] or biphasic systems.^{[22c, 251}



Figure 4. Results of fructose dehydration to HMF with increasing fructose concentration (*conditions:* 10 to 50 wt% fructose (9 mol-% HCl+KBr)_(aq)-MeCN 1:2 v/v, MW 160 °C, 1 min).

The use of glucose-to-fructose isomerization catalyst enables a one-pot tandem isomerization-dehydration process to produce HMF directly from glucose and glucose-containing carbohydrates, as depicted in Scheme 2.^[33] High HMF yields of up to 63 % from glucose have been reported for aqueous systems involving various catalyst such as La^{III}, Cr^{III} and Al^{III} halides, boric acid and borates.^[4] In view of this, we tested the efficiency of our system, described above, in the dehydration of glucose to HMF. Accordingly, an isomerization catalysts (Boric acid,^[18, 34] sodium borate,^[22c] CrCl₃×6H₂O^[17, 35] or AlCl₃×6H₂O ^[36]) was added to the $(acid+KBr)_{(aq)}$ -GVL or $(acid+KBr)_{(aq)}$ -MeCN system applying Amberlyst-38 (wet) or HCI as acid catalysts (Table 2).



Scheme 2 Cascade glucose transformation to HMF trough fructose.

In contrast to fructose dehydration, we found that Amberlyst-38(wet) as an acid catalyst performed equally or slightly better than 0.05 M HCl in the reaction. Also, MeCN was found to be less suitable solvent than GVL as an organic

Published on 04 February 2016. Downloaded by New York University on 05/02/2016 06:48:30

Published on 04 February 2016. Downloaded by New York University on 05/02/2016 06:48:30

Journal Name

extractive phase (constantly 1-4% better yields using GVL, See Table 2 and Table S5 in Supporting Info). The use of THF as an organic phase led to decreased HMF yield compared to those of MeCN and GVL (Entry 12).

 $\begin{array}{c} \textbf{Table 2.} Results of glucose dehydration to HMF with various isomerization catalysts in (Amberlyst-38+KBr)aq-GVL biphasic system .^{[a]} \end{array}$

Entry	Time	Isomerization	Glucose	HMF Yield
	(min)	Catalyst	Conversion (%)	(%)
1	3	Boric acid	30	10
2 ^[b]	3	Boric acid	1	-
3	3	Sodium borate	61	-
4	1	CrCl₃×6H₂O	87	59
5	2	CrCl₃×6H₂O	93	70
6	3	CrCl₃×6H₂O	98	74
7	4	CrCl₃×6H₂O	99	73
8	3	AICl ₃ ×6H ₂ O	82	40
9 ^[c]	3	AICl ₃ ×6H ₂ O	93	66
10 ^[d]	3	CrCl ₃ ×6H₂O	98	71
11 ^[b]	3	CrCl₃×6H₂O	97	65
12 ^[e]	3	CrCl ₃ ×6H ₂ O	98	70
13 ^[f]	3	CrCl ₃ ×6H ₂ O	92	54

[a] Reaction conditions: 10 mol% metal halide catalyst, 20 mol-% boric acid or borate, 21 mg Amberlyst-38 (wet) ~10 wt% glucose in KBr_(aq)-GVL 1:2 v/v, MW 160°C, 1-4 min. [b] without Amberlyst-38(wet). [c] 30 mol-% AlCl₃×6H₂O. [d] 0.05 M HCl as catalyst. [e] MeCN as an organic phase. [f] THF as an organic phase.

Boric acid and sodium borate (Borax) were reported as efficient catalysts in glucose-to-fructose isomerization in ionic liquid ^[34] and biphasic aqueous phosphate buffer-(MIBK+2-BuOH) system, ^[22c] affording HMF yields of 41% and 63%, respectively. However, when applied to our system these catalysts were inefficient. The use of boric acid gave HMF in a low 10% yield with poor selectivity after 3 minutes (Entry 1). In the absence of strong Brønsted acid only 1% glucose conversion occurred (Entry 2). Surprisingly, with sodium borate as catalyst no HMF was formed albeit 61% glucose conversion was observed after the reaction (Entry 3). Of the isomerization catalysts investigated in this study, CrCl₃×6H₂O was the most efficient under MW irradiation conditions and, in agreement with previous reports, performed better than AlCl₃×6H₂O (Entries 6, 8-9).^[17, 35b] Thus, the best HMF yield of 74% with glucose conversion of 98% was obtained in (CrCl₃×6H₂O+Amberlyst-38+KBr)(aq)-GVL system in 3 minutes that is, up to now, the best HMF yield obtained from glucose in aqueous systems.^[4] As with fructose, levulinic acid was detected only in trace amounts (<1%), which is remarkably low if compared to biphasic systems with similar glucose conversions under conventional heating, wherein 5-10% of levulinic acid is typically produced.^[17, 35a] Notably, without strong Brønsted acid catalyst (0.05 M HCl or Amberlyst-38) lower HMF yield of 65% from glucose with CrCl₃×6H₂O was obtained (the dehydration step proceeds because of the intrinsic Brønsted acidity of CrCl₃×6H₂O in aqueous solutions, entry 10 vs 11). Recently, it was reported that additional strong mineral acids affect the CrCl₃×6H₂O catalyzed glucose dehydration to HMF under conventional oil-bath heating at

140 °C by significantly decelerating glucose-to-fructose isomerization.^[17, 35a] This was ascribed to the restrained formation of the chromium–glucose chelate complex with increasing acidity, leading to the change in the rate-determining step from fructose dehydration to glucose-to-fructose isomerization.^[17] The strong retardation of the glucose-to-fructose isomerization, arising from the presence of Brønsted acid, resulted in lower substrate conversions, HMF selectivity and yield. According to our results, this tendency can be avoided by conducting the reaction rapidly at high temperature under MW irradiation.

We also studied the (Amberlyst-38+KBr)_(aq)-GVL catalytic system for the dehydration of mannose, various disaccharides (lactose, cellobiose and sucrose) and polysaccharides (inulin and cellulose) with or without $CrCl_3 \times 6H_2O$ additive, depending on the carbohydrate constituent (Table 3).

Table 3. The results of dehydration of various carbohydrates with Amberlyst-38 (wet) catalysts in KBr_{aq}-GVL biphasic system.^{[a]}

Entry	Carbohydrate	Time (min)	HMF Yield (%)
1	Mannose + CrCl ₃ ×6H ₂ O	3	69
2	Lactose + CrCl ₃ ×6H ₂ O	3	55
3	Cellobiose + CrCl ₃ ×6H ₂ O	3	71
4 ^[b]	Cellobiose + CrCl ₃ ×6H ₂ O	3	67
5	Sucrose + CrCl ₃ ×6H ₂ O	3	77
6 ^[c]	Sucrose	3	49
7	Inulin	1	80
8 ^[d]	MC Cellulose + CrCl ₃ ×6H ₂ O	3	40

[a] Reaction conditions: 10 mol% CrCl₃×6H₂O, 21mg Ambelyst-38(wet) and 150 mg of carbohydrate in KBr_(aq)-GVL 1:2 v/v, MW 160°C, 1-3 min. [b] MeCN as organic phase. [c] 38% glucose remaining after the reaction [d] T=175 °C.

HMF yields with disaccharides were only slightly lower than those of glucose under the same reaction conditions, showing that no additional strong Brønsted acid along with Amberlyst-38(wet) was necessary to promote the hydrolysis of the glycosidic linkage of disaccharides. The system worked notably well with cellobiose and inulin leading to good HMF yields of 71% and 80%, respectively. Additionally, the reaction with sucrose together with CrCl₃×6H₂O gave HMF in 77% yield. As expected, the absence of an isomerization catalyst reduced the HMF yield to 49%. With cellulose as a substrate an elevated temperature of 175 °C was necessary for efficient depolymerization to obtain reasonable HMF yield of 40%.

Conclusions

We have studied several aqueous biphasic systems to efficiently promote the fructose dehydration to HMF under MW irradiation. In comparison to conventional heating, a short-term reaction implementing microwaves was more efficient by greatly reducing the reaction time and consequently, the formation of by-products, especially levulinic acid, leading to higher HMF selectivity and yield. Particularly, the use of bromide salts in aqueous phase and

DOI: 10.1039/C5RA25564C Journal Name

ARTICLE

common organic solvent MeCN or lignocellulose-derived GVL as an organic extractive phase were highly advantageous resulting in excellent HMF yields of up to 91% with catalytic amount of HCl (9 mol-%) as acid catalyst. Only small decrease in HMF yield occurred when Amberlyst-38(wet) catalyst was applied in the system. Also, the reaction was scalable up to fructose concentration of 50 wt% with only small decrease in HMF selectivity.

In contrast to fructose dehydration, the biphasic system with added isomerization catalyst performed better with glucose when GVL and Amberlyst-38(wet) were used in place of MeCN and HCl, resulting in very good HMF yield of 74%. The high HMF yield from glucose was ascribed to microwave heating, which promoted the Lewis acid-catalyzed glucose dehydration overcoming the rate-determining glucose-to-fructose bv equilibrium barrier, arising from the presence of additional Brønsted acid to enhance the fructose dehydration step. Additionally, this method proved efficient in one-pot cascade hydrolysis-isomerization-dehydration process to produce HMF from disaccharides without additional strong Brønsted acids, and could be applied to more complex carbohydrates such as cellulose. In terms of HMF yields the reported results are, to our knowledge, the best fructose and glucose dehydration results achieved in mono or biphasic aqueous media, and comparable to the best of those obtained in high-boiling organic solvents and ionic liquids.^[4]

Experimental

General Experimental Details

All solvents, carbohydrates, $CrCl_3 \times 6H_2O$, $AlCl_3 \times 6H_2O$, boric acid and sodium borate were purchased from Acros Organics or Sigma-Aldrich and were used as received, except THF which was dried by VAC solvent purification system (Vacuum Atmosphere Systems).

HMF, glucose and fructose yields were determined with High Pressure Liquid Chromatography (HPLC). HPLC runs were performed using Agilent 1200 HPLC system equipped with a Phenomenex Rezex ROA ($300 \times 7.8 \text{ mm}$) column. Sulfuric acid (0.25 mM) in water was used as an eluent at 40 °C with a flow rate 0.35 ml/min. HMF was detected using UV-detector, whereas fructose and glucose were analyzed using refractive index (RID) detector. The exact yields were calculated from calibration curves prepared for all the compounds from commercially available reagents using six different concentrations.

All the reactions were carried out in 2-5 ml glass vials using a Biotage Initiator microwave reactor (2.45 GHz magnetron). The instrument uses one IR sensor to measure temperature of the reaction mixture and adjusts the heating power accordingly. The absorption level was set to "very high" and the reaction mixture was stirred with magnetic stirring at 600 rpm. In all reactions the heating from r.t. to 160 °C took 80 sec, after which the desired reaction time was measured.

General procedure for the fructose dehydration experiments in $salt_{(aq)}/organic solvent$ biphasic systems

To a 2-5 ml microwave vial with a magnetic stirring bar containing fructose (0.15g, 0.83 mmol) was added 1.5 mL of aqueous saturated salt solution (NaCl, NaBr, KCl, KBr, Nal, KI, KF, NH₄Cl, NH₄Br or NH₄l containing the required amount of acid). After dissolution of fructose, desired organic solvent (3 mL) was added, the vial was closed with aluminum/silicone crimp cap and the biphasic solution was heated at 160 °C in the microwave reactor (Biotage Initiator) or in preheated the oil-bath (160 °C) if used. After required time, the vial was immediately cooled down to room temperature and water added to make a total volume of 50 mL. HMF yield and fructose conversion were determined from this solution by HPLC analysis (1:4 dilution with water, 1mL).

All MW reactions were performed using synthesis platform (Chemspeed SLT106 Swing Synthesizer) equipped with microwave reactor (Biotage Initiator).

Glucose dehydration in biphasic KBr(aq)-GVL/MeCN/THF system with Isomerization and, Amberlyst-38 (wet) or HCl catalyst

To a 2-5 ml microwave vial with a magnetic stirring bar containing glucose (0.15g, 0.83 mmol), 21 mg Amberlyst-38(wet) and 10 mol% of required isomerization catalyst (CrCl₃×6H₂O, AlCl₃×6H₂O, boric acid or sodium borate) were added 1.5 mL of aqueous saturated KBr solution. After dissolution of glucose, GVL, THF or MeCN (3 mL) was added, the vial was closed with aluminum/silicone crimp cap and the biphasic solution was heated at 160 °C in the microwave reactor (Biotage Initiator). After required time (1-4 min), the vial was immediately cooled down to room temperature and water added to make a total volume of 50 mL. HMF yield and glucose conversion were determined from this solution by HPLC analysis (1:4 dilution with water, 1mL). All reactions were performed using synthesis platform (Chemspeed SLT106 Swing Synthesizer) equipped with microwave reactor (Biotage Initiator).

Dehydration of disaccharides and polysaccharides in biphasic (Amberlyst-38-KBr)_(aq)-GVL system

To a 2-5 ml microwave vial with magnetic stirring bar containing the desired carbohydrate (0.15 g), 21 mg Amberlyst-38(wet) and 10 mol% of $CrCl_3 \times 6H_2$) were added 1.5 mL of aqueous saturated KBr solution. Then GVL was added, the vial closed with aluminum/silicone crimp cap and heated at 160 °C in the microwave reactor (Biotage Initiator). After required time (1-3 min), the vial was immediately cooled down to room temperature and water added to make a total volume of 50 mL. HMF yield and glucose conversion were determined from this solution by HPLC analysis (1:4 dilution with water, 1mL).

Acknowledgements

Funding from Magnus Ehrnrooth Foundation and TEKES (the Finnish Funding Agency for Technology and Innovation) is gratefully acknowledged.

Notes and references

 A. J. Ragauskas, C. K. Williams, B. H. Davison, G. Britovsek, J. Cairney, C. A. Eckert, W. J. Frederick, J. P. Hallett, D. J. Journal Name

[2]

Leak, C. L. Liotta, J. R. Mielenz, R. Murphy, R. Templer, T. Tschaplinski, *Science* **2006**, *311*, 484-489.

- J. J. Bozell, G. R. Petersen, Green Chem 2010, 12, 539-554. [27]
- [3] Y. Roman-Leshkov, C. J. Barrett, Z. Y. Liu, J. A. Dumesic, *Nature* 2007, 447, 982-985.
- [4] aR. J. van Putten, J. C. van der Waal, E. de Jong, C. B.
 Rasrendra, H. J. Heeres, J. G. de Vries, *Chem Rev* 2013, 113, 1499-1597; bT. Wang, M. W. Nolte, B. H. Shanks, *Green Chem* 2014, 16, 548-572.
- J. B. Binder, R. T. Raines, J Am Chem Soc 2009, 131, 1979-1985.
- [6] aZ. Huang, W. Pan, H. Zhou, F. Qin, H. Xu, W. Shen, *Chemsuschem* **2013**, *6*, 1063-1069; bC. Aellig, I. Hermans, *Chemsuschem* **2012**, *5*, 1737-1742.
- S. Dutta, S. De, A. K. Patra, M. Sasidharan, A. Bhaumik, B.
 Saha, Applied Catalysis A: General 2011, 409–410, 133-139.
- [8] C. Moreau, R. Durand, S. Razigade, J. Duhamet, P. Faugeras, P. Rivalier, P. Ros, G. Avignon, *Applied Catalysis* A: General **1996**, 145, 211-224.
- [9] M. E. Zakrzewska, E. Bogel-Łukasik, R. Bogel-Łukasik, Chem Rev 2010, 111, 397-417.
- [10] R. M. Musau, R. M. Munavu, *Biomass* 1987, 13, 67-74.
- [11] C. Lansalot-Matras, C. Moreau, *Catal Commun* 2003, 4, 517-520.
- [12] B. Girisuta, L. P. B. M. Janssen, H. J. Heeres, Green Chem 2006, 8, 701-709.
- P. Rivalier, J. Duhamet, C. Moreau, R. Durand, *Catal Today* 1995, 24, 165-171.
- [14] A. J. Crisci, M. H. Tucker, M.-Y. Lee, S. G. Jang, J. A. Dumesic, S. L. Scott, Acs Catal 2011, 1, 719-728.
- [15] Y. Román-Leshkov, J. N. Chheda, J. A. Dumesic, Science 2006, 312, 1933-1937.
- [16] J. N. Chheda, J. A. Dumesic, Catal Today 2007, 123, 59-70.
- [17] P. Wrigstedt, J. Keskiväli, M. Leskelä, T. Repo, Chemcatchem 2015, 7, 501-507.
- [18] T. S. Hansen, J. Mielby, A. Riisager, Green Chem 2011, 13, 109-114.
- [19] Q. Cao, X. Guo, J. Guan, X. Mu, D. Zhang, Applied Catalysis A: General 2011, 403, 98-103.
- [20] T. Okano, K. Qiao, Q. Bao, D. Tomida, H. Hagiwara, C. Yokoyama, Applied Catalysis A: General 2013, 451, 1-5.
- [21] aC. O. Kappe, Chem Soc Rev 2008, 37, 1127-1139; bC. R.
 Strauss, D. W. Rooney, Green Chem 2010, 12, 1340-1344.
- [22] aT. S. Hansen, J. M. Woodley, A. Riisager, *Carbohydrate research* 2009, 344, 2568-2572; bX. Qi, M. Watanabe, T. M. Aida, J. R. L. Smith, *Green Chem* 2008, 10, 799-805; cJ. H. Lu, Y. N. Yan, Y. H. Zhang, Y. Tang, *Rsc Adv* 2012, 2, 7652-7655.
- [23] S. De, S. Dutta, B. Saha, Green Chem **2011**, *13*, 2859-2868.
- [24] aJ. B. Binder, A. V. Cefali, J. J. Blank, R. T. Raines, *Energy & Environmental Science* 2010, *3*, 765-771; bC. Wang, L. Fu, X. Tong, Q. Yang, W. Zhang, *Carbohydrate research* 2012, 347, 182-185.
- [25] Y. Roman-Leshkov, J. A. Dumesic, *Top Catal* **2009**, *52*, 297-303.
- [26] aJ. S. Luterbacher, J. M. Rand, D. M. Alonso, J. Han, J. T. Youngquist, C. T. Maravelias, B. F. Pfleger, J. A. Dumesic, *Science* 2014, 343, 277-280; bM. A. Mellmer, C. Sener, J. M. R. Gallo, J. S. Luterbacher, D. M. Alonso, J. A. Dumesic, *Angewandte Chemie International Edition* 2014, 53, 11872-11875; cE. I. Gürbüz, J. M. R. Gallo, D. M. Alonso, S.

G. Wettstein, W. Y. Lim, J. A. Dumesic, *Angewandte Chemie International Edition* **2013**, *52*, 1270-1274.

- J. D. Moseley, E. K. Woodman, *Energ Fuel* **2009**, *23*, 5438-5447.
- [28] R. Morschhauser, M. Krull, C. Kayser, C. Boberski, R. Bierbaum, P. A. Puschner, T. N. Glasnov, C. O. Kappe, *Green Process Synth* **2012**, *1*, 281-290.
- [29] B. L. Hayes, Microwave synthesis : chemistry at the speed of light, CEM Pub., Matthews, NC, 2002.
- [30] X. Qi, M. Watanabe, T. M. Aida, R. L. Smith Jr, Catal Commun 2008, 9, 2244-2249.
- [31] aD. J. Braden, C. A. Henao, J. Heltzel, C. C. Maravelias, J. A. Dumesic, Green Chem 2011, 13, 1755-1765; bA. Aden, T. Foust, Cellulose 2009, 16, 535-545.
- [32] aM. Iannelli, F. Bergamelli, C. M. Kormos, S. Paravisi, N. E.
 Leadbeater, Org Process Res Dev 2009, 13, 634-637; bT.
 Razzaq, C. O. Kappe, Chemsuschem 2008, 1, 123-132; cl.
 D. Moseley, C. O. Kappe, Green Chem 2011, 13, 794-806.
- [33] H. B. Zhao, J. E. Holladay, H. Brown, Z. C. Zhang, *Science* 2007, *316*, 1597-1600.
- [34] T. Stahlberg, S. Rodriguez-Rodriguez, P. Fristrup, A. Riisager, Chem-Eur J 2011, 17, 1456-1464.
- [35] aV. Choudhary, S. H. Mushrif, C. Ho, A. Anderko, V. Nikolakis, N. S. Marinkovic, A. I. Frenkel, S. I. Sandler, D. G. Vlachos, J Am Chem Soc 2013, 135, 3997-4006; bV. Choudhary, A. B. Pinar, R. F. Lobo, D. G. Vlachos, S. I. Sandler, Chemsuschem 2013, 6, 2369-2376.
- [36] aY. J. Pagan-Torres, T. F. Wang, J. M. R. Gallo, B. H. Shanks, J. A. Dumesic, Acs Catal 2012, 2, 930-934; bY. Yang, C. W. Hu, M. M. Abu-Omar, J Mol Catal a-Chem 2013, 376, 98-102.



1 to 3 minutes