



Accepted Article

Title: Incorporation of Ti as a pyramidal framework site in the monolayered MCM-56 zeolite and its oxidation activity

Authors: Aleksandra Korzeniowska, Justyna Grzybek, Wieslaw J. Roth, Andrzej Kowalczyk, Piotr Michorczyk, Jiři Čejka, Jan Přech, and Barbara Gil

This manuscript has been accepted after peer review and appears as an Accepted Article online prior to editing, proofing, and formal publication of the final Version of Record (VoR). This work is currently citable by using the Digital Object Identifier (DOI) given below. The VoR will be published online in Early View as soon as possible and may be different to this Accepted Article as a result of editing. Readers should obtain the VoR from the journal website shown below when it is published to ensure accuracy of information. The authors are responsible for the content of this Accepted Article.

To be cited as: ChemCatChem 10.1002/cctc.201800981

Link to VoR: http://dx.doi.org/10.1002/cctc.201800981



WILEY-VCH

www.chemcatchem.org

FULL PAPER

Incorporation of Ti as a pyramidal framework site in the monolayered MCM-56 zeolite and its oxidation activity

Aleksandra Korzeniowska^[a], Justyna Grzybek^[a], Wieslaw J. Roth^[a], Andrzej Kowalczyk^[a], Piotr Michorczyk^[b], Jiři Čejka^[c,d], Jan Přech^[d], and Barbara Gil*^[a]

Abstract: MWW zeolite MCM-56 with Al atoms on the surface was functionalized with Ti to produce pyramidal TiOH groups. This was carried out by removal of AI with nitric acid, calcination and treatment with Ti(acac)₂O(i-propoxide)₂. Up to 0.7% Ti was introduced. Using UV-Vis three types of Ti moieties were identified in uncalcined materials - tetrahedral in the framework, 5/6-coordinated Ti on the surface, presumably in the vacated pyramidal sites, and oxide-like clusters. The presence of TiOH on the surface was indicated by in situ measurement of UV-Vis spectra during calcination. It showed the band at 290 nm, which disappeared at 500 °C, perhaps due to condensation with silanols. Catalytic oxidation tests were carried out with three samples containing 0.13, 0.36, and 0.70% Ti and methylphenyl sulphide and cis-cyclooctene as model reactants. The study confirmed potential of the TiOH moieties in oxidation catalysis although their final form is not certain. Future studies will include increasing Ti content to enhance catalytic activity and better detection of this type of the Ti site.

Introduction

The premise of this work was to take advantage of the unique pyramidal site in the zeolite framework MWW, located on the external surface, for the purpose of functionalization with Ti atoms and possible generation of oxidation activity. These sites are usually occupied by Si-OH groups but in the high Al-form, MCM-56, they are assumed to show high concentration of Al.^[1] The idea was to extract these Al atoms and replace with Ti.

Isolated Ti atoms incorporated in microporous zeolite frameworks are highly efficient as selective oxidation catalysts for various organic reactants.^[2] Zeolite Ti-MFI, designated TS-1,^[3] showed

[a]	Prof. Dr. W.J. Roth, MSc J. Grzybek, MSc A. Korzeniowska,
	MSc A. Kowalczyk, Dr. B. Gil*
	Faculty of Chemistry, Jagiellonian University
	Gronostajowa 2, 30-397 Kraków, Poland
	E-mail: gil@chemia.uj.edu.pl
[b]	Dr. P. Michorczyk
	Faculty of Chemical Engineering and Technology,
	Cracow University of Technology,
	Warszawska 24, 31-155 Kraków, Poland
[c]	Prof. Dr. J. Čejka
	J. Heyrovský Institute of Physical Chemistry,
	Academy of Sciences of the Czech Republic, v.v.i.,
	Dolejškova 2155/3, 182 23 Prague 8, Czech Republic
[d]	Dr. J. Přech
	Department of Physical and Macromolecular Chemistry,
	Faculty of Science, Charles University
	Hlavova 8, 128 43 Prague 2, Czech Republic

exceptional catalytic activity in oxidations with hydrogen peroxide leading to many efforts to generate Ti sites in other frameworks. The key to obtaining good catalysts is the synthesis itself because the capacity for incorporation of Ti into a framework may be adversely affected by various factors and guite often a separated titania phase has been obtained.^[4] Admittedly, very reliable procedures have been developed for preparation of various Tizeolites but alternative approaches have been constantly pursued.^[2b, 5] One example is the exploitation of 2-dimensional (2D) zeolites in various layered forms which are attractive for postsynthesis modifications such as structural expansion and topotactic chemical change.^[6] Framework MWW has been synthesized with Ti as both 3D and 2D forms showing promising catalytic performances.^[7] One of the 2D MWW forms, designated MCM-56, appears to have a unique feature, namely pyramidal AI atoms on the surface of monolayers as shown in Fig 1. The equivalent SiOH sites, which are believed to populate MWW with higher Si/AI are shown for comparison. These sites can be exploited for insertion of isolated hetero-atoms such as Ti by generation of vacancies in the framework, e.g. by acid extractions of AI, and subsequent metal atom incorporation.^[8] Herein, we present results of the study to activate MCM-56 with Ti by this method and describe characterizations to elucidate nature of the incorporated Ti species including catalytic testing.

There are several different forms of Ti species that can be formed upon post-synthesis treatment of zeolites^[9] – from the most desired framework substituted atoms, through different forms of oxo- or hydroxo- species formed upon hydrolysis of Ti precursors and their consecutive calcination, to a separate phase of TiO_2 , usually identified as anatase.



Figure. 1. Formation of the Al-vacancy and pyramidal Ti site from pyramidal Al site upon acid treatment followed by reaction with $Ti(acac)_2OiPr_2$

In the case of the aforementioned highly valued TS-1 catalyst, synthesized first by the ENI Group, a specific form of the framework titanium, called a 'closed site', is claimed to be the active centre for catalytic reactions. It is a Ti atom coordinated by four oxygen atoms with no hydrogen attached to any of them. If an OH group is formed, the site is called 'open site' and is considered to be a structural defect, lowering performance of the catalyst.^[10] For the TS-1 structure, the amount of closed sites is

FULL PAPER

limited and the Ti/(Ti+Si) ratio is usually not greater than 0.025 (Si/Ti around 40). $^{[11]}$

Both of these forms of Ti sites can be formed in the MWW zeolite but, as mentioned, this framework contains a special T-site located only at the external surface of the MWW layers. It can produce pyramidal Ti centre, not as defect (cf. Fig. 1). It was suggested^[7] that this form may not be stable and convert upon heating into extraframework TiO₂ clusters, which are generally not desirable for oxidation reactions because they decompose H₂O₂. We can assume, based on our previous work on the incorporation of Ce into the MWW framework,^[12] that these pyramidal sites may be preferentially occupied by Ti, since the Ti⁴⁺ cation is much bigger than Si⁴⁺ so it is more likely that it will be located at the external surfaces of the layers than in the more constrained internal parts of the framework.

In this work Ti-MWW zeolites were obtained by the treatment of MCM-56 with concentrated nitric acid to create vacancies through dealumination, followed by treatments with soluble Ti-compounds. Uncalcined MCM-56 was used as the starting material. This way the template protected inside of the micropore structure and the vacancies could be formed preferentially on the external surfaces of the layers. It was expected that Al atoms populating the pyramidal centres would be extracted and subsequently replaced with Ti, thus predominantly forming the pyramidal Ti-atoms. The stability of incorporated Ti-sites was examined both in thermal and acid-leaching treatments.

Results and Discussion

The goal of this study was substitution of Ti atoms into the unique pyramidal position on the surface of the framework MWW after dealumination of MCM-56 by contacting with nitric acid. The obtained products were characterized to determine basic properties and nature of the Ti centres including catalytic oxidation. To that effect the evaluated characteristics included preservation of zeolite structure by X-ray powder diffraction (XRD), porosity by nitrogen sorption, concentration of acid sites by FTIR, nature of Ti sites by UV-Vis and, finally, catalytic activity in model reactions – oxidation of methylphenyl sulphide (MPS) and ciscyclooctene by H_2O_2 .

Sample pretreatment - dealumination and Ti-insertion

The starting MCM-56 consisting primarily of individual MWW mono-layers was used in as-synthesized form, containing the hexamethyleneimine (HMI) template. It was first treated with concentrated nitric acid for 4 hours at room temperature. The organic template (HMI) was expected to protect the framework AI atoms inside micropores and inhibit their extraction. At the same time the external AI atoms, especially those in the pyramidal positions were expected to be removed preferentially. Both XRD patterns shown in Fig. 2 and textural properties listed in Table 1 show very little difference before and after treatment with regard to apparent structure and pore characteristics. XRF results (Table 1) show an increase in the Si/AI ratio from 10 to 15/1, consistent

with only partial removal of Al atoms. The BAS concentrations also indicate that approximately 1/3 of Al initially present was extracted. The introduction of Ti was carried out after calcination of the acid treated sample by contacting with $Ti(acac)_2OiPr_2$ solutions in isopropanol of different concentrations (0.01 and 0.001 M for 1 hour, respectively). This gave products containing 0.70 wt.% of Ti (molar Ti:(Si+Al) equal to 1:110) designated Ti-MCM-56_0.70) and 0.36 wt% of Ti (Ti-MCM-56_0.36). Part of the 0.70% Ti material was additionally treated after calcination with concentrated HNO₃, which reduced the amount of Ti to 0.13% present only, according to UV-Vis, in tetrahedral coordination (vide infra).



Scheme 1 Scheme of MCM-56 zeolite modifications

XRD patterns confirmed structure preservation both of the framework and the initial layer disorder. Regarding the latter, there was a slight depression in the diagnostic band between 8- 10° 20, indicating some lateral ordering and possibly slight condensation of the layers.^[13]



Figure 2. XRD patterns of the starting, dealuminated and Ti-treated MCM-56 zeolites in uncalcined form.

FULL PAPER

Sample	Ti, wt.%	Si/Al (XRF)	Si/Ti (XRF)	BET, m² g⁻¹	S _{ext} , m ² g ⁻¹	V _{micro} , cm ³ g ⁻¹	BAS µmol g ⁻¹	LAS, µmol g ⁻¹
MCM-56	-	10	-	426	154	0.084	649	122
MCM-56_dealuminated	-	15	-	382	145	0.063	428	74
TiMCM-56_0.70	0.70	15	100	365	148	0.062	221	67
TiMCM-56_0.36	0.36	15	257	425	179	0.081	371	97
TiMCM-56_0.13	0.13	16	525	360	171	0.056	150	32

Table 1. Composition and basic properties of the starting, dealuminated, and Ti-treated MCM-56 zeolites

The evaluation of textural properties by low-temperature nitrogen adsorption showed that dealumination did not produce change in the shape of isotherms (Fig. 3), which had small hysteresis loops that may be assigned to intercrystalline, slit-like mesopores frequently observed for layered materials. There was slight decrease of BET surface area after dealumination from 426 to 380 m² g⁻¹ for treated samples and some decrease in the micropore volume, from 0.084 to 0.063 cm³ g⁻¹.

framework degradation, e.g. through breaking of Si-O-Si bonds. The band at 3615 cm⁻¹, characteristic of Si-OH-AI groups synonymous with strong Brønsted acid sites (BAS) shows lower intensity for all treated samples. This is confirmed by the BAS concentration of ca. 450 μ mol g⁻¹, measured by pyridine desorption.



Ti-MCM-56_0.13 Ti-MCM-56_0.36 Ti-MCM-56_0.70 MCM-56_dealuminated MCM-56 3800 3700 3600 3500 3400

Figure 4. IR spectra of OH groups of the starting, dealuminated and Ti-treated MCM-56 zeolites

Figure 3. Nitrogen adsorption isotherms for parent, dealuminated and Ti-forms of MCM-56 zeolites. Isotherms are shifted to allow better visualization of their shape.

The above XRD patterns and N₂ adsorption isotherms indicated small changes in the structure due to acid treatment/dealumination but FTIR revealed more significant changes in the chemical nature of the products (Fig. 4). In general, for dealuminated samples, the intensity of silanol groups increased considerably, especially the hydrogen-bonded ones (IR maximum at ca. 3730 cm⁻¹). The background in the whole OH region is elevated, suggesting greater number of defects or partial

Characterization and nature of Ti

To obtain some variation of Ti content different amounts of the Ti source were applied (cf. scheme 1). A nominally monomeric titanium compound was used, diluted solution of Ti(acac)₂OiPr₂ in isopropanol (iPr = iso-propanol), to lower the formation of multicentre Ti sites. No TiO₂ crystallites of the sizes that can be detected with XRD were observed before and after calcination, (patterns in the range 30-70° 20, not shown). Concentration of BAS decreased after Ti incorporation by about 50% for 0.7% Ti but less than 20 % for 0.36% Ti.

FULL PAPER

In the literature, the presence of a band at 960 cm⁻¹ in the IR spectral region of skeletal vibrations of titanosilicates/ titanozeolites is assigned to tetrahedral Ti⁴⁺ sites^[11] and could be used for its detection. However, as pointed out by Perego et al.,^[3c] Ti-free silicates or high surface area silicas have an absorption in this range as well, due to surface silanols. In our case, the dealuminated zeolites also have an absorption band in this region apparently because of having high silanol concentration. As a result, FTIR after the Ti treatment cannot verify the presence or absence of the framework four-coordinated Ti⁴⁺ (Fig. 5).



Figure 5. IR spectra of the skeletal vibrations of dealuminated and Ti-modified MCM-56 zeolites. The spectra are normalized to the same intensity of the 800 cm^{-1} maximum (bending vibrations of T-O bonds inside tetrahedra).

The most important aspect of the metal incorporation is the nature and quantity of different Ti-species that have been formed. The studied samples showed three different types of bands by DR-UV-Vis, with different intensities changing before and after calcination (bands at 210, 290 and 330 nm). Zecchina et al.^[4] and Wu et al.^[14] assigned the band at 210-220 nm to tetrahedrally coordinated framework Ti(OSi)₄ 'closed sites'. They are highly desirable and very active for oxidation. The absorption between 260 and 300 nm is characteristic of 5- and 6-coordinated extraframework titanium species^[15] and/or partially framework TiOOH species (analogous to the AIOOH groups in boehmite).^[16] This band is also present in the MFI TS-1B material, synthesized by Balducci et al.^[17] or TS-1+ zeolite synthesized by L. Wu et al.^[18] It was suggested by Wu et al.^[7] and Liu et al.^[19] that this band is characteristic of Ti forming octahedrally coordinated species on the external surface of the layers and identified as 'open sites'. The pyramidal Ti-OH species that might form on the MCM-56/MWW layer should give rise to the maximum at the same region, since its coordination would be very similar to any of such 'open sites'. The absorption above 300 nm, in the case of Ti-MCM-56 zeolites at 330 nm, is characteristic for anatase-related TiO₂ phase,^[20] which is generally undesired.



Figure 6. DR-UV-Vis spectra of Ti-MCM-56 zeolites recorded before calcination (non-calc), after calcination and exposure to air for several days (calc) and after treatment in pure O_2 at 500 °C (oxidized). The spectra are vertically offset for better visibility.

The spectrum of uncalcined sample with the highest Ti amount, i.e. 0.70%, is dominated by the maximum at 290 nm, which indicates substantial insertion into vacated Al sites as TiOH or its precursors. This was examined further by in situ calcination discussed later. Both samples that were reacted with Ti compounds contain a TiO₂ phase indicated by the shoulders above 300 nm in UV-Vis. They are presumably present as small clusters rather than distinct anatase crystallites, since they have not been detected by XRD. The UV-Vis spectra and accordingly the nature of Ti-species changed dramatically upon calcination (as discussed above, FTIR spectra in the skeletal vibration range cannot confirm unequivocally the nature of Ti inserted in zeolite frameworks).



Figure 7. DR-UV-Vis spectra of Ti-MCM-56 zeolites during in situ calcination from 50 to 500 $^\circ C$, step 50 $^\circ C$ (from bottom to top).

The changing nature of Ti in MWW due to calcination was monitored by performing calcination in situ in an UV-Vis spectrometer (Fig. 7). The signal at 290 nm became more intense initially, reaching maximum around 250 $^{\circ}$ C but then gradually disappeared at the highest calcination temperature (500 $^{\circ}$ C). This

FULL PAPER

Table 2. Conversion (X) and yield (y) of the products for oxidation of methylphenyl sulphide (MPS) and epoxidation of ciscyclooctene over the Ti-MCM-56 catalysts.

Catalyst	Substrate	Time	conversion [%]			
		[11111]		sulphoxide	sulphone	cyclooctene oxide
Ti-MCM-56_0.70	Methyl Phenyl Sulphide	120	41	35	9	
Ti-MCM-56_0.36	Methyl Phenyl Sulphide	120	29	25	5	
Ti-MCM-56_0.13	Methyl Phenyl Sulphide	120	20	18	1	-
Ti-MCM-56_0.70	cis-Cyclooctene	240	12	-	-	5
Ti-MCM-56_0.36	cis-Cyclooctene	240	9	-	-	4
Ti-MCM-56_0.13	cis-Cyclooctene	240	2	-	-	2

behavior is interpreted as associated with pyramidal Ti-sites, which may be at first coordinated by water molecules and alkoxy ligands in addition to their own OH group, thus having expanded 5- or 6-coordination sphere. Heating should cause dehydration and dehydroxylation of such species producing change in the coordination sphere and increasing tetrahedral Ti-OH population. Subsequently the 290 nm peak starts to diminish and ultimately becomes rather weak. The 330 nm band also disappears at higher temperature and the only detectable Ti moieties by UV-Vis are tetrahedral, which indicates the pyramidal Ti-sites do not form TiO₂ during calcination, which is different from the earlier proposal.^[7] It is most probable that the species with the 290 nm band convert eventually into closed tetrahedral sites as they are the only ones visible in the 'working catalyst', i.e. the one activated before catalytic reaction It is not certain how this change in Ti environment takes place but one possibility is condensation with SiOH on adjacent layers.

Additional effect at higher temperatures is the appearance of new bands in the range 395-450 nm. They are assigned to coke being formed upon decomposition of the deposited Ti moieties with residual acac or i-propanol groups. The calcination is carried out in this experiment in an inert gas flow or under vacuum and this may promote coke deposits since there is no oxygen for the combustion of organic residue. In the literature several corresponding UV-Vis signals have been reported,^[21] and all of the bands visible in the spectra presented in Fig. 6 with wavenumbers above 350 nm may be attributed to coke. Additionally, the sample with higher concentration of Ti (Ti-MCM-56_0.7) was, after vacuum activation to 500 °C, exposed to pure oxygen, and this resulted in removal of the coke (confirmed by IR) and disappearance of the 395-450 nm UV-Vis bands.

An additional piece of evidence that in the calcined samples, Ti⁴⁺ cations are incorporated in the zeolite framework is provided by the concentration of Lewis acid sites measured by pyridine adsorption. It did not change after Ti incorporation and according to Zecchina et al.^[22] Lewis acidity cannot be associated with framework Ti⁴⁺ ions. Tetrahedrally coordinated Ti⁴⁺ cations bear no charge and are coordinatively saturated thus cannot interact with pyridine as Lewis acid sites. Extraframework titanium (in the

form of single sites or TiO_2 clusters) may be coordinatively unsaturated thus can act as a Lewis acid site and increase their concentration. In other words if Ti had ended outside the framework it would have increased the concentration of Lewis sites.

An additional transformation was carried out and it involved treatment of Ti-MCM-56_0.7 with acid. It resulted in disappearance of the 290 and >330 absorption and only the Ti(OSi)₄ tetrahedral sites remained (measured concentration 0.13%). As a result, the overall catalytic ability was reduced but produced more favourable selectivity in the oxidation of ciscyclooctene.

Oxidation of methyl phenyl sulphide and cis-cyclooctene epoxidation

The obtained Ti-MWW catalysts were tested in oxidation of methylphenyl sulphide (MPS) and cyclooctene with aqueous hydrogen peroxide in acetonitrile at 30 °C (MPS) and 60 °C (cyclooctene). The former was chosen because it is one of the most common model compounds to study oxidation of organic sulphides. A blank experiment without the catalyst confirmed slow reaction under the experimental conditions (2.5% conversion after 120 min). Consequently, the observed increased conversions can be attributed to the presence of catalysts. The maximum theoretical conversion is 50% under the applied conditions.^[5b] The main product in the sulfoxidation reaction was methyl phenyl sulphoxide and only a small amount of methyl phenyl sulphone was formed (up to about 20% of the combined product amount). The activity of samples, in terms of the substrate conversion, increase with the total amount of incorporated Ti-species: 41% for the catalyst having 0.70 wt.% of Ti, 25% for 0.36 wt.% of Ti and 18% for 0.13 wt.% of Ti. It is not possible to tell how much different Ti forms contribute to this activity but the tetrahedral sites (220 nm UV peak) seem to be particularly active - the last materials with 0.13% Ti shows only 2 times lower conversion in comparison to the most active material with 5 times higher Ti content. Conversion of methyl phenyl sulphoxide vs time on stream is presented in Fig. 8. The product yields show similar profiles (not

FULL PAPER

included for brevity) indicating that oxidation to sulfone is harder than the first step to sulfoxide.



Figure 8. Conversion vs. time on stream for methyl phenyl sulphide and cyclooctene oxidation with H_2O_2 over Ti-MCM-56 zeolites.

In the case of epoxidation of cyclooctene, the conversion and Ti content are proportional for the two extreme concentration - 12 and 2% conversions for 0.7 and 0.13% Ti. The middle one with 9% conversion is closer to the most active. This may be because in this reaction, the substrate (cis-cyclooctene) and the main product (cyclooctene oxide) are relatively big so it is expected that the reaction may proceed mainly at the external surfaces of the MWW layers. For that reason, even if the concentration of titanium drops by half, it is mostly retained on the surface so the conversion dropped only from 12 to 9%. For acid-leached sample, where apparently only tetrahedral sites, located inside the micropores are present, the conversion drops to 2%. At the same time Ti-MCM-56_0.13 seems to show better selectivity but it may be only due to low overall conversion with uncertain measurement error. The described catalytic tests confirm that the synthesized Ti-MCM-56 materials are active in oxidation reactions, which is especially evidenced by the increasing conversion with Ti content. The latter effect (relative increase) seems to depend on the reactant being oxidized. This can be seen with Ti-MCM-56_0.13, which is relatively more active in MPS oxidation in comparison to the more Ti-rich catalysts but with cis-cyclooctene shows comparable conversion-to-Ti ratio to Ti-MCM-56_0.7.

The most likely mechanism in these reactions should be the same as the standard titanosilicate catalysed oxidations, which are rather well elucidated.^[23] In this mechanism titanium atoms activate coordinated H₂O₂ by withdrawing electrons from the O-O bond making it more susceptible to nucleophilic attack by a substrate, which leads to its oxidation. The mechanism is believed to be of the Rideal-Eley type and is not dependent on substrate adsorption on the catalyst.^[24]

Conclusions

The high Al version of zeolite MWW, MCM-56, was treated with nitric acid and lost about 1/3 of its Al preferentially from the surface where they were not protected by the SDA molecules. The values of Si/Al ratio changed from 10/1 to 15/1 and the number of Brønsted acid sites decreased by approximately the same amount, while the textural properties and structure were affected only slightly if at all. Subsequent treatment with $Ti(acac)_2OiPr_2$ in iso-propanol was carried out leading to introduction of up to 0.7% of Ti into the MWW zeolite.

Based on UV-Vis spectra we identified 3 modes of Ti – tetrahedral in the framework, 5/6-coordinated Ti on the surface, presumably in the vacated pyramidal sites, and oxide-like clusters. After calcination the bands due to the latter two were not seen because of conversion to tetrahedral centres on the surface terminated with OH.

Catalytic oxidation was tested using 3 samples with different amount of Ti: 0.7, 0.36 and 0.13% and different Ti speciation. The conversion of methylphenyl sulphide and cis-cyclooctene increased with the amount of Ti. The sample containing 0.13% Ti, which was obtained by additional treatment with nitric acid after Ti-insertion showed highest relative conversion of methylphenyl sulphide per Ti content. The study confirms potential of the open TiOH moieties in oxidation catalysis although their final form is not certain as it may condense to fully closed Ti centres.

Experimental Section

Synthesis

High Al-MWW zeolite (MCM-56) was prepared according to the published procedures^[25] using Ultrasil (Evonik), sodium aluminate (Riedel-del-Haen), 50% NaOH and hexamethyleneimine (HMI, Sigma Aldrich) in the following molar ratio: Si/Al = 12, OH/Si = 0.15, HMI/Si = 0.35 and H₂O/Si = 19.3. The gel mixture was crystallized for 37 hours in a Teflon-lined autoclave at 143 °C. The product was filtered, washed with distilled water and dried at room temperature overnight.

Modification

The Ti insertion procedure was adopted from the work of Baran et al.^[26] In the first step, 1 g samples of as-synthesized MCM-56 were stirred at 500 rpm with 15 ml of concentrated HNO₃ acid (Avantor, Poland, p.p.a.) at room temperature for 4 hours. The solid was isolated by filtration, washed with distilled water and dried at room temperature (RT) for overnight.

The acid treated, partially dealuminated samples weighing 0.7 g were contacted with 50 ml of a monomeric source of titanium: 0.01 M and 0.001 M solution of di-isopropoxytitanium bis(acetylacetonate) (Ti(acac)₂OiPr₂) in isopropanol (containing 0.24 g and 0.024 g of Ti total). These mild conditions were chosen to reduce hydrolysis and agglomeration of titanium. The obtained products were washed with isopropanol and dried at RT overnight.

Part of the Ti-MCM-56 with 0.7% Ti content was stirred under reflux at 100 °C with 2 M HNO₃ for 20 hours according to the procedure by Wu et al.^[27] in order to remove weakly bonded metal. The solid was filtered, washed with distilled water, dried at RT overnight and calcined at 600 °C. **Characterization**

X-ray powder diffraction (XRD) patterns were collected on a Philips X'Pert diffractometer APD with CuK α radiation ($\lambda = 0.154$ nm) in the range 3-30° 2 θ with steps of 0.02° 2 θ .

Relative content of Ti, AI and Si was determined in the samples formulated into pellets, 20 mm in diameter, with the use of Energy-Dispersive XRF spectrometer (Thermo Scientific, ARL QUANT'X). The X-rays of 4-50 kV (1 kV step) with the beam size of 1 mm generated with the Rh anode. The

FULL PAPER

detector used was a 3.5 mm Si(Li) drifted crystal with a Peltier cooling (ca. 185 K). For quantitative analysis, calibration with a series of metallic standards and a UniQuant software were used.

Nitrogen adsorption isotherms were determined by the standard method at -196 °C (liquid nitrogen temperature) using an ASAP 2025 (Micromeritics) static volumetric apparatus. Before the adsorption experiments samples were outgassed at 350 °C using turbomolecular pump to remove pre-adsorbed water.

The DR-UV-Vis spectroscopy was carried out using an Evolution 600 (Thermo) spectrophotometer. The measurements of non-calcined samples were performed at room temperature in the range 200–900 nm with resolution of 2 nm.

Calcination in situ in was carried out by DR-UV-Vis using an Ocean Optics HR2000+ instrument (integration time 20 ms, 20 scans) equipped with an Ocean Optics DH-2000 BAL halogen-deuterium light source and a high-temperature reflection probe (FCR-7UV400-2-ME-HTX, 7 × 400 µm fibres). The spectra were collected within the wavelength range 225–1100 nm using BaSO₄ as a reflection standard. The spectra are shown in the Kubelka-Munk format $(F(R) = (1 - R)^2/2R)$, where R stands for reflectance). A high-temperature probe was attached at the top of the quartz microreactor. The distance between the sample bed and the high-temperature probe tip was 2-3 mm. The sample bed thickness was 4–5 mm.

IR spectra were recorded on Perkin Elmer Frontier spectrometer equipped with DTGS detector and a single reflection diamond ATR module, working with spectral resolution of 4 cm⁻¹. ATR spectra were normalized to the intensity of the 800 cm⁻¹ band, characteristic of T-O internal vibrations. Acidity was investigated by FITR spectroscopy based on adsorption of CO and pyridine used as probe molecules. The samples were activated in the form of self-supporting wafers for 1 hour at 450 °C prior to the adsorption of probe molecules at the following temperatures: 170 °C for pyridine (POCh Gliwice, analytical grade) and -100 °C for CO (Linde Gas Polska, 99.95% used without further purification). All spectra in absorbance mode, presented in this work have been normalized to the standard 10 mg pellet (density 3.2 mg cm⁻²). The concentrations of Lewis and Brønsted acid sites were evaluated using previously reported absorption coefficients^[25]: ϵ (LAS) = 0.165 cm²µmol⁻¹, and ϵ (BAS) = 0.044 cm²µmol⁻¹ and calculated from intensities of the corresponding pyridine maxima after pyridine desorption at 170 °C to ensure complete removal of weakly adsorbed species.

The oxidations of methylphenyl sulphide (Aldrich, 99%) were carried out at 30 °C in a 25 ml magnetically stirred round bottom three-neck glass flask equipped with a Dimroth condenser (procedure taken from ref.^[28]). Samples before reaction were activated at in air, at 450 °C for 90 min, cooled down in a desiccator and then transferred to the reaction flask. Typically, 8 mmol (1 g) of the sulphide was dissolved in 10 ml of acetonitrile (Fisher chemical, HPLC grade) together with 250 µl of 1,3-diisopropylbenzene as internal standard (Fluka, 95%) and 50 mg of a catalyst were introduced into the mixture. The substrate/catalyst mass ratio was S/C = 20. The mixture was heated to the reaction temperature and the reaction was started by addition of H₂O₂ aqueous solution (Aldrich, 35 wt%). The typically sulphide/H₂O₂ molar ratio was equal 2.



The conversion (X) of sulfoxidation reaction was calculated as the ratio of consumed and initial molar amount of the substrate (eqn 1). Yield of sulphoxide resp. sulphone was calculated as the ratio between produced sulphoxide resp. sulphone and consumed sulphide (eqn 2).



The epoxidations of cis-cyclooctene (Aldrich, 95%) were carried out according to the procedure presented by Prech et al.,^[5a] in a 25 ml magnetically stirred glass three-necked round bottom flask equipped with a Dimroth condenser at 60 °C. The alkene/catalyst mass ratio was 10 and alkene/H₂O₂ molar ratio was 2. Acetonitrile (Fisher chemical, HPLC grade) was used as a solvent and mesitylene (99%, Acros-Organics) served as an internal standard. In a standard experiment, 500 mg of cyclooctene were mixed with 250 mg of the internal standard, 50 mg of the catalyst and 6.65 ml of acetonitrile. The reaction was started by addition of H₂O₂ aqueous solution (35 wt.%, Aldrich) into the mixture. Samples were taken in regular intervals, centrifuged, cooled and analyzed using an Agilent 6850 GC system with 50 m long DB-5 column, an autosampler and a FID or a MS detector. Helium was used as a carrier gas.

The conversion (X) of epoxidation reaction was calculated as the ratio of consumed and initial molar amount of the substrate (eqn 3), while the yield was calculated by analogy to eqn (2).

$$X = \frac{n(cyclooctene)_{initial} - n(cyclooctene)_{sample}}{n(cyclooctene)_{initial}}$$
(3)

Acknowledgements

Financial support from National Science Centre Poland, grant no 2016/21/B/ST5/00858 is gratefully acknowledged. J.P. and J.Č. acknowledge the Czech Science Foundation for the project P106/12/G015.

Keywords: • zeolites • layered compounds • Ti-MWW • pyramidal Ti-sites • oxidation reaction

- W. J. Roth, J. Cejka, R. Millini, E. Montanari, B. Gil, M. Kubu, *Chem. Mater.* 2015, 27, 4620-4629.
- [2] a) M. G. Clerici, M. E. Domine, Liquid Phase Oxidation Via Heterogeneous Catalysis: Organic Synthesis and Industrial Applications 2013, 21-93; b) T. Tatsumi, in Modern Heterogeneous Oxidation Catalysis, Wiley-VCH Verlag GmbH & Co. KGaA, 2009, pp. 125-155.
- [3] a) G. Bellussi, V. Fattore, *Stud. Surf. Sci. Catal.* **1991**, *69*, 79-92; b) G.
 Bellussi, M. S. Rigutto, *Stud. Surf. Sci. Catal.* **1994**, *85*, 177-213; c) C.
 Perego, A. Carati, P. Ingallina, M. A. Mantegazza, G. Bellussi, *Appl. Catal.*, *A* **2001**, *221*, 63-72.
- [4] A. Zecchina, G. Spoto, S. Bordiga, A. Ferrero, G. Petrini, G. Leofanti, M. Padovan, *Stud. Surf. Sci. Catal.* **1991**, *69*, 251-258.
- [5] a) J. Přech, J. Čejka, Catal. Today 2016, 277, 2-8; b) J. Přech, Catal. Rev. 2018, 60, 71-131.
- [6] A. Corma, U. Diaz, M. E. Domine, V. Fornes, Angew. Chem., Int. Ed. 2000, 39, 1499-1501.
- [7] P. Wu, H. Xu, L. Xu, Y. Liu, M. He, in MWW-Type Titanosilicate: Synthesis, Structural Modification and Catalytic Applications to Green Oxidations (Eds.: P. Wu, H. Xu, L. Xu, Y. Liu, M. He), Springer Berlin Heidelberg, Berlin, Heidelberg, **2013**, pp. 9-34.

FULL PAPER

- a) J. Prech, D. Vitvarova, L. Lupinkova, M. Kubu, J. Cejka, *Microporous Mesoporous Mater.* 2015, *212*, 28-34; b) J. P. Nogier, Y. Millot, P. P. Man, C. Methivier, M. Che, S. Dzwigaj, *Catal. Lett.* 2009, *130*, 588-592.
- [9] D. Gleeson, G. Sankar, C. R. A. Catlow, J. M. Thomas, G. Spano, S. Bordiga, A. Zecchina, C. Lamberti, *Phys. Chem. Chem. Phys.* 2000, 2, 4812-4817.
- [10] C. Lamberti, S. Bordiga, D. Arduino, A. Zecchina, F. Geobaldo, G. Spano, F. Genoni, G. Petrini, A. Carati, F. Villain, G. Vlaic, *J. Phys. Chem. B* 1998, *102*, 6382-6390.
- [11] R. Millini, E. P. Massara, G. Perego, G. Bellussi, J. Catal. 1992, 137, 497-503.
- [12] W. J. Roth, W. Makowski, B. Marszalek, P. Michorczyk, W. Skuza, B. Gil, J. Mater. Chem. A 2014, 2, 15722-15725.
- a) W. J. Roth, Stud. Surf. Sci. Catal. 2005, 158A and B, 19-26; b) W. J. Roth, D. L. Dorset, Microporous Mesoporous Mater. 2011, 142, 32-36; c) K. Varoon, X. Y. Zhang, B. Elyassi, D. D. Brewer, M. Gettel, S. Kumar, J. A. Lee, S. Maheshwari, A. Mittal, C. Y. Sung, M. Cococcioni, L. F. Francis, A. V. McCormick, K. A. Mkhoyan, M. Tsapatsis, Science 2011, 333, 72-75; d) G. G. Juttu, R. F. Lobo, Microporous Mesoporous Mater. 2000, 40, 9-23.
- [14] P. Wu, T. Tatsumi, T. Komatsu, T. Yashima, J. Phys. Chem. B 2001, 105, 2897-2905.
- [15] D. Srinivas, P. Manikandan, S. C. Laha, R. Kumar, P. Ratnasamy, J. Catal. 2003, 217, 160-171.
- [16] M. Sasaki, Y. Sato, Y. Tsuboi, S. Inagaki, Y. Kubota, ACS Catal. 2014, 4, 2653-2657.
- [17] L. Balducci, D. Bianchi, R. Bortolo, R. D'Aloisio, M. Ricci, R. Tassinari, R. Ungarelli, Angew. Chem., Int. Ed. 2003, 42, 4937-4940.
- [18] L. Z. Wu, X. J. Deng, S. F. Zhao, H. M. Yin, Z. X. Zhuo, X. Q. Fang, Y. M. Liu, M. Y. He, *Chem. Commun.* **2016**, *52*, 8679-8682.
- [19] N. Liu, Y. M. Liu, W. Xie, L. L. Wang, M. Y. He, P. Wu, From Zeolites to Porous MOF Materials: the 40th Anniversary of International Zeolite Conference, Proceedings of the 15th International Zeolite Conference 2007, 170, 464-469.
- [20] X. S. Liu, K. K. Lu, J. K. Thomas, J. Chem. Soc., Faraday Trans. 1993, 89, 1861-1865.
- [21] M. Rutkowska, D. Macina, Z. Piwowarska, M. Gajewska, U. Diaz, L. Chmielarz, *Catal. Sci. Technol.* 2016, 6, 4849-4862.
- [22] A. Zecchina, G. Spoto, S. Bordiga, M. Padovan, G. Leofanti, G. Petrini, Stud. Surf. Sci. Catal. 1991, 65, 671-680.
- [23] a) G. H. Gao, S. F. Cheng, Y. An, X. J. Si, X. L. Fu, Y. M. Liu, H. J. Zhang, P. Wu, M. Y. He, *ChemCatChem* **2010**, *2*, 459-466; b) H. Munakata, Y. Oumi, A. Miyamoto, *J. Phys. Chem. B* **2001**, *105*, 3493-3501; c) G. Ricchiardi, A. de Man, J. Sauer, *Phys. Chem. Chem. Phys.* **2000**, *2*, 2195-2204; d) S. N. Wei, H. J. He, Y. Cheng, C. P. Yang, G. M. Zeng, L. Qiu, *RSC Adv.* **2016**, *6*, 103253-103269.
- [24] S. Kwon, N. M. Schweitzer, S. Park, P. C. Stair, R. Q. Snurr, J. Catal. 2015, 326, 107-115.
- [25] B. Gil, W. Makowski, B. Marszalek, W. J. Roth, M. Kubu, J. Čejka, Z. Olejniczak, *Dalton Trans.* 2014, *43*, 10501-10511.
- [26] R. Baran, Y. Millot, T. Onfroy, J. M. Krafft, S. Dzwigaj, *Microporous Mesoporous Mater.* 2012, 163, 122-130.
- [27] P. Wu, T. Miyaji, Y. M. Liu, M. Y. He, T. Tatsumi, *Catal. Today* 2005, 99, 233-240.
- [28] J. Prech, R. E. Morris, J. Cejka, Catal. Sci. Technol. 2016, 6, 2775-2786.

FULL PAPER

Entry for the Table of Contents

FULL PAPER



MWW structure with high AI content on the surface can produce TiOH as non-defect oxidation centres.

Aleksandra Korzeniowska, Justyna Grzybek, Wieslaw J. Roth, Andrzej Kowalczyk, Piotr Michorczyk, Jiři Čejka, Jan Přech, and Barbara Gil*

Page No. – Page No.

Incorporation of Ti as a pyramidal framework site in the mono-layered MCM-56 zeolite and its oxidation activity