

Electrochemical Deprotection of *para*-Methoxybenzyl Ethers in a Flow Electrolysis Cell

Robert A. Green,[†] Katherine E. Jolley,[†] Azzam A. M. Al-Hadedi,[†] Derek Pletcher,[†] David C. Harrowven,[†] Oscar De Frutos,[‡] Carlos Mateos,[‡] David J. Klauber,[§] Juan A. Rincón,[‡] and Richard C. D. Brown^{*,†}[©]

[†]Department of Chemistry, University of Southampton, Southampton, Hampshire SO17 1BJ, U.K.

[‡]Centro de Investigación Lilly S.A., Avda. de la Industria 30, 28108 Alcobendas-Madrid, Spain

[§]Early Chemical Development, AstraZeneca, Charter Way, Macclesfield, SK10 2NA, U.K.

(5) Supporting Information

ABSTRACT: Electrochemical deprotection of *p*-methoxybenzyl (PMB) ethers was performed in an undivided electrochemical flow reactor in MeOH solution, leading to the unmasked alcohol and *p*-methoxybenzaldehyde dimethyl acetal as a byproduct. The electrochemical method removes the need for chemical oxidants, and added electrolyte (BF_4NEt_4) can be recovered and reused. The method was applied to 17 substrates with high conversions in a single pass, yields up to 92%, and up to 7.5 g h⁻¹ productivity. The PMB protecting group was also selectively removed in the presence of some other common alcohol protecting groups.



T he use of protecting groups is common during multistep syntheses of target molecules of even moderate complexity,¹ adding reaction steps and reducing atom economy.² Yet, without protecting groups the scope of application of many synthetic methods would be greatly compromised. Although efforts to avoid protecting groups or to combine their introduction and/or removal with other chemical transformations have had some success,³ for now the use of protecting groups seems inevitable. Therefore, the development of more sustainable deprotection methods is a worthy line of investigation, particularly where the ultimate objective will involve scale up.

The *p*-methoxybenzyl (PMB), or *p*-methoxyphenylmethyl (MPM), group is a well-known protecting group used to mask the reactivity of alcohols in multistep synthesis.^{1,4} PMB protection of carboxylic acids and nitrogen-containing compounds can also be useful.⁵ Typical conditions for cleavage of PMB ethers employ stoichiometric excesses of DDQ or CAN (Scheme 1),⁶ but various other deprotection methods have been reported.^{1a,7,8} PMB ethers are frequently employed in situations where a benzyl-type protecting group is desirable, but other functionality present in the substrate are incompatible with removal by hydrogenolysis or dissolving metal conditions. On the other hand, PMB and benzyl ethers can be used together in orthogonal protecting group strategies.⁹

Benzylic oxidation is very well-known in the electrochemical literature, with the oxidation of *p-tert*-butyltoluene to *p-tert*-butylbenzaldehyde performed on an industrial scale.¹⁰ Electrosynthesis offers an opportunity for substantial reduction in the waste associated with PMB deprotection, by removing the need for chemical oxidants completely or allowing catalytic loadings of a mediator. In 1974 Weinreb reported direct electrochemical





deprotection of PMB ethers using a divided batch cell (Scheme 1), while in 1978 Streckhan reported the use of tris(*p*-bromophenyl)amine as an electrochemical mediator to cleave PMB and benzyl protected alcohols, also in a divided batch cell.¹¹ Microfluidic electrolysis cells offer some advantages over batch reactors, such as favorable electrode area to reactor volume, improved control over heat transfer, and ease of scale-up by extending the period of operation.¹² Furthermore, narrow interelectrode gaps allow reduced amounts of electrolyte to be used.¹³ Recently, we described extended path microflow electrolysis reactors for laboratory synthesis on 100 mg to 100 g scales, which are designed to achieve high

Received: March 2, 2017

Organic Letters

conversion in one pass.¹⁴ Here we report their application in reagent-free anodic cleavage of PMB ethers.

The electrochemical deprotection of PMB ether **1** was selected for initial optimization using an undivided cell containing an extended spiral flow channel (length: 1000 mm, width: 2 mm, interelectrode gap: 0.5 mm) formed by a perfluoroelastomer spacer separating a carbon/PVDF anode and a stainless steel cathode.^{14a} MeOH and H₂O were considered to be suitable solvents, functioning as nucleophilic traps for the benzylic cations produced at the anode, while also providing useful cathode counter electrode reactions, where formation of methoxide or hydroxide and H₂ counteracts buildup of H⁺ in the flow channel. Formation of gas bubbles may also increase turbulence and improve reactor performance.¹⁵

A general electrochemical deprotection protocol was established for the PMB ether 1, using a 0.10 M MeOH solution, containing Et_4NBF_4 (0.05 M) as an added electrolyte, at a flow rate of 0.25 mL min⁻¹. It is important to recognize that sufficient current is needed to drive the desired chemical change,¹⁵ and electrolysis conditions were optimized to achieve full conversion, which requires at least 80 mA under conditions of mass transfer control. In practice, a scan of currents of 80–135 mA (Table 1, entries 1–4) revealed conversions in the

Table 1. Optimization of Electrochemical Deprotection ^a									
Ph	OPMB <u>Hec</u> 1 [0.1 M]	₄NBF₄ (0.05 M))H, 0.25 mL min ^{−1} conditions (see Table 1)	h + MeO 2 OMe	OMe					
entry	current (mA)	cell voltage (V)	current efficiency (%)	yield ^b (%)					
1	80	3.4	79	79					
2	100	3.3	68	84					
3	120	3.4	58	87					
4	135	3.5	55	92					
5	160	3.7	41	82					
6	135	3.6	45	75 [°]					
7	135	5.5	49	82 ^d					
8	135	3.4	30	51 ^e					
9	135	3.0	8	13 ^f					

^{*a*}Reactions performed on a 0.5 mmol scale (5.0 mL) in the Ammonite 8 electrochemical flow reactor. ^{*b*}Yield determined using calibrated GC. ^{*c*}Reaction solvent was MeOH/H₂O (10:1); byproduct was 4-methoxybenzaldehyde. ^{*d*}Reduced electrolyte (0.005 M). ^{*e*}Electrolyte was NaBF₄ (0.05 M). ^{*f*}Pt electrode.

range 94–100%, with the highest yield of **2** obtained at 135 mA (entry 4). Increasing the current further (entry 5) led to a reduction in yield due to over-oxidation. The results in MeOH alone were superior in comparison to MeOH/H₂O (10:1) mixtures (entry 6). Reducing the amount of electrolyte (Et_4NBF_4) to 0.005 M (entry 7) gave a modest decrease in yield of **2**, and an expected increase in cell voltage due to the more poorly conducting medium. Changing the electrolyte to NaBF₄ or anode material to Pt (sheet, 0.1 mm thickness, 99.9%) both resulted in substantial reductions in yield. It is noteworthy that the Et_4NBF_4 is conveniently recovered from the crude reaction mixture by trituration with EtOAc and can be recrystallized and reused over many electrosyntheses.

The conditions established for anodic deprotection of PMB ether **1** proved to be effective for a range of substrates containing unsaturation and sulfonyl functionality (Table 2,

Table 2. Electrochemical Cleavage of PMB Ethers^a

RO´	\sim	MeOH, 0.25 Et ₄ NBF ₄	5 mL min ⁻¹ (0.05 M)	вон + Ме	OMe
1,3	- 19 [0.1 M	`OMe 135 m ∕l]	nA 2,	20–36	OMe
	entry	substrate	product, yield ^b (%)	current efficiency (%)	$\begin{array}{l} productivity \\ (mg \ h^{-1}) \\ \{mmol \ h^{-1}\} \end{array}$
	1		2 , 92	53	189 {1.39}
	2	Me () OPMB	20 , 90	52	261 {1.40}
	3	SO ₂ Ph OPMB 4	21 , 85	49	336 {1.32}
	4	ОРМВ	22 , 77 ^c	45	81 {1.16}
	5	РМВО 6	23 , 92	53	216 {1.38}
	6	AcO ^{VI} OPMB ACO ^{VI} OAc OAc 7	24 , 62	41	129 {0.27}
	7	©NH → OPMB	25 , 89	52	225 {1.34}
	8		26 , 81	47	321 {1.21}
	9	Boc-N-OPMB	27 , 82 ^d	82	246 {1.22}
	10	Ts -N OPMB	28 , 73	42	279 {1.09}
	11	Ph ^{-N} 12	29 , 69 ^d (82) ^e	68	276 {1.04}
	12	PGO () ₄ OPMB PG=THP (13)	30 , 74	43	225 {1.11}
	13	PG=TBDPS (14)	31 , 87	50	462 {1.30}
	14	PG=TBS (15)	32 , 66 ^f	76	228 {0.98}
	15	PG=Ac (16)	33 , 76	44	183 {1.14}
	16	OPMB	34 , 92	54	291 {1.40}
	17	OTBS	35 , 70 ^{f,g}	80	243 {1.05}
	18		36 , 42	24	126 {0.62}

^{*a*}Reactions performed in the Ammonite 8 electrochemical flow reactor, fitted with a C/PVDF anode and stainless steel cathode. All reactions conducted on 0.50 mmol scale (20 min run time with 5 mL total volume). ^{*b*}Isolated yield. ^{*c*}GC yield. ^{*d*}Reaction performed at 80 mA. ^{*c*}Yield based on recovered **12**. ^{*f*}Reaction performed at 70 mA. ^{*g*}I8% yield of diol product was also obtained.

entries 3 and 4), a protected sugar derivative (entry 6), and examples of saturated and unsaturated nitrogen heterocycles (entries 7–10). Selective cleavage of the PMB ether was generally achieved, including examples where oxidizable nitrogen functional groups were present (entries 8–11). For PMB deprotection of Boc-protected amines 10 and 12 a reduced current of 80 mA was used to avoid oxidation α to the nitrogen functionality (entries 9 and 11).¹⁶ Piperazine and tosyl-protected piperidine substrates, 9 and 11 (entries 8 and 10), were deprotected without overoxidation under the higher current conditions.

Anodic cleavage of the PMB group was also achieved in the presence of other common alcohol protecting groups, including OTHP, OAc, OTBDPS, OTBS, and OBn. Notably, PMB ethers of diols protected with TBS or THP groups at the primary alcohol positions proved to be more sensitive to the

Organic Letters

deprotection conditions, and the TBS ethers **15** and **18** afforded fully deprotected diols as the major products at 135 mA (entries 12, 14, 17, and 18). Selective removal of the PMB ether group was achieved by reducing the cell current to 70 mA (entries 14 and 17). It is possible that increased local acidity in the proximity of the anode, a consequence of oxidation of the PMB group, may catalyze cleavage of the more acid sensitive silyl ether functionality.

Current efficiencies for electrochemical deprotection in flow were ~50% for most of the examples studied, which is expected under conditions of excess current. This is due to oxidation of the solvent and formation of minor unidentified byproducts. Significant over-oxidation was only observed for the N-Boc derivatives **10** and **12**, but the methoxylated byproducts were minimized at lower current. It is emphasized, however, that the conditions have been optimized to favor high conversion rather than high current efficiency, and the cost of electricity is not important on a laboratory scale, and considerably less than that of common oxidizing agents.

A benefit of electrosynthesis in flow is the ability to quickly scale up the reaction by (a) increasing the flow rate, (b) increasing the concentration, or (c) increasing the volume of the reaction solution. To demonstrate the ease of laboratory scale-up the deprotection of 1, generating 2, was investigated at higher concentration and flow rate, over a longer duration (Table 3). Increasing the concentration to 0.475 M in the

Table	3.	Scale	up	of	Electroc	hemical	De	protection	in	Flow	ŗ
-------	----	-------	----	----	----------	---------	----	------------	----	------	---

	Ph_{4}	`ОРМВ 1	Et ₄ NBI MeOH, r conditio	F ₄ (0.05 M) eactor A or B	Ph ()2	[^] он 2
entry	concn 1 (M)	flow (mL	v rate min ⁻¹)	current (A)	yield ^a (%)	$productivity (g h^{-1})$
1 ^b	0.475	0	.25	0.65	89	0.86 ^d
2 ^c	0.30	4	.00	6.00	77	7.6 ^e
		1				

^{*a*}Isolated yield. ^{*b*}Ammonite 8 electrochemical flow reactor (A). ^{*c*}Ammonite 15 electrochemical flow reactor (B). ^{*d*}6.3 mmol h⁻¹. ^{*e*}55.5 mmol h⁻¹.

Ammonite 8, along with an adequate increase in current, led to the isolation of 17.2 g (89%) of product **2** over 20 h. The larger

Ammonite 15 reactor, with a 2 m long channel and reactor volume of 5.0 mL, allows for a higher flow rate while preserving high conversions.^{14b} At a substrate concentration of 0.30 M and flow rate to 4.0 mL min⁻¹, 63 g of the alcohol **2** was obtained over 8.3 h without additional optimization.

Sustainability metrics provide a useful guide to assess the impact of a reaction or process, and their application is becoming more widespread.¹⁷ With this in mind we performed a comparative analysis of the electrochemical PMB deprotection with that of other reported deprotections (Table 4).^{17a} Atom economy (AE) scores are inherently compromised for deprotection reactions and are largely dependent on the size of the molecule compared to the protecting group. Consequently, for the low molecular weight molecules being compared, mostly scores that raise concern are observed (entries 1, 2, 4 and 5). Reaction mass efficiency (RME), which also considers reagents and stoichiometry, can provide a good assessment of the sustainability credentials. Here the electrochemical deprotection scores favorably (entries 1 and 2), as only a small amount of electrolyte is required to facilitate the reaction. RME can be improved by electrolyte recovery. For the other deprotection methods RME values are lower due to the requirement for excess reagents or additives (entries 3-5), and use of metals with potential future supply issues is also of concern (entries 3 and $\tilde{5}$).^{17a} Finally, solvent selection is highly influential on the impact of a reaction, as it is often the largest single component added,^{17a} and replacement of chlorinated solvent or MeCN with MeOH is advantageous.

There are many metrics available to assess sustainability credentials, and the ones used here focus on the reactions and do not include work-up and purification steps because these have not been optimized. However, reagentless processes such as this electrochemical methodology can help to reduce the process mass intensity (PMI) through further process development by simplifying work-ups as excess reagent or byproduct does not need to be removed.¹⁸

In summary, an electrochemical deprotection of PMB ethers in a microflow cell has been described, and demonstrated for a range of substrates. Furthermore, the ease of scale up in a laboratory context has been highlighted, with the Ammonite 8 reactor producing 17.2 g of alcohol 2 in 20 h and the Ammonite 15 yielding 63.0 g (consuming 153.8 g of starting

								14	
Table 4	Commention	of Coloriad	Curstain a hility	Matui as fa	" DVD	Ethan Da	manation	Desetions ¹⁰	а
Table 4.	Comparison	of Selected	Sustainability	wietrics io	r pwid	Ether De	protection	Reactions	

entry	reaction and conditions	yield (%)	scale (g)	atom econ- omy (%)	reaction mass efficiency (%)	hazardous or pre- cious chemicals	solvents
1	$\begin{array}{c} \begin{array}{c} \text{OPMB} \\ \text{Ph} (1)_2 \\ 1 \\ 1 \\ 0.1 \\ \text{M} \end{array} \begin{array}{c} \text{Et}_4 \text{NBF}_4 \\ 135 \\ 135 \\ \text{mA}, 0.25 \\ \text{mL} \\ \text{mL} \\ \text{ml} \end{array} \begin{array}{c} \text{OH} \\ \text{Ph} (1)_2 \\ 2 \\ 2 \\ 1 \\ 2 \end{array} \begin{array}{c} \text{OH} \\ \text{Ph} (1)_2 \\ 2 \\ 2 \\ 2 \\ 2 \end{array} \begin{array}{c} \text{OH} \\ \text{Ph} (1)_2 \\ 2 \\ 2 \\ 2 \\ 2 \\ 2 \\ 2 \\ 2 \\ 2 \\ 2 \\$	92 •	0.051	53.1 ●	34.6 (49.2) ^b	- •	МеОН ●
2	1 [0.3 M] <u>Et₄NBF₄ (0.05 M)</u> <u>6.0 A, 4.0 mL min⁻¹</u> 2	77 🔴	63	53.1 ●	35.9 (41.0) ^b	-	МеОН ●
3 ^{6c}	PMBO, BnO OME DBn D D D D D D D D D D D D D D D D D D	98 ●	0.15	75.7 •	22.4	CAN O	CH ₂ Cl ₂ ●
4 ^{8e}	OPMB H 8 1,3-dimethoxybenzene [0.2 M] (3.0 equiv), batch	97 ●	0.031	56.4 🛑	20.1	- •	CH ₂ Cl ₂ ●
5 ^{8f}	OPMB Ir(df(CF ₃)ppy) ₂ (dtbbp)PF ₆ OH Ph → (10 mol %) Ph → Ph	86 🔴	0.086	50.4 🔴	15.9	Ir catalyst 🔸	MeCN / H ₂ O

"Key: green = desired/no problems; orange = problematic; red = undesired/very problematic/hazardous." RME value taking into consideration recovery of Et_4NBF_4 by precipitation from the crude reaction mixture.

material) in 8.3 h. Finally, sustainability metrics were compared with those of other reported procedures for PMB deprotection. In particular, the RME was favorable and the use of preferred solvents makes the described PMB deprotection a useful option on a variety of scales.

ASSOCIATED CONTENT

Supporting Information

The Supporting Information is available free of charge on the ACS Publications website at DOI: 10.1021/acs.or-glett.7b00641.

Experimental details and procedures, compound characterization data, description of flow electrolysis cells, cyclic voltammetry, expanded metrics tables, and copies of ¹H and ¹³C NMR spectra for all new compounds (PDF)

AUTHOR INFORMATION

Corresponding Author

*E-mail: rcb1@soton.ac.uk.

ORCID 💿

Richard C. D. Brown: 0000-0003-0156-7087

Notes

The authors declare the following competing financial interest(s): The Ammonite electrochemical flow cells used in this work were co-developed by Brown and Pletcher with Cambridge Reactor Design.

ACKNOWLEDGMENTS

The authors acknowledge financial support from EPSRC (EP/L003325/1 and EP/K039466/1). This work was also supported by Eli Lilly and Company through the Lilly Research Award Program (LRAP).

REFERENCES

(1) (a) Kocieński, P. J. Protecting Groups, 3rd ed.; Thieme: Stuttgart, 2005. (b) Wuts, P. G. M. The Role of Protecting Groups. In Greene's Protective Groups in Organic Synthesis, 5th ed.; John Wiley & Sons: New York, 2014; pp 1–16. (c) Schelhaas, M.; Waldmann, H. Angew. Chem., Int. Ed. Engl. **1996**, 35, 2056.

(2) For reviews: (a) Saicic, R. N. Tetrahedron 2014, 70, 8183. (b) Hoffmann, R. W. Handbook of Green Chemistry; Wiley-VCH Verlag GmbH & Co. KGaA: 2010. (c) Young, I. S.; Baran, P. S. Nat. Chem. 2009, 1, 193. (d) Newhouse, T.; Baran, P. S.; Hoffmann, R. W. Chem. Soc. Rev. 2009, 38, 3010. (e) Hoffmann, R. W. Synthesis 2006, 2006, 3531.

(3) For selected examples in natural product synthesis: (a) Stambulyan, H.; Minehan, T. G. Org. Biomol. Chem. 2016, 14, 8728.
(b) Yan, X. X.; Hu, X. D. J. Org. Chem. 2014, 79, 5282. (c) Morales, C. P.; Catalán, J.; Domingo, V.; González Delgado, J. A. G.; Dobado, J. A.; Herrador, M. M.; Quílez del Moral, J. F. Q.; Barrero, A. F. J. Org. Chem. 2011, 76, 2494. (d) Cecil, A. R. L.; Brown, R. C. D. Org. Lett. 2002, 4, 3715.

(4) For selected examples in natural product synthesis: (a) Fuwa, H.; Sakamoto, K.; Muto, T.; Sasaki, M. *Tetrahedron* **2015**, *71*, 6369. (b) Mukaiyama, T.; Shiina, I.; Iwadare, H.; Saitoh, M.; Nishimura, T.; Ohkawa, N.; Sakoh, H.; Nishimura, K.; Tani, Y.; Hasegawa, M.; Yamada, K.; Saitoh, K. *Chem. - Eur. J.* **1999**, *5*, 121. (c) Kocienski, P. J.; Brown, R. C. D.; Pommier, A.; Procter, M.; Schmidt, B. J. Chem. Soc., Perkin Trans. 1 **1998**, 9. (d) Horita, K.; Oikawa, Y.; Nagato, S.; Yonemitsu, O. *Tetrahedron Lett.* **1988**, *29*, 5143.

(5) For a recent review of PMB esters: (a) Howard, K. T.; Chisholm, J. D. *Org. Prep. Proced. Int.* **2016**, *48*, 1. For selected examples of PMB protection of nitrogen compounds: (b) Owen, D. R.; Bull, D. J.;

Bunnage, M. E.; Glossop, M. S.; Maguire, R. J.; Strang, R. S. Bioorg. Med. Chem. Lett. 2010, 20, 92. (c) Bartoli, G.; Bartolacci, M.; Cortese, M.; Marcantoni, E.; Massaccesi, M.; Pela, R.; Sambri, L. Eur. J. Org. Chem. 2004, 2004, 2359. (d) Chern, C. Y.; Huang, Y. P.; Kan, W. M. Tetrahedron Lett. 2003, 44, 1039.

(6) (a) Oikawa, Y.; Yoshioka, T.; Yonemitsu, O. Tetrahedron Lett. 1982, 23, 885. (b) Classon, B.; Garegg, P. J.; Samuelsson, B. Acta Chem. Scand. 1984, 38b, 419. (c) Johansson, R.; Samuelsson, B. J. Chem. Soc., Perkin Trans. 1 1984, 2371.

(7) (a) Wuts, P. G. M. Protection of the Hydroxyl Group, Including 1,2- and 1,3-Diols. In *Greene's Protective Groups in Organic Synthesis*, 5th ed.; John Wiley & Sons: New York, 2014; pp 17–471. For a review: (b) Weissman, S. A.; Zewge, D. *Tetrahedron* **2005**, *61*, 7833.

(8) (a) Kern, N.; Dombray, T.; Blanc, A.; Weibel, J.-M.; Pale, P. J. Org. Chem. 2012, 77, 9227. (b) Liu, L.; Floreancig, P. E. Org. Lett. 2010, 12, 4686. (c) Sharma, G. V. M; Reddy, C. G.; Krishna, P. R. J. Org. Chem. 2003, 68, 4574. (d) Hinklin, R. J.; Kiessling, L. L. Org. Lett. 2002, 4, 1131. (e) Jung, M. E.; Koch, P. Tetrahedron Lett. 2011, 52, 6051. (f) Tucker, J. W.; Narayanam, J. M. R.; Shah, P. S.; Stephenson, C. R. J. Chem. Commun. 2011, 47, 5040.

(9) Oikawa, Y.; Tanaka, T.; Horita, K.; Yonemitsu, O. Tetrahedron Lett. 1984, 25, 5397.

(10) (a) Organic Electrochemistry, 4th ed.; Lund, H., Hammerich, O., Eds.; Marcel Dekker: New York, 2001. (b) Steckhan, E.; Arns, T.; Heineman, W. R.; Hilt, G.; Hoormann, D.; Jörissen, J.; Kröner, L.; Lewall, B.; Pütter, H. Chemosphere 2001, 43, 63. (c) Hayashi, R.; Shimizu, A.; Yoshida, J. J. Am. Chem. Soc. 2016, 138, 8400.

(11) (a) Weinreb, S. M.; Epling, G. A.; Comi, R.; Reitano, M. J. Org. Chem. 1975, 40, 1356. (b) Schmidt, W.; Steckhan, E. Angew. Chem., Int. Ed. Engl. 1978, 17, 673.

(12) Reviews: (a) Watts, K.; Baker, A.; Wirth, T. J. Flow Chem. 2015, 4, 2. (b) Yoshida, J. Chem. Commun. 2005, 4509. Selected examples: (c) Arai, T.; Tateno, H.; Nakabayashi, K.; Kashiwagi, T.; Atobe, M. Chem. Commun. 2015, 51, 4891. (d) Arai, K.; Wirth, T. Org. Process Res. Dev. 2014, 18, 1377. (e) Gütz, C.; Bänziger, M.; Bucher, C.; Galvão, T. R.; Waldvogel, S. R. Org. Process Res. Dev. 2015, 19, 1428. (f) Attour, A.; Dirrenberger, P.; Rode, S.; Ziogas, A.; Matlosz, M.; Lapicque, F. Chem. Eng. Sci. 2011, 66, 480.

(13) (a) Horcajada, R.; Okajima, M.; Suga, S.; Yoshida, J. *Chem. Commun.* **2005**, 1303–1305. (b) Horii, D.; Atobe, M.; Fuchigami, T.; Marken, F. *J. Electrochem. Soc.* **2006**, *153*, D143–D147.

(14) (a) Green, R. A.; Brown, R. C. D.; Pletcher, D.; Harji, B. *Electrochem. Commun.* 2016, 73, 63. (b) Green, R. A.; Brown, R. C. D.; Pletcher, D.; Harji, B. Org. Process Res. Dev. 2015, 19, 1424.
(c) Kuleshova, J.; Hill-Cousins, J. T.; Birkin, P. R.; Brown, R. C. D.; Pletcher, D.; Underwood, T. J. *Electrochim. Acta* 2012, 69, 197.
(d) Kuleshova, J.; Hill-Cousins, J. T.; Birkin, P. R.; Brown, R. C. D.; Pletcher, D.; Underwood, T. J. *Electrochim. Acta* 2011, 56, 4322.

(15) (a) Green, R. A.; Brown, R. C. D.; Pletcher, D. J. Flow Chem. 2016, 6, 191. (b) Green, R. A.; Brown, R. C. D.; Pletcher, D. J. Flow Chem. 2015, 5, 31.

(16) See Supporting Information for details of metric calculations.

(17) (a) McElroy, C. R.; Constantinou, A.; Jones, L. C.; Summerton, L.; Clark, J. H. Green Chem. 2015, 17, 3111. (b) Dach, R.; Song, J. J.; Roschangar, F.; Samstag, W.; Senanayake, C. H. Org. Process Res. Dev. 2012, 16, 1697. (c) Constable, D. J. C.; Curzons, A. D.; Cunningham, V. L. Green Chem. 2002, 4, 521.

(18) Process mass intensity is defined as the total mass in a process or step divided by the mass of the product. For a more detailed description of the sustainability metrics, see Supporting Information.