

# Flow Photochemistry

# **Batch versus Flow Photochemistry:** A Revealing Comparison of Yield and Productivity

Luke D. Elliott,<sup>[a]</sup> Jonathan P. Knowles,<sup>[a]</sup> Paul J. Koovits,<sup>[a]</sup> Katie G. Maskill,<sup>[a]</sup> Michael J. Ralph,<sup>[a]</sup> Guillaume Lejeune,<sup>[a]</sup> Lee J. Edwards,<sup>[b]</sup> Richard I. Robinson,<sup>[b]</sup> Ian R. Clemens,<sup>[b]</sup> Brian Cox,<sup>[b]</sup> David D. Pascoe,<sup>[b]</sup> Guido Koch,<sup>[c]</sup> Martin Eberle,<sup>[c]</sup> Malcolm B. Berry,<sup>[d]</sup> and Kevin I. Booker-Milburn\*<sup>[a]</sup>

Abstract: The use of flow photochemistry and its apparent superiority over batch has been reported by a number of groups in recent years. To rigorously determine whether flow does indeed have an advantage over batch, a broad range of synthetic photochemical transformations were optimized in both reactor modes and their yields and productivities compared. Surprisingly, yields were essentially identical in all comparative cases. Even more revealing was the observation that the productivity of flow reactors varied very little

## Introduction

In the last ten years, the use of flow chemistry in organic synthesis has increased dramatically and is now rapidly being established as a routine tool for mainstream synthesis.<sup>[1-8]</sup> Flow techniques have also been applied to synthetic organic photochemistry on a variety of platforms.<sup>[9,10]</sup> In 2005, Booker-Milburn and Berry reported a practical flow reactor for general lab-based synthetic photochemistry.<sup>[11-13]</sup> This employed a reactor of flexible, UV-transparent fluorinated ethylene propylene (FEP) tubing wrapped closely around a UV-emitting source (Figure 1 a). The surface area and proximity of the photolysate to the UV source ensured effective irradiation of large volumes of solution minimizing transmission versus distance con-

[a] Dr. L. D. Elliott, Dr. J. P. Knowles, Dr. P. J. Koovits, K. G. Maskill, M. J. Ralph, Dr. G. Lejeune, Prof. K. I. Booker-Milburn School of Chemistry, University of Bristol Cantock's Close, Bristol, BS8 1TS (UK) E-mail: k.booker-milburn@bristol.ac.uk

[b] L. J. Edwards, R. I. Robinson, I. R. Clemens, B. Cox, D. D. Pascoe Novartis Institutes for Biomedical Research Wimblehurst Road, Horsham, West Sussex, RH12 4AB (UK)

[c] G. Koch, M. Eberle Novartis Pharma AG Novartis Institutes for Biomedical Research, 4002 Basel (Switzerland)

[d] M. B. Berry GlaxoSmithKline, Gunnels Wood Road, Stevenage, Herts, SG1 2NY (UK) Supporting information for this article is available on the WWW under http://dx.doi.org/10.1002/chem.201404347. It contains a comprehensive account of all experimental details, including supplementary figures and tables, full experimental procedures, analytical data, as well as copies of <sup>1</sup>H and <sup>13</sup>C NMR data.

These are not the final page numbers! 77

to that of their batch counterparts when the key reaction parameters were matched. Those with a single layer of fluorinated ethylene propylene (FEP) had an average productivity 20% lower than that of batch, whereas three-layer reactors were 20% more productive. Finally, the utility of flow chemistry was demonstrated in the scale-up of the ringopening reaction of a potentially explosive [1.1.1] propellane with butane-2,3-dione.

straints, resulting in the production of 20-500 g of photochemical products in 24 h. Precise regulation of flow rate enabled residence time to be controlled in the cases when over-irradiation of evolving product is a problem.<sup>[14-16]</sup> Recently, a secondgeneration reactor has enabled use of air-cooled low-pressure 36 W lamps in conjunction with FEP tubing,<sup>[16-18]</sup> with the advantage of allowing controlled irradiation at selected wavelengths centered around 254, 312 and 365 nm by simply exchanging lamps (Figure 1 b).

The FEP reactor concept has now been used and adapted for a number of reactions, resulting in the synthesis of a wide range of complex, photochemically derived products.<sup>[19-28]</sup> Perhaps the most striking of these has been the use of an FEP flow reactor in the scaled-up continuous synthesis of the frontline anti-malarial drug artemisinin described by Seeberger and co-workers.<sup>[29, 30]</sup>

Many groups have now reported the advantages of flow photochemistry over previously reported batch results.<sup>[9,10]</sup> Whilst it is true that scale-up has now been clearly demonstrated in flow, and there is a real safety advantage when irradiating large volumes of flammable solvents, flow photochemistry involves a considerable equipment investment compared to the simplicity of a conventional batch reactor. On scale-up, the increased path length of larger batch reactors theoretically suffer from the constraints imposed by the Beer-Lambert law (e.g., longer reaction times/photo-degradation), nevertheless, huge photochemical industrial processes have been developed in batch. For example, the Toray process for the synthesis of cyclohexanone oxime (Nylon 6 production) is a semi-continuous photochemical batch process that in 1976 had a worldwide production capacity of 160 000 tonnes pa.<sup>[31]</sup>

Chem. Eur. J. 2014, 20, 1-8

Wiley Online Library

1

ChemPubSoc Europe





**Figure 1.** Batch and flow reactors used in this study. (a) Comparison of the footprints of a 400 W medium-pressure Hg lamp batch reactor and power supply (left) with equivalent three-layer FEP flow reactor and peristaltic pump (right). (b) A triad of one-layer FEP reactors customized for use with 40 cm 36 W low-pressure Hg lamps. This example depicts the use of 254 nm (UVC) lamps, in which three-reactors have been daisy chained together for increased productivity (see Table 1, entry 7).

Faced with this conflicting picture, the following question arises: is it possible that batch limitations in photochemistry are not as great as feared and the superiority of flow is yet to be proven unequivocally? With many readily available bespoke and commercially available reactor choices, today's first-time photochemistry user may well ask the question: which is better, batch or flow? With this in mind, we embarked on an investigation and careful comparison of batch versus flow-reactor performance for a variety of different photochemical reactions. This study would prove for the first time whether photochemical flow reactors are more or less productive under the same time period of an optimized batch process when both are exposed to the same amount of UV light.

#### **Results and Discussion**

Attempting to compare batch and flow photo-reactors is not straightforward, because encapsulating the light efficiently in flow is more challenging due to the non-planar surface of the tubing, gaps between the tubing and absorption of light by the FEP. To enable fair comparison between reactors, all reactions were performed keeping parameters of concentration, lamp power and distance of photolysate from the UV source as identical as possible. Although it is commonplace in flow chemistry to use residence times (i.e., reactor volume/flow rate) for comparison with batch reaction times, in photochemistry, this often leads to incorrect conclusions (see below) regarding various reaction outcomes.<sup>[9]</sup> Consequently, both modes were optimized independently under the above-described reaction parameters, and their yields, and critically, productivities compared at the end-time point obtained for the batch process.

Table 1 summarizes the extensive data collected on twelve different cycloaddition and rearrangement reactions. Perhaps the most strikingly obvious feature is the similarity in isolated yields between batch and flow, which in most cases are essentially identical. After extensive optimization of each reaction, it also became clear that the productivity of the flow reactor differed to that of the batch reactor by a relatively small amount. Similar to previous studies,<sup>[11]</sup> the number of layers of FEP had a significant effect. For example, in entry 1, Table 1, although the yields of 3<sup>[32]</sup> were the same, the productivity was 50% higher for a three-layer compared to one-layer system. This was due to the more effective capture of light in the threelayer system, enabling a faster flow rate (3 mLmin<sup>-1</sup>) and the isolation of 62.7 g of 3 in a single 22 h run. Conversely, it was clear that the one-layer system was less effective at capturing light thus reflecting its lower productivity compared to batch (5.70 vs. 6.56 g in 3 h). For this reason, all subsequent reactions studied with a 400 W lamp utilized the three-layer system. The other maleimide cycloadditions (entries 2-4)<sup>[11,32-33]</sup> proceeded in a similar fashion, and the desired [2+2] cycloaddition adducts were obtained in near identical yields for both batch and flow reactions but with slightly greater productivity levels for flow.

Entry 5 proved to be very interesting. It was found that the absorption of amino maleimide 10 is redshifted with respect to the parent maleimide, similar to the methoxy maleimides we have previously studied.<sup>[34,35]</sup> This amino maleimide chromophore had a  $\lambda_{max}$  centered at 350 nm, ideally suited to irradiation with 36 W UVA lamps (Figure 2). Under flow conditions, this intramolecular [2+2] cycloaddition was an exceptional performer with a productivity of 12.69 g/100 min at 80% isolated yield. The absorption was so strong, and the efficiency of the reaction so high, that it could be run at a flow rate of 16 mLmin<sup>-1</sup> using two 36 W lamps in series, enabling the production of 40 g of tricyclic product 11 in a 5 h run. However, when it came to comparing the batch process by using the same low-pressure 36 W lamp, we were faced with the problem that the lamp was too long to be fully immersed in a 400 mL batch immersion well, and only half of the lamp could be utilized. When this batch irradiation was carried out in this way, it gave an optimized 77% isolated yield of the tricyclic product at a productivity of 3.11 g/100 min. On face value, this appears to be a quarter as productive as the flow result for the same time period. However, when the four-fold

2

© 2014 Wiley-VCH Verlag GmbH & Co. KGaA, Weinheim



CHEMISTRY A European Journal Full Paper

Table 1. Batch versus flow yields and productivities for a variety of photochemical reactions.							
Entry		Lamp	Mode	Conditions <sup>[a]</sup>	Yield [%]	Productivity at batch end [g]	Batch vs. flow <sup>[g]</sup>
1	$MeN \rightarrow 1 \qquad Cl \qquad $	400 W 400 W 400 W	batch flow <sup>[b]</sup> flow <sup>[c]</sup>	0.096 м, 180 min 0.096 м, 3 mLmin <sup>-1</sup> 0.096 м, 2 mLmin <sup>-1</sup>	68 68 68	6.56 8.55 5.70	1/1.30 1.15/1
2		400 W 400 W	batch flow <sup>(b)</sup>	0.1 м,120 min 0.1 м, 4 mLmin <sup>-1</sup>	67 68	4.77 5.90	1/1.24
3	$MeN \rightarrow 0 1 MeN \rightarrow 0 7 MeN$	400 W 400 W	batch flow <sup>[b]</sup>	0.1 м, 80 min 0.1 м, 6 mLmin <sup>-1</sup>	56 52	4.32 4.82	1/1.12
4	HN =	400 W 400 W	batch flow <sup>[b]</sup>	0.1 м, 120 min 0.1 м, 4 mLmin <sup>-1</sup>	65 64	4.0 4.70	1/1.18
5		1×36 W UVA 2×36 W UVA	batch flow <sup>[c]</sup>	0.05 м, 100 min 0.055 м, 16 mLmin <sup>-1</sup>	77 80	3.11 [12.44] <sup>[f]</sup> 12.69	1/1.02
6	$ \begin{array}{c}                                     $	1×36 W UVA 1×36 W UVA	batch flow <sup>[c]</sup>	0.1 м, 105 min 0.1 м, 7.5 mLmin <sup>-1</sup>	80 77	7.09 [13.10] <sup>[f]</sup> 10.70	1.22/1
7	$\begin{array}{cccccccccccccccccccccccccccccccccccc$	1×36 W UVC 1×36 W UVC 3×36 W UVC	batch flow <sup>[c]</sup> flow <sup>[c]</sup>	0.02 м, 7 h 0.02 м, 2 mLmin <sup>-1</sup> 0.03 м, 4 mLmin <sup>-1</sup>	84 75 72	2.10 [4.20] <sup>[f]</sup> 3.54 10.06	1.19/1 1.25/1
8	$ \underbrace{\bigcirc}_{\text{PhMe}} \overset{\text{Ph}}{\underset{\text{T7}}{}} \overset{\text{H}}{\underset{\text{Ph}}{}} \overset{\text{H}}{\underset{\text{Ph}}{\overset{\text{Ph}}{\underset{\text{Ph}}{}}} \overset{\text{H}}{\underset{\text{Ph}}{}} \overset{\text{H}}{\underset{\text{Ph}}{\overset{\text{Ph}}{\underset{\text{Ph}}{\overset{\text{Ph}}{\underset{\text{Ph}}{\overset{\text{Ph}}{\underset{\text{Ph}}}}} \overset{\text{H}}{\underset{\text{Ph}}{\overset{\text{Ph}}{\underset{\text{Ph}}{\overset{\text{Ph}}{\underset{\text{Ph}}{\overset{\text{Ph}}{\underset{\text{Ph}}{\overset{\text{Ph}}{\underset{\text{Ph}}{\overset{\text{Ph}}{\underset{\text{Ph}}{\overset{\text{Ph}}{\underset{\text{Ph}}{\overset{\text{Ph}}{\underset{\text{Ph}}{\overset{\text{Ph}}{\underset{\text{Ph}}{\overset{\text{Ph}}{\underset{\text{Ph}}{\overset{\text{Ph}}{\underset{\text{Ph}}{\overset{\text{Ph}}{\underset{\text{Ph}}{\overset{\text{Ph}}{\underset{\text{Ph}}{\overset{Ph}}{\overset{Ph}}}} \overset{\text{Ph}}{\underset{Ph}} \overset{\text{Ph}}{\overset{Ph}}{\overset{Ph}} \overset{\text{Ph}}{\overset{Ph}}{\overset{Ph}}{\overset{Ph}}} \overset{\text{Ph}}{\overset{Ph}}{\overset{Ph}}{\overset{Ph}}{\overset{Ph}}{\overset{Ph}}} \overset{\text{Ph}}{\overset{Ph}}{\overset{Ph}} \overset{Ph}}{\overset{Ph}}{\overset{Ph}}} \overset{Ph}}{\overset{Ph}} \overset{Ph}}{\overset{Ph}} \overset{Ph}}{\overset{Ph}}{\overset{Ph}}{\overset{Ph}}{\overset{Ph}}} \overset{Ph}}{\overset{Ph}}{\overset{Ph}}{\overset{Ph}}} \overset{Ph}}{\overset{Ph}}{\overset{Ph}}{\overset{Ph}}} \overset{Ph}}{\overset{Ph}}{\overset{Ph}}} \overset{Ph}}{\overset{Ph}}{\overset{Ph}}} \overset{Ph}}{\overset{Ph}}} \overset{Ph}}{\overset{Ph}} \overset{Ph}}{\overset{Ph}}} \overset{Ph}}{\overset{Ph}}} \overset{Ph}}{\overset{Ph}}} \overset{Ph}}{\overset{Ph}}} \overset{Ph}}{\overset{Ph}} \overset{Ph}}{\overset{Ph}} \overset{Ph}}{\overset{Ph}}} \overset{Ph}}{\overset{Ph}} \overset{Ph}}{\overset{Ph}}} \overset{Ph}}{\overset{Ph}} \overset{Ph}}{\overset{Ph}} \overset{Ph}}{\overset{Ph}} \overset{Ph}}{\overset{Ph}} \overset{Ph}}{\overset{Ph}} \overset{Ph}}{\overset{Ph}} \overset{Ph}}{\overset{Ph}} \overset{Ph}}{\overset{Ph}} \overset{Ph}}{\overset{Ph}} \overset{Ph}} \overset{Ph}} \overset{Ph}} \overset{Ph}}{\overset{Ph}} \overset{Ph}} \overset{Ph}}{\overset{Ph}} Ph$	400 W 400 W	batch flow <sup>[b]</sup>	0.3 м, 3 h 3 mL min <sup>-1</sup>	67 72	14.05 20.52	1/1.46
9	Me Me Me Me Me N Me Me N 18 0 19	400 W 400 W 400 W 400 W	batch flow <sup>(b)</sup> batch flow <sup>(b)</sup>	0.1 м, 4 h 0.1 м, 2 mLmin <sup>-1</sup> 0.02 м, 2 h 0.02 м, 4 mLmin <sup>-1</sup>	63 63 76 77	4.88 5.87 1.18 1.43	1/1.20 1/1.21
10	$CI \longrightarrow N \longrightarrow CH_2CI_2 CI \longrightarrow N \longrightarrow O21$	400 W 400 W	batch flow <sup>(b)</sup>	0.1 м, 100 min 0.1 м, 4.2 mLmin <sup>-1</sup>	62 60	5.82 5.90	1/1.02
11 <sup>[d]</sup>	$\begin{array}{c} \overbrace{22} & \overbrace{\text{MeCN}} & \overbrace{23} \\ \hline \\ MeOC & C \\ \end{array} $	400 W 400 W	batch flow <sup>[b]</sup>	0.6 м, 135 min 0.6 м, 3.3 mLmin <sup>-1</sup>	90 89	30.70 33.83	1/1.10
12	24 MeOC NeCN 24 25	1×36 W UVC 1×36 W UVC	batch flow <sup>[c]</sup>	0.02 м, 310 min 0.02 м, 3.1 mLmin <sup>-1</sup>	49 46	0.80 [2.0] <sup>[f]</sup> 1.86	1.08/1

[a] All reactions run in degassed solvents. [b] Three layers of FEP, flow direction outer layer to inner. [c] One layer of FEP. [d] Acetophenone sensitizer (50 mol %). [f] Parentheses indicate power corrected value for length of the lamp effectively covered (see the Supporting Information for detail). [g] Ratio of productivities; all products are racemic.

power difference is factored in the results between batch and flow are remarkably similar at the 100 min batch end point. With the 36 W low-pressure lamps, a three-layer version was

These are not the final page numbers! **77** 

not investigated, because the longer length of the lamps (40 cm) would require a large amount of FEP, leading to an excessive reactor volume (ca. 300 mL).

3



Figure 2. UV absorption of amino maleimide 10 overlaid with emission of 36 W UVA low-pressure lamp.

Entry 6 describes the known<sup>[36-38]</sup> intramolecular cycloaddition of dieneone **12** to caged diketone **13** with a single 36 W UVA lamp in flow. The batch reaction was conducted by using approximately 50% immersion of the lamp. Optimized yields were again very similar, and it was found that the batch reaction was approximately 20% more productive once the power difference had been accounted for. Interestingly, unlike the flow reactor, for this example, the batch reactor suffered from foul-up over-time and required cleaning (base bath) between runs. Recently, Aillet et al. described a chemical engineering analysis of this reaction in a microcapillary flow reactor and also concluded that in this case, productivity was higher in batch.<sup>[39]</sup>

The intramolecular [2+2] cycloaddition of pyrrole 14 (entry 7, Table 1) provided an example of the use of a 36 W UVC lamp at 254 nm, which was also conducted with 50% lamp immersion.<sup>[40]</sup> Once power correction had been applied, this also displayed the same trend as entry 6, Table 1. Although the yield and power corrected productivity in batch was higher, by using a three-lamp system in flow, we were able to produce 29.2 g of 15 in a single 21 h run (cf. 10.06 g/7 h). To process the same 5 L solution of substrate 14 in batch would be impractical. The cycloaddition was also carried out with a 125 W medium-pressure lamp through a quartz filter (see Figure S14 in the Supporting Information; 69%, 0.57 g/2 h). Over the course of 7 h, this lamp could only produce about 2 g of 15, the same as half a 36 W UVC lamp. This clearly demonstrates the superior efficiency of the low-pressure UVC emission over that of a medium-pressure lamp.

The Paternò–Büchi reaction of benzaldehyde and dihydrofuran **16** (entry 8) had previously been optimized in a detailed study by Griesbeck et al. by using a falling film reactor with a high power 3 kW XeCl excimer lamp (75%, 130 g, 14 h).<sup>[41]</sup> In our hands, scale-up under batch conditions at 0.3 M concentration gave a 67% isolated yield (14.05 g, 3 h) of oxetane **17** by using a 400 W lamp. Under flow conditions, an optimized 72% yield was obtained with a productivity of 20.52 g at the batch end point of 3 h. This represented an almost 50% increase in productivity for the flow reactor in this particular case.

Moving away from four-membered ring formation, we next studied the performance of the maleimide chromophore in the previously developed intramolecular [5+2] cycloaddition to azepines (entries 9 and 10).<sup>[42,43]</sup> With dimethylmaleimide **18**, the reactions were run at two different concentrations, the lower concentrations enabling a higher conversion to be obtained in a shorter reaction time. For this reaction, it was remarkable to observe identical yields for batch and flow, even with a ten-fold difference in concentration. However, in both cases, flow conditions proved to be approximately 20% more productive than batch.

The [5+2] cycloaddition of dichloromaleimide **20** proved to be a very interesting example (entry 10). Previously in batch, this reaction had proved to be very sensitive using a 125 W lamp at 0.02 M, and the window between maximum conversion of starting material and over-irradiation of the sensitive product was very narrow.<sup>[9,14]</sup> Consequently, we had previously never been able to perform this reaction on scales much greater than 0.5 g by using batch apparatus. So it was to our surprise that when this reaction was performed at the much higher concentration of 0.1 M in batch (400 mL) with a 400 W lamp, we were able to follow the reaction over time without observing any noticeable product degradation (Figure 3).



**Figure 3.** Batch [5+2] photocycloaddition of dichloromaleimide **20** monitored over time by using <sup>1</sup>H NMR technique with 1,3,5-trimethoxy benzene as internal standard.

In batch, azepine formation progressed rapidly over the first 100 min or so to give an optimal conversion in the region of 60–70% (by NMR spectroscopy). Cessation of irradiation at this point gave a 62% isolated yield of pure azepine **21** with a productivity of 5.82 g/100 min. We found that the batch reaction could be irradiated for a total of 210 min allowing the isolation of product in a record yield of 69%, albeit at a lower productivity. This product was also less pure; a tell-tale red colouration indicating photodegradation from over-irradiation.

Two factors are likely at play here: firstly, at this higher concentration, the sensitive product is more effectively "screened" by the starting maleimide. Secondly, because the irradiation time is longer at higher concentration, the reaction was much easier to monitor by NMR spectroscopy, and therefore, the point between maximum conversion and over-irradiation

4



could be more accurately determined compared to our earlier studies. This example clearly illustrates the importance of matching substrate concentration with photon flux (lamp power) in batch reactions, that is, too much power risks product degradation and too little leads to slow and incomplete conversion. Performing the reaction in flow using a three-layer system (0.1 M,  $4.2 \text{ mLmin}^{-1}$ ) resulted in essentially identical yield and productivity to batch (5.90 g/100 min, 60% yield).

Entry 11 describes an acetophenone-sensitized di- $\pi$ -methane rearrangement first reported by Edman.<sup>[44,45]</sup> We found this reaction to be exceptionally efficient both in flow and in batch and actually struggled to identify its limits. For example, this was run at a very high concentration of 0.6 m to give almost quantitative yields in both batch and flow, with the latter proving marginally more productive at the batch end time.

Entry 12 describes a reaction previously developed by us involving the irradiation of pyrrole **24** to tricyclic aziridine **25** through a complex photochemical two-step process.<sup>[17]</sup> Consistent with the rest of the 1-layer/36 W reactors used in this study, the yields between batch and flow were essentially identical, with a minor increase in batch productivity when the power correction was factored in.

Finally, we studied the scale-up of the photochemical ring opening of propellane **26** with butane-2,3-dione to diketone **28**, which was previously described in batch (58%, 26.5 g, 8 h).<sup>[46,47]</sup> After optimization in flow, this reaction proceeded in an identical 58% yield, but with greatly increased productivity to deliver 51.8 g of pure **28** in a single 70 min run (projected 1.07 kg/24 h). Due to the potentially explosive nature (Figure S19 in the Supporting Information) of **26**, we declined to carry out a comparative batch reaction on the same scale. The ability to safely irradiate large quantities (1400 mL) of the potentially hazardous solution of **26** through a relatively small reactor (53 mL volume) represents a significant safety advance for this useful reaction (Scheme 1).



Scheme 1. Photochemical ring opening and reaction of propellane 26 with butane-2,3-dione in flow.

As was mentioned previously, residence times are commonly used in flow chemistry to assess the efficiency of a reactor. In our own experience with flow photochemistry, we have found residence time to be a less relevant parameter than productivity, especially when comparing batch and flow. For example, the data collected for the cycloaddition of 1 to 3, can be used to compare residence time and productivity as metrics of the efficiency of a reactor. On residence time alone, the Reactor 3 would appear to be superior, that is, two times faster than Reactor 2, and eight faster than Reactor 1 in achieving the same maximum 68% yield. However, analysis of productivities shows



ropean Journa

**Full Paper** 

this approach to be highly misleading, because it is immediately apparent that the three-layer reactor is superior for preparative chemistry (Table 2). For example, running the reaction in Reactor 2 for 22 h gave 63 g of isolated product **3**. In the same time period, Reactor 3 would give approximately 40 g of product.

This highly rewarding study has uncovered a number of features of both batch and flow photochemistry for a wide variety of reactions. When comparing both modes at the same photolysate concentrations, UV lamp powers and wavelengths, three important and general trends are apparent:

- 1) Yields for batch and flow reactors in synthetic photochemistry are essentially the same at full conversion.
- 2) Three-layer FEP reactors have on average 20% higher productivity compared to the same batch end point.
- One-layer FEP reactors have on average 20% lower productivity compared to the same batch end point.

It is straightforward to understand the lower productivity of a one-layer FEP reactor compared to batch due to the shorter path lengths, gaps between channels and the absorption of light by FEP. For example, in scenario A (Figure 4), light entering a tube would encounter some absorption by FEP polymer, before either exciting a substrate molecule or leaving the FEP tube. In scenario B, light could simply pass through the gaps between the FEP tubing. Overall, this would result in less efficient capture of photons in the one-layer reactor compared to batch. Moving to the three-layer system, this reactor consistently exceeded the productivity of the batch reactor by an average of 20%. This enhancement over the one-layer system reflects increased residence time due to the larger reactor volume and the resultant improvement in the capture of photons previously lost through gaps in the channels (scenario B). This leads to an increase in the effective path length, because any light leaving the inner layer would be able to penetrate the second and third layers. It is also interesting to compare the path length of the batch reactor (8.7 mm) with the threelayer flow reactor. Although it is tempting to suggest that the flow reactor path length is similar  $(3 \times 2.7 = 8.1 \text{ mm})$  to batch,

Chem. Eur. J. 2014, 20, 1–8 www.chemeurj.org These are not the final page numbers! 77





Figure 4. Light-transmission scenarios through one-layer and three-layer FEP reactors.

Figure 4 shows that due to the offset layering of the FEP tubing, the effective path length is likely to be significantly less. Combining this with the expected absorption of FEP tubing, one might expect batch to be superior to even the three-layer FEP reactor. Clearly, this is not the case. At present, the superior performance of the FEP reactor is not fully understood and may reflect more complicated factors, such as different concentration gradients between tubes and possible light scattering effects affecting photon path lengths (Figure 4, C).

## Conclusion

In light of this study, the answer to the question-which is better, batch or flow?—is a complex one, as we have shown that both modes can do the same chemistry in essentially identical yields and similar productivities for a range of reactions. Ultimately, scale will likely dictate which reactor the user chooses. For example, batch photochemical reactors are ideal for first-time reactions (and users) due to lower cost, ease of operation, reaction monitoring and ease of optimization. To avoid over-irradiation in batch, it is essential to match the power of the lamp with the concentration of substrate (e.g., entry 10, Table 1). It is likely that in the past, many poorly performing small-scale batch reactions have been unnecessarily discounted due to over-irradiation with an unsuitably matched UV source. Batch reactors using 400 W lamps and 400 mL volume immersion wells are well suited for reactions up to 10-15 g scales, and in some cases, even larger (e.g., entry 11, Table 1). FEP flow reactors are ideal for producing products on scales of greater than 10 g in a single run, and for processing larger volumes safely and efficiently (e.g., 26 to 28, Scheme 1). FEP reactors are also ideal for irradiating large volumes of dilute solutions, which would be impractical in batch mode, especially when using large low-pressure lamps (e.g., entries 5,7 and 12, Table 1).

This study concludes that where productivity is concerned both batch and flow modes of irradiation are equally important in synthetic photochemistry. The choice of one mode over the other depends on what is required from a particular experiment. We hope that these observations will enable firsttime users of photochemistry to choose appropriately. Finally, this study highlights clearly that unless careful steps are taken to compare batch versus flow under the most equitable conditions possible, then it is difficult to make meaningful conclusions between the two. This in turn risks leading to dogmatic assertions over the superiority of one mode over another. This study has been highly revealing and has helped overturn assumptions we have held over our own previous work in the area. Whilst these conclusions hold for the range of photoreactions described in this study, it is unclear whether similar outcomes would be observed for other types of reaction involving light, for example, photocatalysis, photooxygenation and Single Electron Transfer. We hope that similar studies in these areas and other non-photochemical areas of flow chemistry are carried out so that the field can blossom into a technique that is used in conjunction with established batch modes rather than attempt to compete against it.

## **Experimental Section**

#### **General details**

Batch reactions were analysed over time by <sup>1</sup>H NMR using an internal standard (see the Supporting Information for detail). The productivity of a batch reactor was then determined by the amount of product isolated over the reaction time. For short-flow photochemistry runs, at least one reactor volume was allowed to pass through the irradiated reactor (to achieve "steady state") before photolysate was collected for a determined run time. For longer runs of several hours and beyond, the total photolysate was collected. In each case, the product was isolated and purified, and the amount obtained was then extrapolated up or down to match the batch end point.

Batch reactors (Figure 1 a) were standard immersion well quartz reactors fitted with a Pyrex sleeve (36 mm o.d., 33 mm i.d.) that accommodate a 400 W medium pressure Hg lamp and have a typical filled volume of 400 mL, that is, the volume of photolysate that covers the whole length of the Hg lamp. The reactor's effective path length was calculated to be approximately 8.7 mm. Cooling was provided by either mains water or by a glycol/water-chilled circulator. When monochromatic radiation was used, 36 W (40 cm) single ended PL-L lamps (254 or 365 nm) were inserted into the unfiltered quartz immersion well (i.e., no Pyrex sleeve) resulting in approximately 50% immersion (see the Supporting Information for exact power conversions in each case).

400 W flow reactors (Figure 1 a) have been described previously by us and involve 1–3 layers of FEP tubing (2.7 mm i.d., 3.1 mm o.d.) wrapped around a customized water- or glycol-cooled Pyrex immersion well (with sufficient tubing to cover the whole length of the Hg lamp, ca. 15 cm) containing a 400 W medium pressure Hg lamp.<sup>[11]</sup> Reactor volumes: 45 mL (one layer); 145 mL (three layer).

36 W flow reactors (Figure 1 b) have been described previously by us and involve one layer of FEP tubing (2.7 mm i.d., 3.1 mm o.d.) wrapped around a custom quartz tube containing a low pressure 36 W single ended PL-L lamp (254 or 365 nm) cooled by air.<sup>[16]</sup> Reactor volume: 90 mL (one layer).

## Acknowledgements

6

We thank Novartis (L.D.E.), EPSRC EP/K006053/1 (P.J.K.), EPSRC EP/L003325/1 (L.D.E.), University of Bristol (J.P.K.) for Postdoctoral funding, and the EPSRC Bristol Chemical Synthesis Doctoral Training Centre (EP/G036764/1), AstraZeneca, Syngenta

Chem. Eur. J. 2014, 20, 1–8 www

www.chemeurj.org



for PhD studentship funding (K.G.M., M.J.R.). We also thank P. Dinham, D. Mitchell and D. Tarling (University of Bristol) for reactor construction, and C. Heuberger (Novartis, Basel) for DSC analysis of **26**.

**Keywords:** batch reactors · cycloaddition · flow photochemistry · rearrangement · scale-up

- [1] J. C. Pastre, D. L. Browne, S. V. Ley, Chem. Soc. Rev. 2013, 42, 8849-8869.
- [2] I. R. Baxendale, J. Chem. Technol. Biotechnol. 2013, 88, 519-552.
- [3] J. Wegner, S. Ceylan, A. Kirschning, Adv. Synth. Catal. 2012, 354, 17-57.
- [4] J. Yoshida, H. Kim, A. Nagaki, *ChemSusChem* **2011**, *4*, 331–340.
- [5] J. Wegner, S. Ceylan, A. Kirschning, Chem. Commun. 2011, 47, 4583– 4592.
- [6] R. L. Hartman, J. P. McMullen, K. F. Jensen, Angew. Chem. 2011, 123, 7642–7661; Angew. Chem. Int. Ed. 2011, 50, 7502–7519.
- [7] D. Webb, T. F. Jamison, Chem. Sci. 2010, 1, 675-680.
- [8] X. Y. Mak, P. Laurino, P. H. Seeberger, *Beilstein J. Org. Chem.* 2009, *5*, 19.
   [9] J. P. Knowles, L. D. Elliott, K. I. Booker-Milburn, *Beilstein J. Org. Chem.* 2012, *8*, 2025–2052.
- [10] M. Oelgemoeller, Chem. Eng. Technol. 2012, 35, 1144-1152.
- [11] B. D. A. Hook, W. Dohle, P. R. Hirst, M. Pickworth, M. B. Berry, K. I. Booker-Milburn, J. Org. Chem. 2005, 70, 7558-7564.
- [12] C. Birr, W. Lochinger, G. Stahnke, P. Lang, Justus Liebigs Ann. Chem. **1972**, *763*, 162-172.
- [13] A. M. Braun, M-T. Maurette, E. Oliveros, *Photochemical Technology*. Chapter 4, Wiley, Chichester, **1991**.
- [14] M. D. Lainchbury, M. I. Medley, P. M. Taylor, P. Hirst, W. Dohle, K. I. Booker-Milburn, J. Org. Chem. 2008, 73, 6497–6505.
- [15] F. R. Bou-Hamdan, F. Lévesque, A. G. O'Brien, P. H. Seeberger, *Beilstein J. Org. Chem.* 2011, 7, 1124–1129.
- [16] K. G. Maskill, J. P. Knowles, L. D. Elliott, R. W. Alder, K. I. Booker-Milburn, Angew. Chem. 2013, 125, 1539–1542; Angew. Chem. Int. Ed. 2013, 52, 1499–1502.
- [17] D. C. Harrowven, M. Mohamed, T. P. Gonçalves, R. J. Whitby, D. Bolien, H. F. Snedon, *Angew. Chem.* 2012, *124*, 4481–4484; *Angew. Chem. Int. Ed.* 2012, *51*, 4405–4408.
- [18] A. Yavorskyy, O. Shvydkiv, N. Hoffmann, K. Nolan, M. Oelgemöller, Org. Lett. 2012, 14, 4342–4345.
- [19] M. Hurevich, J. Kandasamy, B. M. Ponnappa, M. Collot, D. Kopetzki, D. T. McQuade, P. H. Seeberger, *Org. Lett.* **2014**, *16*, 1794–1797; M. Collot, D. Kopetzki, D. T. McQuade, P. H. Seeberger, *Org. Lett.* **2014**, *16*, 1794– 1797.
- [20] H.-Q. Do, S. Bachman, A. C. Bissember, J. C. Peters, G. C. Fu, J. Am. Chem. Soc. 2014, 136, 2162–2167.
- [21] D. Cantillo, O. de Frutos, J. A. Rincon, C. Mateos, C. O. Kappe, J. Org. Chem. 2014, 79, 223–229.
- [22] T. P. Willumstad, O. Haze, X. Y. Mak, T. Y. Lam, Y. P. Wang, R. L. Danheiser, J. Org. Chem. 2013, 78, 11450–11469.

- [23] S. Cludius-Brandt, L. Kupracz, A. Kirschning, Beilstein J. Org. Chem. 2013, 9, 1745 – 1750.
- [24] D. T. McQuade, A. G. O'Brien, M. Dorr, R. Rajaratnam, U. Eisold, B. Monnand, T. Nobuta, H. D. Lohmannsroben, E. Meggersc, P. H. Seeberger, *Chem. Sci.* 2013, 4, 4067–4070.
- [25] B. G. Anderson, W. E. Bauta, R. C. Cantrell Jr., Org. Process Res. Dev. 2012, 16, 967–975.
- [26] R. S. Andrews, J. J. Becker, M. R. Gagné, Angew. Chem. 2012, 124, 4216– 4219; Angew. Chem. Int. Ed. 2012, 51, 4140–4143.
- [27] Y. S. M. Vaske, M. E. Mahoney, J. P. Konopelski, D. L. Rogow, W. J. McDonald, J. Am. Chem. Soc. 2010, 132, 11379–11385.
- [28] T. Horie, M. Sumino, T. Tanaka, Y. Matsushita, T. Ichimura, J. Yoshida, Org. Process Res. Dev. 2010, 14, 405-410.
- [29] F. Lévesque, P. H. Seeberger, Angew. Chem. 2012, 124, 1738-1741; Angew. Chem. Int. Ed. 2012, 51, 1706-1709.
- [30] D. Kopetzki, F. Lévesque, P. H. Seeberger, Chem. Eur. J. 2013, 19, 5450– 5456.
- [31] M. Fischer, Angew. Chem. 1978, 90, 17–27; Angew. Chem. Int. Ed. Engl. 1978, 17, 16–26.
- [32] For original batch reactions for Table 1 entries 1 and 3, see R. F. Childs, A. W. Johnson, J. Chem. Soc. C 1967, 874–876.
- [33] K. I. Booker-Milburn, J. K. Cowell, F. D. Jiménez, A. Sharpe, A. J. White, *Tetrahedron* **1999**, *55*, 5875–5888.
- [34] K. I. Booker-Milburn, J. R. Baker, I. Bruce, Org. Lett. 2004, 6, 1481–1484.
- [35] P. J. Hickford, J. R. Baker, I. Bruce, K. I. Booker-Milburn, Org. Lett. 2007, 9, 4681–4684.
- [36] R. C. Cookson, E. Crundwell, R. R. Hill, J. Hudec, J. Chem. Soc. 1964, 3062–3075.
- [37] S. D. Banister, M. Manoli, M. L. Barron, E. L. Werry, M. Kassiou, *Bioorg. Med. Chem.* 2013, 21, 6038-6052.
- [38] A. M. Kenwright, J. D. Sellars, Mag. Res. Chem. 2012, 50, 803-808.
- [39] T. Aillet, K. Loubiere, O. Dechy-Cabaret, L. Prat, Chem. Eng. Prog. 2013, 64, 38–47.
- [40] L. D. Elliott, M. Berry, A. J. Orr-Ewing, K. I. Booker-Milburn, J. Am. Chem. Soc. 2007, 129, 3078–3079.
- [41] A. G. Griesbeck, N. Maptue, S. Bondock, M. Oelgemöller, Photochem. Photobiol. Sci. 2003, 2, 450–451.
- [42] K. I. Booker-Milburn, N. J. Costin, R. F. Dainty, D. Patel, A. Sharpe, *Tetrahe-dron Lett.* **1998**, *39*, 7423–7426.
- [43] K. I. Booker-Milburn, C. E. Anson, C. Clissold, N. J. Costin, R. F. Dainty, M. Murray, D. Patel, A. Sharpe, *Eur. J. Org. Chem.* 2001, 1473–1482.
- [44] J. R. Edman, J. Am. Chem. Soc. 1966, 88, 3454-3455.
- [45] J. R. Edman, J. Am. Chem. Soc. 1969, 91, 7103 7107.
- [46] P. Kaszynski, J. Michl, J. Org. Chem. 1988, 53, 4593-4594.
- [47] I. J. Lochert, Ph.D Thesis, Flinders University of South Australia, 1996.

Received: July 10, 2014 Published online on ■■ ■, 0000



# **FULL PAPER**

## Flow Photochemistry

L. D. Elliott, J. P. Knowles, P. J. Koovits, K. G. Maskill, M. J. Ralph, G. Lejeune, L. J. Edwards, R. I. Robinson, I. R. Clemens, B. Cox, D. D. Pascoe, G. Koch, M. Eberle, M. B. Berry, K. I. Booker-Milburn\*

# 

Batch versus Flow Photochemistry: A **Revealing Comparison of Yield and** Productivity

Photochemical Synthesis



Spot the difference! By careful matching of reaction parameters, the performance of 13 different photochemical reactions were compared in both batch and flow reactors. Surprisingly, the yields obtained in the different reactor

modes were essentially identical. Similarly, the productivity differences between the two reactor modes, under the same time scales, were relatively small (see figure).

CHEMISTRY A European Journal

**Full Paper**