

noquinoline.³ It is also very easily accessible from *p*-nitroaniline.

A mixture of 338 g. of *p*-nitroaniline, 130 g. of glycerol, 84 g. of ferrous sulfate, 150 g. of nitrobenzene and 800 g. of concentrated sulfuric acid was heated until reaction set in and the reaction was then checked by discontinuing the heating. When the reaction subsided the mixture was refluxed for three hours, diluted with water, steam-distilled to remove nitrobenzene, and the solution was decolorized with 34 g. of Norit, filtered and neutralized with sodium hydroxide solution. The crude product was dried and purified by extraction with benzene in a Soxhlet apparatus or by distillation; b. p. 160° (2 mm.). Crystallization from benzene or alcohol gave needles, m. p. 173°; yield 200 g. (46%).

Anal. Calcd. for C₁₂H₈N₂: C, 80.0; H, 4.4. Found: C, 79.7; H, 4.5.

(3) Kaufmann and Radosevic, *Ber.*, **42**, 2612 (1909).

DANIEL SIEFF RESEARCH INSTITUTE

REHOVOTH, PALESTINE

RECEIVED JANUARY 2, 1947

Laboratory Disposal of Mercaptan Vapors

BY HUBERT M. HILL¹ AND M. L. WOLFROM

In the course of many years of work with ethyl mercaptan (ethanethiol), the problem of its reeking odor has been ever present. We have been concerned recently with experiments employing this substance as a solvent and with its subsequent removal by evaporation techniques. We have found that these vapors readily can be adsorbed on a column of carbon impregnated with cupric chloride. This principle is not new and has been employed on a large scale by the chemical engineer.² Its adaptation to organic laboratory practice may, however, be of interest.

A good grade of activated carbon (6-14 mesh) of the type used for gas purification or solvent recovery, is impregnated by immersion at room temperature for twenty-four hours in a saturated aqueous solution of cupric chloride. The carbon is then removed by decantation, washed once or twice with water and dried by heating in an open dish to 130° or until hydrogen chloride fumes are evolved. One kilogram of carbon will adsorb 250-300 g. of cupric chloride. This material is then packed in a glass tube which is placed in the directed gas stream containing the volatile mercaptan. The packing converts the thiol to the disulfide with liberation of sufficient heat to require cooling by running water. The packing should be replaced before it is saturated, a condition detectable by the odor of disulfide in the exit gases.

(1) Bristol Laboratories Research Associate of The Ohio State University Research Foundation (Project 224).

(2) Cf. W. L. Nelson, "Petroleum Refinery Engineering," 2nd ed., McGraw-Hill Book Co., New York, N. Y., 1941, p. 586.

DEPARTMENT OF CHEMISTRY
THE OHIO STATE UNIVERSITY
COLUMBUS, OHIO

RECEIVED MARCH 3, 1947

Preparation of Alkyldichloramines

BY L. K. JACKSON, G. N. R. SMART AND GEORGE F. WRIGHT

A method for the preparation of alkyldichloramines which is different from that of Tcherniak¹

(1) J. Tcherniak, *Bull. soc. chim.*, **24**, 451 (1875); *ibid.*, **25**, 160 (1876); *Ber.*, **9**, 146 (1876).

and a modification of that of Berg² has been devised by close regulation of acidity or, better, by introduction of gaseous chlorine into a cold solution of sodium bicarbonate and the free amine.

The crude oils obtained by this treatment are usually sufficiently pure, on the basis of electro-positive chlorine analysis by Chattaway's method,³ that they can be used for subsequent reaction. When they are handled in this manner, especially with a slight excess of contaminant chlorine, they are fairly stable. Distilled material is relatively less stable and some of the distillations are quite dangerous.

The yield and quality of both *n*-butyldichloramine² and *N*-tetrachloro-1,2-diaminoethane³ have been improved over those originally reported. In addition a new primary compound, *n*-octyldichloramine, has been prepared as well as three secondary dichloramines. The *n*-octyldichloramine as well as these *i*-propyl, *s*-butyl and cyclohexyl compounds were not sufficiently stable in the pure state to be shipped for elemental analysis, but were analyzed iodometrically for electro-positive chlorine content.

Experimental

***n*-Butyldichloramine.**—To a solution of 504 g. (6 moles) of sodium bicarbonate in 3 liters of cold water, was added 110 g. (1.5 moles) of butylamine. The mixture was maintained at 8-12° for six hours while chlorine was passed in over this period until saturation was reached. The yellow-orange oil which settled out (density *ca.* 1.1) was separated, washed with cold 5% sulfuric acid, then cold water, and dried with calcium chloride to weigh 187 g. or 88% of theoretical. When a sample was dissolved in acetic acid, treated with potassium iodide and titrated iodometrically it seemed to contain 103% butyldichloramine. The free chlorine which thus was demonstrated to be present was not removed, since it prevented decomposition to butylammonium chloride. The chlorine could be removed by washing with aqueous sodium thiosulfate. If *n*-butyl monochloramine was suspected to be present (low chlorine analyses) it could be removed by a quick wash with cold 50% sulfuric acid, followed by thorough washing with cold water.

When the molar ratio of bicarbonate to amine was decreased to 2:1 the yield was decreased to 74%; when the ratio was decreased to 3:1, the yield was increased to 92%. Although further purification was not usually necessary, the material could be distilled at 39-40° (17 mm.), (b. p. 46° (30 mm.)) *d*₄²⁰, 1.108, *n*_D²⁰ 1.4553. The electropositive chlorine content was 98% of theoretical.

***n*-Octyldichloramine** was prepared in 76% crude yield when a 3:1 ratio of bicarbonate to amine was used. The chlorine addition time was ten hours. The crude (*d*₄²⁰, 1.007) showed an electropositive chlorine content which was 97% of the calculated value.

***s*-Butyldichloramine** was prepared in 96% yield using a 3:1 ratio of bicarbonate to amine over a ten-hour chlorine addition at 10°. The crude material was pure according to its electropositive chlorine content (*d*₄²⁵, 1.116).

Cyclohexyldichloramine was obtained in 95% crude yield under conditions identical with those above. A 90% recovery of product was obtained by distillation; b. p. 89-90° (17 mm.), *d*₄²⁰, 1.199.

***N*-Tetrachloro-1,2-diaminoethane** could be obtained in 92% yield only if an 8:1 bicarbonate-amine ratio was used. Chlorine addition over twelve hours at 10° yielded 70 g. of crude product from 30 g. (0.385 mole) of ethylene diamine

(2) A. Berg, *Ann. chim. phys.*, [7] **3**, 289 (1905).

(3) F. D. Chattaway, *J. Chem. Soc.*, **87**, 381 (1905).