SAFETY DATA SHEET

1. PRODUCT

1.1 Product identifiers

Name: 1-Methoxy-2-propanol

CAS-No.: 107-98-2

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Laboratory chemicals, Synthesis of substances

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 3), H226

Reproductive toxicity (Category 1B), H360

Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram	
Signal word	Danger
Hazard statement(s)	H226 Flammable liquid and vapour. H336 May cause drowsiness or dizziness. H360 May damage fertility or the unborn child.
Precautionary statement(s)	P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/ eye protection/ face protection. P281 Use personal protective equipment as required. P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower. P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell. P308 + P313 IF exposed or concerned: Get medical advice/ attention. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction. P403 + P235 Store in a well-ventilated place. Keep container tightly closed. P403 + P235 Store in a well-ventilated place. Keep cool. P405 Store locked up. P501 Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS

No data available

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Mixtures

Synonyms: Propylene glycol methyl ether

Propyleneglycol monomethyl ether

Formula: $C_4H_{10}O_2$ Molecular weight: 90.12 g/mol

Hazardous components

Component		Classification	Concentration
Monopropylen	e glycol methyl ether		
CAS-No.	107-98-2	Flam. Liq. 3; STOT SE 3; H226, H336	<= 100 %
EC-No.	203-539-1		
2-Methoxyprop	oanol		
CAS-No.	1589-47-5	Flam. Liq. 3; Skin Irrit. 2; Eye Dam. 1; Repr. 1B; STOT SE 3; H226, H315, H318, H335, H360	>= 0.1 -< 1 %
EC-No.	216-455-5	SE 3; H226, H315, H318, H335, H360	

For the full text of the H-Statements mentioned in this Section, see Section 16.

4. FIRST AID MEASURES

4.1 Description of first aid measures

General advice
Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.
If inhaled
If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.
In case of skin contact
Wash off with soap and plenty of water. Consult a physician.
In case of eye contact
Flush eyes with water as a precaution.
If swallowed
Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.2 Indication of any immediate medical attention and special treatment needed

No data available

5. FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

Flash back possible over considerable distance., Container explosion may occur under fire conditions., Vapours may form explosive mixture with air., May form peroxides of unknown stability.

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

Use water spray to cool unopened containers.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

6.4 Reference to other sections

For disposal see section 13.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Avoid inhalation of vapour or mist.

Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Air sensitive. Forms explosive peroxides on prolonged storage May form peroxides on contact with air.

Storage class (TRGS 510): Flammable liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Components with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
Monopropylene glycol methyl ether	107-98-2	TWA	50.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)
	Remarks	Upper Respiratory Tract irritation Eye irritation 2015 Adoption Not classifiable as a human carcinogen		
C. C.		STEL	100.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)
0.11		Upper Respiratory Tract irritation Eye irritation 2015 Adoption Not classifiable as a human carcinogen		
Cir		TWA 100.000000 ppm 360.000000 mg/m3 USA. NIOSH Recommended Exposure Limits		
		ST	150.000000 ppm 540.000000 mg/m3	USA. NIOSH Recommended Exposure Limits
		TWA	50 ppm	USA. ACGIH Threshold Limit Values (TLV)

Component	CAS-No.	Value	Control parameters	Basis
		Upper Respiratory Tract irritation Eye irritation Not classifiable as a human carcinogen		
		STEL 100 ppm USA. ACGIH Threshold Limit Values (TLV)		
		Upper Respiratory Tract irritation Eye irritation Not classifiable as a human carcinogen		
We.		PEL 100 ppm 360 California permissible exposure limits for chemical contaminants (Title 8, Article 107)		
0		Skin		
		STEL	150 ppm 540 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
		Skin		

Hazardous components without workplace control parameters

8.2 Exposure controls

Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Personal protective equipment

	Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).
Skin protection	Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands. Full contact Material: butyl-rubber Minimum layer thickness: 0.3 mm Break through time: > 480 min Material tested:Butoject® (KCL 897 / Aldrich Z677647, Size M) Splash contact Material: Nature latex/chloroprene Minimum layer thickness: 0.6 mm Break through time: 37 min Material tested:Lapren® (KCL 706 / Aldrich Z677558, Size M) data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374 If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.
Body Protection	Impervious clothing, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
Respiratory protection	Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi- purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).
Control of environmen tal exposure	Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance	Form: liquid, clear Colour: colourless		
Odour	No data available		
Odour Threshold	No data available		
pH	No data available		
Melting point/freezing point	No data available		
Initial boiling point and boiling range	118 - 119 °C (244 - 246 °F) - lit.		
Flash point	34 °C (93 °F) - closed cup		
Evaporation rate	No data available		
Flammability (solid, gas)	No data available		
Upper/lower flammability or explosive limits	Upper explosion limit: 16 %(V) Lower explosion limit: 1.8 %(V)		

Vapour pressure	14.5 hPa (10.9 mmHg) at 25 °C (77 °F)		
Vapour density	3.11 - (Air = 1.0)		
Relative density	0.916 g/cm3 at 25 °C (77 °F)		
Water solubility	completely miscible		
Partition coefficient: n-octanol/water	No data available		
Auto-ignition temperature	No data available		
Decomposition temperature	No data available		
Viscosity	No data available		
Explosive properties	No data available		
Oxidizing properties	No data available		

9.2 Other safety information

Relative vapour density: 3.11 - (Air = 1.0)

10. STABILITY AND REACTIVITY

10.1 Reactivity

No data available

10.2 Chemical stability

May form peroxides on prolonged storage. Date container and periodically test for peroxides.

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

Strong oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides

Other decomposition products - No data available

In the event of fire: see section 5

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Mouse - 11,700 mg/kg

Remarks: Behavioral:Convulsions or effect on seizure threshold. Behavioral:Ataxia. Lungs, Thorax, or

Respiration: Dyspnea.

LC50 Inhalation - Rat - 5 h - 10000 ppm LD50 Dermal - Rabbit - 13,000 mg/kg

No data available

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

Eyes - Rabbit

Result: Mild eye irritation - 24 h

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity

No data available No data available

Specific target organ toxicity -single exposure

May cause drowsiness or dizziness

Specific target organ toxicity -repeated exposure

No data available

Aspiration hazard

No data available

Additional Information

RTECS: UB7700000

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly

investigated.

Stomach - Irregularities - Based on Human Evidence Stomach - Irregularities - Based on Human Evidence

12. ECOLOGICAL INFORMATION

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

No data available

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging

Dispose of as unused product

14. TRANSPORT INFORMATION

DOT (US)

UN number: 3092 Class: 3 Packing group: III

Proper shipping name: 1-Methoxy-2-propanol

Reportable Quantity (RQ):
Poison Inhalation Hazard: No

IMDG

UN number: 3092 Class: 3 Packing group: III EMS-No: F-E, S-D

Proper shipping name: 1-METHOXY-2-PROPANOL

IATA

UN number: 3092 Class: 3 Packing group: III
Proper shipping name: 1-Methoxy-2-propanol

15. REGULATORY INFORMATION

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

Massachusetts Right To Know Components

Component	CAS-No.	Revision Date
Monopropylene glycol methyl ether	107-98-2	1994-04-01

Pennsylvania Right To Know Components

Component	CAS-No.	Revision Date
Monopropylene glycol methyl ether	107-98-2	1994-04-01

New Jersey Right To Know Components

Component	CAS-No.	Revision Date
Monopropylene glycol methyl ether	107-98-2	1994-04-01

California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

16. OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3.

Eye Dam. Serious eye damage

Flam. Liq. Flammable liquids

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H360 May damage fertility or the unborn child.

Repr. Reproductive toxicity

Skin Irrit. Skin irritation

STOT SE Specific target organ toxicity - single exposure

HMIS Rating

Health hazard: 2

Chronic Health Hazard: *

Flammability: 3

Physical Hazard 0

NFPA Rating

Health hazard: 2

Fire Hazard: 3

Reactivity Hazard: 0