

MATERIAL SAFETY DATA SHEET

For R&D use only. Not for drug, household or other uses.

Click <http://www.lookchem.com/cas-250/25013-15-4.html> for suppliers of this product.

Composition/Information on Ingredient

Cas:

25013-15-4

Code:

M

RTECS:

Code:

X

Name:

VINYL TOLUENE ALKYD

Other REC Limits:

NK

OSHA PEL:

NK

Code:

M

OSHA STEL:

Code:

ACGIH TLV:

ND

Code:

M

ACGIH STEL:

N/P

Code:

Control Measures

Respiratory Protection:

NK

Ventilation:

RECOMMENDED/LOCAL EXHAUST ADEQUATE

Protective Gloves:

NK

Eye Protection:

NK

Other Protective Equipment:

Equipment NK

Work Hygienic Practices:

WASH WITH WATER

Supplemental Safety and Health:

NK

Health Hazards Data

LD50/LC50/Mixture:

NK

Route Of Entry Inds - Inhalation:

YES

Skin:

YES

Ingestion:

YES

Carcinogenicity Inds - NTP:

N/P

IARC:

N/P

OSHA:

N/P

Health Hazards Acute And Chronic:

NK

Explanation Of Carcinogenicity:

NK 4

Signs And Symptoms Of Overexposure:

EYES:IRRITATION SKIN:MINOR IRRITATION INHALATION:DIZZINESSINGESTION:NAUSEA

Medical Cond Aggravated By Exposure:

NK

First Aid:

EYES:FLUSH W/WATER MINIMUM OF FIVE MINUTES. SKIN:WASH W/WATER INHALATION:REMOVE TO FRESH AIR.CALL PHYS ICIAN.GIVE MOUTH-TO-MOUTH RESUSCITATION IF BREATHING SS. INGESTION:GET MEDICAL HELP

Spill Release Procedures:

MOP UP,SOAK UP,OR WIPE UP IMMEDIATELY.PROVIDE VENTILATION.

Neutralizing Agent:

NK

Waste Disposal Methods:

DO NOT PUNCTURE OR INCINERATE "EMPTY" OR FULL CANS.ONCE SPILLS OR LEAKS ARE CLEANED UP,DISPOSE OF WASTE IN ACCORDANCE WITH GOVERNMENTAL ORDINANCES.

Handling And Storage Precautions:

DO NOT STORE WHERE TEMPERATURE COULD EXCEED 120F

Other Precautions:

USE AND FOLLOW LABEL DIRECTIONS.

Fire and Explosion Hazard Information

Flash Point Method:

N/P

Flash Point:

Flash Point Text:

BELOW 25F

Autoignition Temp:

Autoignition Temp Text:

NK

Lower Limits:

NK

Upper Limits:

NK 5

Extinguishing Media:

WATER FOG,STANDARD FOAM,CO2,DRY CHEMICAL,HALON

Fire Fighting Procedures:

KEEP CONTNRS COOL.USE EQUIP./SHIELDING TO PROTECT PERSONNEL AGAINST BURSTING/VENTING CONTNRS.DONOT PUNCTURE/INCINERATE CONTNR.BURSTING/VENTING W/TEMPS OVER 120F

Unusual Fire/Explosion Hazard:

DO NOT USE NEAR OPEN FLAME, FIRE OR WHILE SMOKING.

Physical/Chemical Properties

HCC:

6 V3

NRC/State LIC No:

NK

Net Prop WT For Ammo:

Boiling Point:

B.P. Text:

NK

Melt/Freeze Pt:

M.P/ F.P Text:

NK

Decomp Temp:

Decomp Text:

NK

Vapor Pres:

40-50

Vapor Density:

NK

Volatile Org Content %:

Spec Gravity:

0.976

VOC Pounds/Gallon:

PH:

NK

VOC Grams/Liter:

Viscosity:

NK

Evaporation Rate & Reference:

NK

Solubility in Water:

SLIGHT

Appearance and Odor:

PAINT/SOLVENT ODOR

Percent Volatiles by Volume:

NK

Corrosion Rate:

NK

Reactivity Data

Stability Indicator:

N/P

Stability Condition To Avoid:

DO NOT STORE ABOVE 120F.

Materials To Avoid:

NK

Hazardous Decomposition Products:

NK

Hazardous Polymerization Indicator:

N/P

Conditions To Avoid Polymerization:

NK

Toxicological Information

Information:

N/P

MSDS Transport Information

Information:

N/P

Regulatory Information

Sara Title III Information:

N/P

Federal Regulatory Information:

N/P

State Regulatory Information:

N/P

Other Information

Other Information:

N/P

LookChem

Look for Chemicals

www.lookchem.com

For R&D use only. Not for drug, household or other uses.

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information with regard to appropriate safety is based on the state of our knowledge and is applicable to the product in the form in which it is shipped. It does not represent any guarantee or warranty of the properties of the product. Lookchem shall not be liable for any damage resulting from handling or from contact with the above product. See reverse side of invoice or packing slip for additional terms and conditions of sale.