

Material Safety Data Sheet

Date Printed: 02/JUN/2005
Date Updated: 17/MAR/2004
Version 1.1
According to 91/155/EEC

Classified as Hazardous according to the criteria of EU Annex 1 and NOHSC.

1 - Product and Company Information

Product Name TITANIUM(III) SULFATE, 99.9+, CA. 45
Product Number WT. % SOLN IN DILUTE SULFURIC ACID
495182
Company Sigma-Aldrich Pty, Ltd
Unit 2, 14 Anella Avenue
Castle Hill NSW 1765
Australia
Technical Phone # +61 2 9841 0555
Fax +61 2 9841 0500
Emergency Phone # +61 2 9841 0566

2 - Composition/Information on Ingredients

Product Name	CAS #	EC no	Annex I Index Number
TITANIUM(III) SULFATE 45% SOLUTION IN DILUTE SULFURIC ACID	None	None	None
Ingredient Name	Percent	CAS #	Annex I Index Number
SULFURIC ACID, >= 51%	55	7664-93-9	231-639-5
Symbols: C			016-020-00-8
R-Phrases: 35			
Causes severe burns.			
TITANIUM(III) SULFATE	45	19495-80-8	None
Formula	O12S3Ti2		
Molecular Weight	383.9 AMU		

3 - Hazards Identification

SPECIAL INDICATION OF HAZARDS TO HUMANS AND THE ENVIRONMENT
Toxic by inhalation. Causes severe burns.

4 - First Aid Measures

AFTER INHALATION

If inhaled, remove to fresh air. If not breathing give artificial respiration. If breathing is difficult, give oxygen.

AFTER SKIN CONTACT

In case of skin contact, flush with copious amounts of water for at least 15 minutes. Remove contaminated clothing and shoes. Call a physician.

AFTER EYE CONTACT

In case of contact with eyes, flush with copious amounts of water for at least 15 minutes. Assure adequate flushing by separating the eyelids with fingers. Call a physician.

AFTER INGESTION

If swallowed, wash out mouth with water provided person is conscious. Call a physician. Do not induce vomiting.

5 - Fire Fighting Measures

CONDITIONS OF FLAMMABILITY

Strong dehydrating agent which may cause ignition of finely divided materials on contact.

EXTINGUISHING MEDIA

Suitable: Use extinguishing media appropriate to surrounding fire conditions.

Unsuitable: Do not use water.

SPECIAL RISKS

Specific Hazard(s): Emits toxic fumes under fire conditions.

SPECIAL PROTECTIVE EQUIPMENT FOR FIREFIGHTERS

Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes.

6 - Accidental Release Measures

PERSONAL PRECAUTION PROCEDURES TO BE FOLLOWED IN CASE OF LEAK OR SPILL

Evacuate area.

PROCEDURE(S) OF PERSONAL PRECAUTION(S)

Wear self-contained breathing apparatus, rubber boots, and heavy rubber gloves.

METHODS FOR CLEANING UP

Cover with dry lime or soda ash, pick up, keep in a closed container, and hold for waste disposal. Ventilate area and wash spill site after material pickup is complete.

7 - Handling and Storage

HANDLING

Directions for Safe Handling: Do not breathe vapor. Do not get in eyes, on skin, on clothing. Avoid prolonged or repeated exposure.

STORAGE

Conditions of Storage: Keep tightly closed.

8 - Exposure Controls / Personal Protection

ENGINEERING CONTROLS

Safety shower and eye bath. Use only in a chemical fume hood.

GENERAL HYGIENE MEASURES

Wash contaminated clothing before reuse. Discard contaminated shoes. Wash thoroughly after handling.

PERSONAL PROTECTIVE EQUIPMENT

Respiratory Protection: Government approved respirator.

Hand Protection: Compatible chemical-resistant gloves.
Eye Protection: Chemical safety goggles.
Special Protective Measures: Faceshield (8-inch minimum).

9 - Physical and Chemical Properties

Appearance	Physical State: Liquid	
Property	Value	At Temperature or Pressure
pH	N/A	
BP/BP Range	N/A	
MP/MP Range	N/A	
Flash Point	N/A	
Flammability	N/A	
Autoignition Temp	N/A	
Oxidizing Properties	N/A	
Explosive Properties	N/A	
Explosion Limits	N/A	
Vapor Pressure	N/A	
SG/Density	1.456 g/cm ³	
Partition Coefficient	N/A	
Viscosity	N/A	
Vapor Density	N/A	
Saturated Vapor Conc.	N/A	
Evaporation Rate	N/A	
Bulk Density	N/A	
Decomposition Temp.	N/A	
Solvent Content	N/A	
Water Content	N/A	
Surface Tension	N/A	
Conductivity	N/A	
Miscellaneous Data	N/A	
Solubility	N/A	

10 - Stability and Reactivity

STABILITY

Stable: Stable.

Materials to Avoid: Strong oxidizing agents, Bases, Halides, Organic materials Incompatible with carbides, chlorates, fulminates, nitrates, picrates, cyanides, alkali halides, zinc iodide, permanganates, hydrogen peroxide, azides, perchlorates, nitromethane, phosphorous, and nitrites. Violent reaction with: cyclopentadiene, cyclopentanone oxime, nitroaryl amines, hexolithium disilicide, and phosphorous(III) oxide, Finely powdered metals

HAZARDOUS DECOMPOSITION PRODUCTS

Hazardous Decomposition Products: Nature of decomposition products not known, Titanium/titanium oxides.

HAZARDOUS POLYMERIZATION

Hazardous Polymerization: Will not occur

11 - Toxicological Information

SIGNS AND SYMPTOMS OF EXPOSURE

Material is extremely destructive to tissue of the mucous membranes and upper respiratory tract, eyes, and skin. Inhalation may result in spasm, inflammation and edema of the larynx and bronchi, chemical pneumonitis, and pulmonary edema.

Symptoms of exposure may include burning sensation, coughing, wheezing, laryngitis, shortness of breath, headache, nausea, and vomiting.

ROUTE OF EXPOSURE

Skin Contact: Causes burns.

Skin Absorption: May be harmful if absorbed through the skin.

Eye Contact: Causes burns.

Inhalation: Material is extremely destructive to the tissue of the mucous membranes and upper respiratory tract. Toxic if inhaled. May be harmful if inhaled.

Ingestion: May be harmful if swallowed.

TARGET ORGAN INFORMATION

Teeth. Cardiovascular system.

12 - Ecological Information

No data available.

13 - Disposal Considerations

SUBSTANCE DISPOSAL

Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber. Observe all federal, state, and local environmental regulations.

14 - Transport Information

RID/ADR

UN#: 3264

Class: 8

PG: II

Proper Shipping Name: Corrosive liquid, acidic, inorganic, n.o.s.

IMDG

UN#: 3264

Class: 8

PG: II

Proper Shipping Name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.

Marine Pollutant: No

Severe Marine Pollutant: No

Technical Name: Required

IATA

UN#: 3264

Class: 8

PG: II

Proper Shipping Name: Corrosive liquid, acidic, inorganic, n.o.s.

Inhalation Packing Group I: No

Technical Name: Required

15 - Regulatory Information

CLASSIFICATION AND LABELING ACCORDING TO EU DIRECTIVES

INDICATION OF DANGER: T

Toxic.

R-PHRASES: 23 35

Toxic by inhalation. Causes severe burns.

S-PHRASES: 45 36/37/39 23 30

In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Wear suitable protective clothing, gloves, and eye/face protection. Do not breathe vapor. Never add water to this product.

16 - Other Information

WARRANTY

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Inc., shall not be held liable for any damage resulting from handling or from contact with the above product. See reverse side of invoice or packing slip for additional terms and conditions of sale. Copyright 2005 Sigma-Aldrich Co. License granted to make unlimited paper copies for internal use only.

DISCLAIMER

For R&D use only. Not for drug, household or other uses.