```
1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING
Product name
                           Selenium oxychloride
```

```
2. HAZARDS IDENTIFICATION
 Classification of the substance or mixture
```

According to Regulation (EC) No1272/2008

Acute toxicity, Inhalation (Category 3) Skin corrosion (Category 1A) Acute aquatic toxicity (Category 1)

Acute toxicity, Oral (Category 3)

Specific target organ toxicity - repeated exposure (Category 2) Chronic aquatic toxicity (Category 1)

According to European Directive 67/548/EEC as amended.

Reacts violently with water. Toxic by inhalation and if swallowed. Danger of cumulative effects. Causes severe burns. Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Label elements Pictogram

Signal word Danger Hazard statement(s) Toxic if swallowed. H301

H314 Causes severe skin burns and eye damage. H331 Toxic if inhaled. H373 May cause damage to organs through prolonged or repeated exposure.

H410 Very toxic to aquatic life with long lasting effects. Reacts violently with water. **EUH014** 

Precautionary statement(s) P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P273 Avoid release to the environment. P280 P301 + P310

IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician. P305 + P351 + P338IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Wear protective gloves/ protective clothing/ eye protection/ face protection.

P310 Immediately call a POISON CENTER or doctor/physician. Hazard symbol(s) T Toxic N Dangerous for the environment

R-phrase(s) R14 Reacts violently with water. Toxic by inhalation and if swallowed. R23/25

**R33** Danger of cumulative effects. **R35** Causes severe burns. R50/53Very toxic to aquatic organisms, may cause long-term adverse effects in

S-phrase(s) S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Wear suitable protective clothing, gloves and eye/face protection. S36/37/39

the aquatic environment.

In case of accident or if you feel unwell, seek medical advice immediately S45 (show the label where possible). This material and its container must be disposed of as hazardous waste. S60 Avoid release to the environment. Refer to special instructions/ Safety data S61 sheets.

Other hazards Vesicant. 3. COMPOSITION/INFORMATION ON INGREDIENTS

Seleninyl chloride

Cl2OSe

232-244-0

165,87 g/mol Molecular Weight CAS-No. EC-No. Classification Concentration Selenium oxychloride

> Acute Tox. 3; Skin Corr. 1A; STOT RE 2; Aquatic Acute 1;

Aquatic Chronic 1; H301,

H314, H331, H373, H410, **EUH014** T, N, R14 - R23/25 - R33 -R35 - R50/53

If inhaled If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician. In case of skin contact Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

# If swallowed

Water

Synonyms

Formula

7791-23-3

4. FIRST AID MEASURES

In case of eye contact

General advice

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

Extinguishing media which shall not be used for safety reasons

Wear self contained breathing apparatus for fire fighting if necessary.

Methods and materials for containment and cleaning up

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

resealed and kept upright to prevent leakage. Store in cool place.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Special protective equipment for fire-fighters

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

For the full text of the H-Statements mentioned in this Section, see Section 16.

Consult a physician. Show this safety data sheet to the doctor in attendance.

5. FIRE-FIGHTING MEASURES Suitable extinguishing media Carbon dioxide (CO2) Dry powder

6. ACCIDENTAL RELEASE MEASURES Personal precautions Wear respiratory protection. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Evacuate

# Soak up with inert absorbent material and dispose of as hazardous waste. Do not flush with water. Keep in suitable, closed containers for disposal.

**Precautions for safe handling** 

7. HANDLING AND STORAGE

personnel to safe areas.

**Environmental precautions** 

environment must be avoided.

Normal measures for preventive fire protection. **Conditions for safe storage** Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves

after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the

multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the

Never allow product to get in contact with water during storage. Moisture sensitive.

## respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU). Hand protection

standard EN 374 derived from it.

Personal protective equipment

Respiratory protection

# Eye protection Tightly fitting safety goggles. Faceshield (8-inch minimum). Use equipment for eye protection tested and

Hygiene measures

product.

Colour

Safety data

рΗ

Melting point

Lower explosion limit

Upper explosion limit

10. STABILITY AND REACTIVITY

Vapour pressure

Water solubility

Chemical stability

Exposure to moisture.

Materials to avoid

Density

approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Skin and body protection Complete suit protecting against chemicals, Flame retardant protective clothing, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the

9. PHYSICAL AND CHEMICAL PROPERTIES **Appearance** clear, liquid Form

Boiling point 180 °C - lit. Flash point not applicable Ignition temperature no data available

yellow

8,5 °C

no data available

no data available

no data available

0,07 hPa at 20 °C

no data available

2,43 g/cm3 at 25 °C

### 5,73 Relative vapour - (Air = 1.0)density

# Possibility of hazardous reactions Reacts violently with water. Conditions to avoid

Stable under recommended storage conditions.

no data available Hazardous decomposition products Hazardous decomposition products formed under fire conditions. - Hydrogen chloride gas, Selenium/selenium oxides 11. TOXICOLOGICAL INFORMATION **Acute toxicity** LD50 Subcutaneous - rabbit - 7 mg/kg Skin corrosion/irritation no data available Serious eye damage/eye irritation no data available

Respiratory or skin sensitization

no data available

no data available

Carcinogenicity

Germ cell mutagenicity

Reproductive toxicity

no data available

no data available

no data available

Inhalation

Ingestion

Potential health effects

**Additional Information** 

12. ECOLOGICAL INFORMATION

Persistence and degradability

PBT and vPvB assessment

13. DISPOSAL CONSIDERATIONS

**Contaminated packaging** Dispose of as unused product.

14. TRANSPORT INFORMATION

UN-Number: 2879 Class: 8 (6.1)

ADR/RID

**IMDG** 

Very toxic to aquatic life with long lasting effects.

RTECS: Not available

**Toxicity** 

no data available

no data available

no data available

no data available

Other adverse effects

Specific target organ toxicity - repeated exposure May cause damage to organs through prolonged or repeated exposure. **Aspiration hazard** 

Specific target organ toxicity - single exposure

Skin Harmful if absorbed through skin. Causes skin burns. Eyes Causes eye burns. Signs and Symptoms of Exposure Material is extremely destructive to tissue of the mucous membranes and upper respiratory tract, eyes, and skin., spasm, inflammation and edema of the larynx, spasm, inflammation and edema of the bronchi, pneumonitis, pulmonary edema, burning sensation, Cough, wheezing, laryngitis, Shortness of breath, Headache, Nausea

**Bioaccumulative potential** no data available Mobility in soil

Packing group: I

Packing group: I

EMS-No: F-A, S-B

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as

membranes and upper respiratory tract.

Toxic if swallowed. Causes burns.

Toxic if inhaled. Material is extremely destructive to the tissue of the mucous

IARC: 3 - Group 3: Not classifiable as to its carcinogenicity to humans (Selenium oxychloride)

probable, possible or confirmed human carcinogen by IARC.

**Product** Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

### UN-Number: 2879 Class: 8 (6.1) Proper shipping name: SELENIUM OXYCHLORIDE Marine pollutant: No **IATA**

Packing group: I Proper shipping name: Selenium oxychloride

# UN-Number: 2879 Class: 8 (6.1)

Acute Tox.

**EUH014** 

Skin Corr.

STOT RE

N

T

R14

R33

R35

R50/53

**Further information** 

H301

Aquatic Acute Aquatic Chronic

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.

# 15. REGULATORY INFORMATION

Proper shipping name: SELENIUM OXYCHLORIDE

16. OTHER INFORMATION Text of H-code(s) and R-phrase(s) mentioned in Section 3

> Causes severe skin burns and eye damage. H314 Toxic if inhaled. H331 H373 May cause damage to organs through prolonged or repeated exposure. H410 Very toxic to aquatic life with long lasting effects.

> > Skin corrosion

Toxic if swallowed.

Acute toxicity

Acute aquatic toxicity

Chronic aquatic toxicity

Reacts violently with water.

Dangerous for the environment Toxic Reacts violently with water. R23/25 Toxic by inhalation and if swallowed.

Causes severe burns.

environment.

Danger of cumulative effects.

For R&D use only. Not for drug, household or other uses. WARRANTY: The above information is believed to be correct but does not purport to be all inclusive and shall be

Specific target organ toxicity - repeated exposure

www.lookchem.com

used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Lookchem shall not be held liable for any damage resulting from handling or from contact with the above product. See reverse side of invoice or packing slip for additional terms and conditions of sale.

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic