

MATERIAL SAFETY DATA SHEET

For R&D use only. Not for drug, household or other uses.

Click <http://www.lookchem.com/cas-287/287-92-3.html> for suppliers of this product.

Composition/Information on Ingredient

Cas:
287-92-3

Code:
M

RTECS:
GY2390000

Code:
M

Name:
CYCLOPENTANE

Other REC Limits:
NOT ESTABLISHED

OSHA PEL:
3 600 PPM

Code:
M

OSHA STEL:

Code:

ACGIH TLV:
600 PPM; 9192

Code:
M

ACGIHSTEL:
N/P

Code:

Control Measures

Respiratory Protection:
USE NIOSH/MSHA APPROVED RESPIRATOR. AIR-SUPPLIED OR FILTERING TYPE WITH ORGANIC VAPOR CARTRIDGES ARE RECOMMENDED.

Ventilation:
LOCAL AND MECHANICAL EXHAUST RECOMMENDED. AVOID OPEN ELECTRICAL SOURCES NEAR PRODUCT VAPOR AREAS.

Protective Gloves:
NEOPRENE, NITRILE, OR POLYVINYL ALCOHOL

Eye Protection:
USE CHEMICAL SAFETY GOGGLES FACESHIELD

Other Protective Equipment:
Equipment EYE WASH STATION SAFETY SHOWER.

Work Hygienic Practices:
DO NOT TAKE INTERNALLY. AVOID SKIN CONTACT. WASH SKIN AFTER USING PRODUCT. DO NOT EAT, DRINK OR SMOKE IN WORK AREA.

Supplemental Safety and Health:
8 FLAMMABLE LIQUID;KEEP AWAY FROM HEAT,OPEN FLAMES AND SPARKS.

Health Hazards Data

LD50LC50Mixture:
N/K

Route Of Entry Inds - Inhalation:
YES

Skin:
YES

Ingestion:
YES

Carcinogenicity Inds - NTP:
NO

IARC:
NO

OSHA:
NO

Health Hazards Acute And Chronic:
ACUTE: OVEREXPOSURE MAY LEAD TO CENTRAL NERVOUS SYSTEM DEPRESSION, LEADING TO IRRITATION, HEADACHE, NAUSEA, DIZZINESS, FATIGUE, CONFUSION AND UNCONSCIOUSNESS. EYE: MAY LEAD TO IRRITATION. SKIN: MAY LE AD TO DERMATITIS. INGESTION: MAY LEAD TOVOMITING. CHRONIC: REPEATED AND PROLONGED SKIN CONTACT MAY CAUSE DERMATITIS.

Explanation Of Carcinogenicity:
DATA PER MSDS 6

Signs And Symptoms Of Overexposure:
OVEREXPOSURE MAY LEAD TO RESPIRATORY IRRITATION, NAUSEA, FATIGUE, DIZZINESS, HEADACHES, UNCONSCIOUSNESS, DERMATITIS AND EYE IRRITATION.

Medical Cond Aggravated By Exposure:
PERSONS WITH A SKIN DISORDER SHOULD USE CAUTION WHEN HANDLING OR USING THIS PRODUCT.

First Aid:
SKIN: REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER. GET MEDICAL ATTENTION IF IRRITATION PERSISTS. INHALATION: REMOVE TO FRESH AIR & RESTORE BREATHING IF NECESSARY. GET MEDICAL ATTENTION. EYE : IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES WHILE HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION. INGESTION: GET IMMEDIATE MEDICAL ATTENTION. DO NOT INDUCE VOMITING. NOTHING BY MOUTH IF UNCONSCIOUS.

Spill Release Procedures:
MINOR: ABSORB MATERIAL WITH CLAY, VERMICULITE, OR SIMILAR ABSORBENT MATERIAL. PLACE IN DISPOSAL CONTAINERS. MAJOR: DIKE & CONTAIN SPILL. ELIMINATE SOURCES OF IGNITION. SHUT OFF LEAKS. REMOVE LIQUID BY VACUUM OR ABSORBENT.

Neutralizing Agent:
NOT APPLICABLE

Waste Disposal Methods:
WASTE MAY BE BURNED IN AN APPROVED INCINERATOR OR DISPOSED OF IN ACCORDANCE WITH ALL APPLICABLE LOCAL, STATE AND FEDERAL LAWS AND REGULATIONS.

Handling And Storage Precautions:
STORE IN A COOL, VENTILATED WORK AREA. KEEP CONTAINERS CLOSED WHEN NOT IN USE. COMBUSTIBLE LIQUID; EMPTY CONTAINERS CAN BE HAZARDOUS.

Other Precautions:
AVOID CONTACT WITH EYES AND SKIN.DO NOT BREATHE VAPORS/MIST.

Fire and Explosion Hazard Information

Flash Point Method:
N/P

Flash Point:
=-45.6C, -50.F

Flash Point Text:
7

Autoignition Temp:

Autoignition Temp Text:
N/K

Lower Limits:
1.1

Upper Limits:
5.9

Extinguishing Media:
USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.

Fire Fighting Procedures:
FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.

Unusual Fire/Explosion Hazard:
HIGHLY FLAM VAPORS,HEAV THAN AIR,MAY ACCUM IN LOW AREAS & SPREAD ALONG GROUND AWAY FROM SITE

Physical/Chemical Properties

HCC:
F2

NRC/State LIC No:
N/R

Net Prop WT For Ammo:

Boiling Point:
=37.2C, 98.1F

B.P. Text:

Melt/Freeze Pt:

M.P/F.P Text:
N/K

Decomp Temp:

Decomp Text:
N/P

Vapor Pres:
13.8

Vapor Density:
2.5

Volatile Org Content %:

Spec Gravity:
0.643

VOC Pounds/Gallon:

PH: N/K

VOC Grams/Liter:

Viscosity:
UNKNOWN

Evaporation Rate & Reference:
>1.0 (N-BUTYL ACETATE=1)

Solubility in Water:
NEGLEGIBLE

Appearance and Odor:
CLEAR LIQUID;MILD GASOLINE ODOR

Percent Volatiles by Volume:
100

Corrosion Rate:
UNKNOWN

Reactivity Data

Stability Indicator:
YES

Stability Condition To Avoid:
HIGH TEMPERATURES, SPARKS, AND OPEN FLAMES

Materials To Avoid:
OXYGEN STRONG OXIDIZERS

Hazardous Decomposition Products:
CARBON MONOXIDE, CARBON DIOXIDE AND OTHER HYDROCARBON COMPOUNDS DURING COMBUSTION.

Hazardous Polymerization Indicator:
NO 9

Conditions To Avoid Polymerization:
NOT APPLICABLE

Toxicological Information

Information:N/P

MSDS Transport Information

Information:N/P

Regulatory Information

Sara Title III Information: N/P

Federal Regulatory Information: N/P

State Regulatory Information: N/P

Other Information

Other Information:N/P