

MATERIAL SAFETY DATA SHEET

For R&D use only. Not for drug, household or other uses.

Click <http://www.lookchem.com/cas-184/18479-58-8.html> for suppliers of this product.

Composition/Information on Ingredient

Cas:

18479-58-8

Code:

M

RTECS:**Code:**

X

Name:

DIHYDRO MYRCENOL RTECS NOT FOUND

Other REC Limits:

NONE RECOMMENDED

OSHA PEL:

NOT ESTABLISHED

Code:

M

OSHA STEL:**Code:****ACGIH TLV:**

NOT ESTABLISHED

Code:

M

ACGIH STEL:

N/P

Code:

Control Measures

Respiratory Protection:

NOT NORMALLY REQUIRED. BUT FOR LARGE SPILLS & ANY SITUATION LEADING TO VERY HIGH EXPOSURE WEAR A NIOSH APPROVED RESPIRATOR FOR ORGANIC VAPORS.

Ventilation:

LOCAL EXHAUST MAY BE NEEDED UNDER SOME CONDITIONS. SPECIFIC NEEDS TO BE ADDRESSED BY SUPERVISORY/HEALTH/SAFETY PERSONNEL

Protective Gloves:

NEOPRENE/OTHER CHEMICAL RESISTANT

Eye Protection:

SAFETY GOGGLES OR FACE SHIELD

Other Protective Equipment:

Equipment APRON OR COVERALLS AS NEEDED TO PREVENT SKIN CONTACT. EYEWASH STATION/SAFETY SHOWER RECOMMENDED.

Work Hygienic Practices:

NK

Supplemental Safety and Health:

NK

Health Hazards Data

LD50/LC50 Mixture:

NK

Route Of Entry Inds - Inhalation:

YES

Skin:

YES

Ingestion:

YES

Carcinogenicity Inds - NTP:

NO

IARC:

NO

OSHA:

NO

Health Hazards Acute And Chronic:

PROLONGED CONTACT MAY CAUSE SKIN IRRITATION. EYE CONTACT MAY CAUSE IRRITATION. INGESTION MAY CAUSE GASTRIC IRRITATION. ANY SITUATION LEADING TO VERY HIGH INHALATION EXPOSURE MAY CAUSE RESPIRATORY IRRITATION.

Explanation Of Carcinogenicity:

NK

Signs And Symptoms Of Overexposure:

NK

Medical Cond Aggravated By Exposure:

NK

First Aid:

EYES: IMMEDIATELY FLUSH W/LARGE AMTS WATER >15 MIN HOLDING LIDS OPEN. GET IMMED MED AID. SKIN: REMOVE CONTAM CLOTHES. WASH THOROUGHLY W/SOAP & WATER. GET MED AID IF ANY SYMPTOMS OVEREXPOSURE OCCUR. INHALATION: MOVE TO FRESH AIR. IF SYMPTOMS DEVELOP GET MEDICAL AID. INGESTION: DON'T INDUCE VOMITING. IF CONSCIOUS/NOT CONVULSIVE GIVE WATER & CALL POISON CONTROL OR DR.

Spill Release Procedures:

WEAR PERSONAL PROTECTIVE EQUIPMENT. REMOVE HEAT/IGNIT SOURCES. VENTILATE AREA. CLEAN UP W/INERT ABSORBENT.

Neutralizing Agent:

NK

Waste Disposal Methods:

DISPOSE OF IN ACCORDANCE W/LOCAL, STATE, FEDERAL REGULATIONS.

Handling And Storage Precautions:

STORE IN A CLOSED CONTAINER IN A COOL DRY AREA.

Other Precautions:

NK

Fire and Explosion Hazard Information

Flash Point Method:

N/P

Flash Point:**Flash Point Text:**

>200F,>93C

Melt/Freeze Pt.:**Melt/Freeze Pt. Text:**

>200F

Decomp Temp.:**Decomp Temp. Text:**

>200F

Decomp Text:

>200F

Vapor Pres.:

NOT EST.

Vapor Pres. Text:

NOT EST.

Vapor Density:

NOT EST.

Volatile Org Content %:

NOT EST.

Spec Gravity:

1.0

VOC Pounds/Gallon:

NOT EST.

pH:

7+-0.5

4**VOC Grams/Liter:**

NOT EST.

Viscosity:

NK

Evaporation Rate & Reference:

COMPLETE

Solubility in Water:

NOT EST.

Appearance and Odor:

PALE YELLOW LIQUID; FLORAL ODOR

Percent Volatiles by Volume:

<10.0

Corrosion Rate:

NK

Autoignition Temp.:

>200F

Autoignition Temp. Text:

>200F

Lower Limits:

NA

Upper Limits:

NA

Extinguishing Media:

CO2, DRY CHEMICAL

Fire Fighting Procedures:

WEAR SCBA.

Unusual Fire/Explosion Hazard:

NK

Physical/Chemical Properties

HCC:**NRC/State LIC No:**

NK

Net Prop WT For Ammo:

NOT EST.

Boiling Point:

NOT EST.

B.P. Text:

>200F,>93C

Melt/Freeze Pt.:**Melt/Freeze Pt. Text:**

>200F

Decomp Temp.:**Decomp Temp. Text:**

>200F

Decomp Text:

>200F

Vapor Pres.:**Vapor Pres. Text:**

NOT EST.

Vapor Density:**Vapor Density Text:**

NOT EST.

Volatile Org Content %:**Volatile Org Content % Text:**

NOT EST.

Spec Gravity:**Spec Gravity Text:**

1.0

VOC Pounds/Gallon:**VOC Pounds/Gallon Text:**

NOT EST.

pH:**pH Text:**

7+-0.5

4**VOC Grams/Liter:****VOC Grams/Liter Text:**

NOT EST.

Viscosity:**Viscosity Text:**

NOT EST.

Evaporation Rate & Reference:

COMPLETE

Solubility in Water:

NOT EST.

Appearance and Odor:

PALE YELLOW LIQUID; FLORAL ODOR

Percent Volatiles by Volume:

<10.0

Corrosion Rate:**Corrosion Rate Text:**

NOT EST.

Autoignition Temp.:**Autoignition Temp. Text:**

>200F

Autoignition Temp.:**Autoignition Temp. Text:**

>200F