MATERIAL SAFETY DATA SHEET For R&D use only. Not for drug, household or other uses.

Click http://www.lookchem.com/cas-121/12136-45-7.html for suppliers of this product.

Т **RTECS:** Code:

NΡ

NΡ

NP Code:

NP Code:

NΡ Code:

Code:

OSHA PEL:

OSHA STEL:

ACGIH TLV:

ACGIHSTEL:

Ventilation:

Protective Gloves:

Eye Protection: SPLASH GOGGLES

NP

YES

Skin: YES

YES

IARC: NO

OSHA: NO

HARM.

First Aid:

IMMEDIATELY.

Spill Release Procedures:

Waste Disposal Methods:

Neutralizing Agent:

Other Precautions:

Flash Point Method:

SCC

N/A

N/R

N/R

HCC: F2

NRC/State LIC No:

Boiling Point: =54.4C, 130.F

Melt/Freeze Pt:

M.P/F.P Text:

Decomp Temp:

Decomp Text:

Vapor Pres:

Vapor Density: >1 (AIR=1)

Spec Gravity: 0.99 + / - 0.03

PH: N/R

Viscosity:

NEGLIGIBLE

N/P

N/A

YES

NO

VOC Pounds/Gallon:

VOC Grams/Liter:

Solubility in Water:

Corrosion Rate:

Stability Indicator:

Materials To Avoid: STRONG OXIDIZERS

Information:N/P

Information:N/P

Appearance and Odor:

Percent Volatiles by Volume:

Reactivity Data

Stability Condition To Avoid:

NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:

Hazardous Polymerization Indicator:

Conditions To Avoid Polymerization: NONE SPECIFIED BY MANUFACTURER.

Toxicological Information

Regulatory Information

Sara Title III Information: N/P

Federal Regulatory Information: N/P

State Regulatory Information: N/P

Other Information

Look for Chemicals

www.lookchem.com

Other Information:N/P

MSDS Transport Information

For R&D use only. Not for drug, household or other uses.

terms and conditions of sale.

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any

guarantee of the properties of the product. Lookchem shall not be held liable for any damage resulting from

handling or from contact with the above product. See reverse side of invoice or packing slip for additional

CARBON DIOXIDE, CARBON MONOXIDE, SMOKE, FUMES.

Evaporation Rate & Reference:

BLACK LIQUID WITH TOLUENE/KETONE ODOR.

Volatile Org Content %:

N/R

N/A

B.P. Text:

Net Prop WT For Ammo:

Flash Point: =-4.4C, 24.F

Flash Point Text:

Autoignition Temp:

Lower Limits:

Upper Limits:

Extinguishing Media:

Fire Fighting Procedures:

Unusual Fire/Explosion Hazard:

CARBON DIOXIDE, DRY CHEMICAL, FOAM

MATERIAL HANDLING POINT. FLAMMABLE.

Physical/Chemical Properties

Autoignition Temp Text:

CONTAINER(S) FOR DISPOSAL 3

NONE SPECIFIED BY MANUFACTURER.

Handling And Storage Precautions:

Ingestion:

Control Measures

ENVIRONMENTAL CONTROLS.

THE PROPER VENTILATION.

RUBBER OR NEOPRENE

Other Protective Equipment:

NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health:

Health Hazards Data

NONE SPECIFIED BY MANUFACTURER.

Route Of Entry Inds - Inhalation:

Carcinogenicity Inds - NTP:

Health Hazards Acute And Chronic:

Explanation Of Carcinogenicity:

SEE HEALTH HAZARDS

Signs And Symptions Of Overexposure:

Medical Cond Aggravated By Exposure: NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices:

LD50LC50Mixture:

Equipment USE PROTECTIVE CLOTHING IMPERVIOUS TO THIS MATERIAL. 4

Respiratory Protection:

Code:

Cas: 12136-45-7

Composition/Information on Ingredient

X 2 Name: POTASSIUM OXIDE

NIOSH/OSHA APPROVED ORGANIC VAPOR-TYPE RESPIRATOR RECOMMENDED IN THE ABSENCE OF PROPER

EYES: MAY CAUSE IRRITATION. SKIN: MAY CAUSE IRRITATION OR SENSITIZATION. INHALATION: ISOCYANATES MAY CAUSE

RESPIRATORY DISTRESS, ORASTHMATIC ATTACK. MAY CAUSE HEADACHE, NAUSEA, DIZZINESS, FATIGUE.

USE, HANDLING, TREATMENT, STORAGE, DISPOSAL AND TRANSPORTATION OF HAZARDOUS WASTE.

FIRE FIGHTERS SHOULD WEAR SELF-CONTAINED, POSITIVE PRESSURE, BREATHING APPARATUS.

VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL ALONG THE GROUND OR BY VENTILATION TO IGNITION SOURCES FAR FROM

STORE INDOORS IN TIGHTLY CLOSED CONTAINERS. STORE BETWEEN 50F AND 95F.

Fire and Explosion Hazard Information

RESPIRATORY IRRITATION OR SENSITIZATION. SYMPTOMS COULD BE IMMEDIATE OR DELAYED AND INCLUDE C HEST TIGHTNESS,

THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS, REPRODUCTIVE

EYES: FLUSH EYES WITH WATER FOR AT LEAST 15 MINUTES AND GET MEDICAL ATTENTION. SKIN: WASH WELL WITH SOAP AND WATER. INHALATION: REMOVE PERSON TO FRESH AIR AND GET MEDICAL ATTENTION. INGESTION: GET MED ICAL ATTENTION

SPILL WITH ABSORBENT MATERIAL. USE NON-SPARKING TOOLS. PUMP DIKED MATERIAL AND SCOO P ABSORBED MATERIAL INTO

SECURE IGNITION SOURCES. WEAR PROTECTIVE EQUIPMENT. DIKE, IF NECESSARY TO PREVENT SPREAD OF SPILL. COVER AND CONTAIN

DISPOSE OF IN COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE/PROVINCIAL AND LOCAL STATUS REGARDING THE MANAGEMENT,

FLAMMABLE. KEEP FROM HEAT, SPARKS AND FLAME. USE APPROPRIATE GROUNDING EQUIPMENT WHILE HANDLING THIS MATERIAL.

BY LAW, THE EXPOSURE MUST BE REDUCED TO OR BELOW THE PEL. IF NECESSARY, CONSULT A SPECIALIST FOR

Other REC Limits: