MATERIAL SAFETY DATA SHEET For R&D use only. Not for drug, household or other uses. Click http://www.lookchem.com/cas-108/108-05-4.html for suppliers of this product.

Cas: 108-05-4 Code: Μ

RTECS: AK0875000 Code:

Μ

Name:

NΡ

OSHA PEL:

OSHA STEL:

ACGIH TLV:

10 PPM/15,A3 STEL;93

Waste Disposal Methods:

Other Precautions:

Flash Point Method:

N/P

N/A

Flash Point:

Flash Point Text: NONE FLAMMABLE

Autoignition Temp:

Lower Limits:

Upper Limits:

Extinguishing Media:

N/A ACCD TO MFR

NRC/State LIC No:

Boiling Point:

Melt/Freeze Pt:

M.P/F.P Text:

Decomp Temp:

Decomp Text:

Vapor Pres:

Vapor Density:

Spec Gravity:

VOC Pounds/Gallon:

VOC Grams/Liter:

SLOWER THAN ETHER

Appearance and Odor:

Percent Volatiles by Volume:

Reactivity Data

Stability Condition To Avoid: EXTREME HEAT OVER 200F

Hazardous Decomposition Products:

Hazardous Polymerization Indicator:

Conditions To Avoid Polymerization:

Toxicological Information

Regulatory Information

Sara Title III Information: N/P

Federal Regulatory Information: N/P

State Regulatory Information: N/P

Other Information

www.lookchem.com

Other Information:N/P

MSDS Transport Information

For R&D use only. Not for drug, household or other uses.

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any

guarantee of the properties of the product. Lookchem shall not be held liable for any damage resulting from

handling or from contact with the above product. See reverse side of invoice or packing slip for additional

WARRANTY

terms and conditions of sale.

Solubility in Water:

Corrosion Rate:

Stability Indicator:

Materials To Avoid:

Evaporation Rate & Reference:

CONSISTENCY OF CREAM; SLIGHT PAINT ODOR.

OIL OIL BASE MATERIALS, PETROLEUM DISTILLATES, STRONG ACIDS.

Volatile Org Content %:

N/A

N/A

024

>1.0 6

1.3600

PH: N/P

Viscosity:

COMPLETE

N/P

50

N/P

N/P

Information:N/P

Information:N/P

B.P. Text: 212F

Net Prop WT For Ammo:

N/A 5

HCC: N1

N/A

Fire Fighting Procedures:

Unusual Fire/Explosion Hazard:

Physical/Chemical Properties

Autoignition Temp Text:

Handling And Storage Precautions: KEEP MATERIAL FROM FREEZING.

MFR RECM DISPOSE IN LANDFILL IAW FED, STATE & LOCAL CODES.

Fire and Explosion Hazard Information

Code:

Code:

Code: Μ

Μ

VINYL ACETATE (SARA III)

Other REC Limits:

10 PPM/15 STEL

Composition/Information on Ingredient

ACGIHSTEL: NΡ Code: **Control Measures Respiratory Protection:** NIOSH/MSHA APPROVED RESPIRATOR WHEN SPRAYING PAINT

Ventilation: ADEQUATE VENTILATION **Protective Gloves:** NOT NEC REQD **Eye Protection:** SPLASH PROOF SAFETY GOG

Other Protective Equipment: Equipment EYE WASH EQUIPMENT **Work Hygienic Practices: NP Supplemental Safety and Health:** ADDITIONAL INGREDIENTS:WATER, 43.6%;COLORANTS, 1.0%; SURFACTANTS, 1.0%.

Health Hazards Data LD50LC50Mixture: N/P **Route Of Entry Inds - Inhalation:** N/P Skin: N/P Ingestion:

N/P **Carcinogenicity Inds - NTP:** N/P **IARC:** N/P

OSHA: N/P **Health Hazards Acute And Chronic:** N/P **Explanation Of Carcinogenicity:** N/P **Signs And Symptions Of Overexposure:** VAPOR MAY BE IRRIT TO EYES, SKIN, MAY CAUSE SYMPTOMS OF HEADACHE, NAUSEA IN POORLY VENTIL AREAS. **Medical Cond Aggravated By Exposure:** N/P SKIN CONTACT: WASH THOROUGHLY W/SOAP & WATER. EYES: FLUSH W/PLENTY OF WATER FOR 15 MIN. CALL PHYSICIAN. IF EXPOSED TO LARGE AMOUNTS OF SPRAY MIST REMOVE TO FRESH AIR. INGEST: 4 INDUCE VOMITING. CALL MD.

Spill Release Procedures: ABSORB SPILL, FLUSH W/LARGE AMOUNTS OF WATER IMMED. TRANSFER TO CONTAINERS FOR RECOVERY OR DISPOSAL. DO NOT FLUSH DOWN SEWER SYSTEM. **Neutralizing Agent:** N/P