

MATERIAL SAFETY DATA SHEET

For R&D use only. Not for drug, household or other uses.

Click <http://www.lookchem.com/cas-801/8012-89-3.html> for suppliers of this product.

Composition/Information on Ingredient

Cas:
8012-89-3

Code:
M

RTECS:

Code:
X

Name:
REFINED BEESWAX

Other REC Limits:
NOT ESTABLISHED

OSHA PEL:
NOT ESTABLISHED

Code:
M

OSHA STEL:

Code:

ACGIH TLV:
NOT ESTABLISHED

Code:
M

ACGIH STEL:

Code:

Control Measures

Respiratory Protection:
NONE SHOULD BE NEEDED

Ventilation:
MECH(EN)OR LOCAL EXHAUST THAT PROVIDES ADEQUATE VENTILATION

Protective Gloves:
IMPERVIOUS

Eye Protection:
SAFETY GLASSES/GOGGLES

Other Protective Equipment:
Equipment PROTECTIVE CLOTHINGS.EYE-WASH FACILITIES,SAFETY SHOWER.

Work Hygienic Practices:
AVOID CONTACT WITH EYES AND SKIN.

Supplemental Safety and Health:
4 WORK IN GOOD VENTILATION SYSTEM.

Health Hazards Data

LD50/LC50 Mixture:
N/K

Route Of Entry Inds - Inhalation:
N/P

Skin:
N/P

Ingestion:
N/P

Carcinogenicity Inds - NTP:
NO

IARC:
NO

OSHA:
NO

Health Hazards Acute And Chronic:
2 N/P

Explanation Of Carcinogenicity:
DATA PER MGF MSDS.

Signs And Symptoms Of Overexposure:
SEE HEALTH HAZARDS DATA.

Medical Cond Aggravated By Exposure:
PRE-EXISTING CONDITIONS MAY BE WORSEN.

First Aid:
NORMAL FIRST AID FOR BURNS

Spill Release Procedures:
SWEEP OR SCRAPE INTO CONTAINER FOR RECOVERY OR DISPOSAL

Neutralizing Agent:
N/R

Waste Disposal Methods:
CONSULT LOCAL AUTHORITIES;DISPOSAL MUST BE IN ACCORDANCE WITH LOCAL,STATE AND FEDERAL REGULATIONS

Handling And Storage Precautions:
STORE IN COOL,DRY AND WELL VENTILATED AREA.KEEP AWAY FROM EXTREME HEAT.

Other Precautions:
WASH THOROUGHLY AFTER EACH USE.

Fire and Explosion Hazard Information

Flash Point Method:

N/P

Flash Point:

Flash Point Text:

>490F,>254C

Autoignition Temp:

Autoignition Temp Text:

N/A

Lower Limits:

N/K

Upper Limits:

N/K

Extinguishing Media:

CO₂, FOAM, DRY CHEM.

Fire Fighting Procedures:

FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.

Unusual Fire/Explosion Hazard:

KEEP MELTED WAX AWAY FROM OPEN FLAME

Physical/Chemical Properties

HCC:

N1

NRC/State LIC No:

N/R

Net Prop WT For Ammo:

N/P

Boiling Point:

N/P

Melt/Freeze Pt:

143F/62C

Decomp Temp:

143F/62C

Decomp Text:

UNKNOWN

Vapor Pres:

N/K

Vapor Density:

N/K

Volatile Org Content %:

N/K

Spec Gravity:

N/K

VOC Pounds/Gallon:

N/K

PH:

N/K

VOC Grams/Liter:

N/K

Viscosity:

N/P

Evaporation Rate & Reference:

N/K

Solubility in Water:

NIL

Appearance and Odor:

SOLID OF VARIABLE YELLOW OR ORANGE COLOR,AGREEABLE AROMA

Percent Volatiles by Volume:

N/K

Corrosion Rate:

UNKNOWN

Reactivity Data:

N/K

Stability Condition To Avoid:

N/K

Hazardous Decomposition Products:

N/K

Conditions To Avoid Polymerization:

N/K

Toxicological Information

Information:

N/P

MSDS Transport Information

Information:

N/P

Regulatory Information

Sara Title III Information:

N/P

Federal Regulatory Information:

N/P

State Regulatory Information:

N/P

Other Information

Other Information:

N/P

For R&D use only. Not for drug, household or other uses.

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information with regard to appropriate safety is based on our present knowledge and is not a guarantee of the properties of the product. Lookchem shall not be held liable for any damage resulting from handling or contact with the above product. See reverse side of invoice or packing slip for additional terms and conditions of sale.

