

Morphology-Controllable Synthesis of CeO₂ on a Pt Electrode

Y. Fu · Z. D. Wei · M. B. Ji · L. Li · P. K. Shen ·
J. Zhang

Received: 13 August 2008 / Accepted: 11 September 2008 / Published online: 30 September 2008
© to the authors 2008

Abstract Nanoscale cerium dioxides with shape of nanoparticles, nanorods, and nanotubes were electrochemically synthesized. The morphology of CeO₂ was modulated by changing electrode potential and potential direction. CeO₂ nanorods and CeO₂ nanotubes were synthesized via the potentiostatic and cyclic voltammetric methods, respectively. The morphology and structure of the obtained CeO₂ were characterized by field emission scanning electron microscope (FESEM) and X-ray diffraction (XRD). A possible formation mechanism has been suggested to illuminate the relationship between the preparation condition and the morphology of CeO₂.

Keywords CeO₂ · Nanorod · Nanotube · Electrosynthesis

Introduction

The one-dimension (1D) nanostructure has attracted much attention since the discovery of carbon nanotubes (CNTs) in 1952 [1] and has offered great potential for applications in the electric devices, sensors, and others uses [2]. Controlled synthesis of inorganic nanoparticles now is one of the important topics in colloid and material chemistry for their shape-dependent properties and potentials of self-assembly as building blocks-artificial atoms with diverse superstructures and mesocrystals [3, 4]. Much effort has been devoted to the design and preparation of nanostructures with different shapes and sizes. The morphology-controllable synthesis of nanostructured metal compounds, such as PbSe [5], ZnO [6, 7], In(OH)₃ [8], SnO₂ [9], and V₂O₅ [10], has been successfully developed.

As one of the most active rare earth materials, ceria (cerium oxide, CeO₂) has been extensively used in catalysts, fuel cells, solar cells, and polishing materials [11, 12]. Stimulated by promising applications and the fantastic properties, much attention has been directed to the controlled synthesis of CeO₂ nanostructured materials. Up to now, several strategies have been demonstrated to fabricate CeO₂ nanotubes, such as arc discharge, chemical vapor deposition, template-directed synthesis, and hydrothermal treatment. CeO₂ nanostructured materials with ordered mesoporous cerium oxides [13], (100) oriented CeO₂ films [14], nanorods [15], nanowires [16], nanotubes [17–19], nanocubes [20], nanospheres [21], and nanobelts [22] have been reported. Most recently, Han et al. [18] reported the production of ceria nanotubes via a two-step procedure, precipitation at 100 °C and aging at 0 °C for 45 days. Tang et al. [19] also reported layer-structured rolling Ce(OH)₃ nanotubes through an alkali thermal-treatment process under oxygen-free conditions. Evidently, the methods used

Y. Fu · Z. D. Wei (✉)
State Key Laboratory of Power Transmission Equipment &
System Security and New Technology, Chongqing University,
Chongqing 400044, China
e-mail: zdwei@cqu.edu.cn

Y. Fu · Z. D. Wei
School of Chemistry and Chemical Engineering,
Chongqing University, Chongqing 400044, China

Z. D. Wei · M. B. Ji · L. Li · J. Zhang
School of Material Science and Engineering,
Chongqing University, Chongqing 400044, China

P. K. Shen (✉)
The State Key Laboratory of Optoelectronic Materials and
Technologies, Sun Yat-Sen University, Guangzhou 510275,
China
e-mail: stsspk@sysu.edu.cn

for synthesis of CeO₂ nanostructured materials are usually complicated and time-consuming. An effective method is necessary for production of high-quality ceria nanotubes in terms of yield, uniformity, and shape control. However, it has been a challenge for the effective synthesis of CeO₂ nanostructured materials so far.

In this work, we report for the first time one-step synthesis of CeO₂ nanoparticles, nanorods, and nanotubes via an electrochemically synthesized route. The morphology was modulated by changing the electric field, strength, and direction. A possible formation mechanism of CeO₂ nanostructured materials has been suggested to illuminate the relationship between the preparation condition and the morphology of yielded CeO₂.

Experimental

Preparation of CeO₂ Nanostructured Materials

CeO₂ was potentiostatically and cyclic voltammetrically synthesized on a Pt electrode, and accordingly, the synthesized CeO₂ are named as ps-CeO₂ and cv-CeO₂, respectively. In the potentiostatically synthesized CeO₂, the Pt electrode potential was kept at 1.2 V (versus KOH saturated Hg/HgO) for a length of 30, 85, and 130 s in a bath of 0.05 M Ce(NO₃)₃ · 6H₂O and 0.1 M NH₄NO₃ at room temperature. The pH of the solution was adjusted to 6 by NH₄OH. In the cyclic voltammetrically synthesized cerium oxide, CeO₂ was prepared on a Pt electrode by cycling potential between 0.5 and 1.4 V at a sweep rate of 20, 30, and 50 mV s⁻¹, respectively, for 120 min in the same bath as used in the potentiostatical synthesis.

Morphologies Characterization

XRD analysis of CeO₂ was carried out on the D/max-1200 diffractometer (Japan) using a Cu K α X-ray source operating at 45 kV and 100 mA, scanning at the rate of 4°/min with an angular resolution of 0.05° of the 2θ scan to get the

XRD patterns. The morphologies of the CeO₂ were studied on a FEI Nova 400 field emission scanning electron microscope (FESEM) (Peabody, Netherland).

Results and Discussion

Morphologies of Synthesized CeO₂ Nanostructured Materials

Figure 1 shows the XRD pattern of the synthesized ps-CeO₂ sample. The diffraction peaks corresponding to the different planes of CeO₂ are marked in Fig. 1. The diffraction peaks can be indexed to the face-centered cubic structure of CeO₂ (space group Fm3 m) with a lattice constant of 0.5410 nm according to JCPDS 78-0694 [15, 23].

Figure 2 shows the growth history of ps-CeO₂ generated potentiostatically at 1.2 V with different lengths of anodic oxidation. As seen, only a few of nanoparticles with size of 15–50 nm (measured from the SEM micrograph and consistent with the crystallite size calculated from XRD) are present on the smooth Pt surface as the





Fig. 1 XRD spectrum of ps-CeO₂ prepared at 1.2 V for 30 s

Fig. 2 FESEM images of ps-CeO₂ prepared at 1.2 V for 30 s (**a**), 85 s (**b**), and 130 s (**c**)



anodic oxidation lasts for 30 s. When the anodic oxidation lasts for 85 s, more CeO_2 spherical crystallites form. Meanwhile, a clear grain boundary is also observed. It indicates that obtained CeO_2 crystallites are constituted by the oriented aggregation of small CeO_2 nanoparticles. The diameter of the CeO_2 nanoparticles is in the range of 20–100 nm calculated by statistical software with the FESEM. With the time of anodic oxidation further increasing to 130 s, number of isolated nanoparticles began to reduce, but nanorods are nearly the sole products as illustrated in Fig. 2c, in which CeO_2 nanorods plus many tiny interconnected nanoparticles are present. The similar structure CeO_2 was synthesized previously via ultrasonication approach with aid of polyethylene glycol as a structure-directing agent [15]. Figure 3 shows morphologies of CeO_2 nanotubes synthesized by the way of CV between 0.5 and 1.4 V at different sweep rates. Figure 3 shows the curve degree of CeO_2 nanotubes increases with the potential sweep rate. That is, the curve degree of CeO_2 nanotubes increases with the potential sweep rates from 20, and then 30, and finally to 50 mV s^{-1} , which is really interesting. Nanoscale CeO_2 synthesized potentiostatically has rod-shape morphology, but those synthesized cyclic-voltammetrically has curve-shape morphology. In short, the morphologies of CeO_2 sized in nanoscale from nanoparticles, nanorods, and to nanowires can be fabricated by simply changing the potential direction and time of anodic oxidation. Why does the curve degree of CeO_2 nanotubes increase with potential sweep rates? The following abecedarian mechanism about CeO_2 nanotube growth was suggested.

Fig. 3 FESEM images of cv- CeO_2 prepared at a sweep rate of 20 mV s^{-1} (**a**), 30 mV s^{-1} (**b**), and 50 mV s^{-1} (**c**) for 2 h







Fig. 4 Possible mechanism of CeO_2 nanorod and nanotubes growth



Possible Formation Mechanism of CeO_2 Nanotubes

Oxidation of Ce (III) to CeO_2 can be accomplished electrochemically in reaction (1) or chemically in reaction (2). In this work, CeO_2 is synthesized electrochemically.



Since an instantaneous nucleation and growth mechanism cannot explain the morphology-controllable synthesis of CeO_2 , the formation of CeO_2 nanorods and nanotubes is assumed to experience the process as illustrated in Fig. 4. The CeO_2 nanoparticles adsorb OH^- ions and fuse them together by hydrogen bonding. Adsorbed OH^- on the surfaces of CeO_2 will further adsorb Ce^{3+} ions, and then OH^- and Ce^{3+} ions combine to CeO_2 with one electron release. OH^- and Ce^{3+} ions are electrically adsorbed on the surfaces of CeO_2 in an oriented manner under pulling force of the direct current electric field and fused together. It leads to the formation of CeO_2 nanorods. Thus, if OH^- and Ce^{3+} ions are electrically adsorbed on the surfaces of CeO_2 under pulling force of a continuously changed electric field direction and fused together, it will certainly lead to the formation of CeO_2 curved nanotubes. The stronger the electric field direction changes, the more frequently the position of adsorbed OH^- and Ce^{3+} ions on the surfaces of CeO_2 moves, the more

curved the CeO₂ nanotubes will be. It is not strange why CeO₂ nanotubes with a different curved degree were generated at different potential sweep rates.

Conclusions

CeO₂ nanoparticles, nanorods, and nanotubes were electrochemically fabricated via a one-step route. The morphology of CeO₂ can be modulated by changing electrode potential and potential direction. At constant electric field, such as the way of potentiostatic, OH⁻ and Ce³⁺ ions are electrically adsorbed onto the surfaces of CeO₂ in an oriented manner under pulling force of the direct current electric field and fused together. It leads to the formation of CeO₂ nanorods. Curved CeO₂ nanotubes can be produced by a continuously changing electric field direction, such as cyclic voltammetry. The curved degrees of CeO₂ nanotubes can be modulated by changing electrode potential sweep rates.

Acknowledgments This work was financially supported by NSFC of China (Grant Nos 20476109 and 20676156), by the Chinese Ministry of Education (Grant No. 307021), China National 863 Program (2007AA05Z124), Chongqing and Guangdong Sci. & Tech. Key Projects, China (CSTC2007AB6012, 2007A010700001, and 2007B090400032).

References

- M. Monthioux, V.L. Kuznetsov, Carbon **44**, 1621 (2006). doi: [10.1016/j.carbon.2006.03.019](https://doi.org/10.1016/j.carbon.2006.03.019)
- P.M. Ajayan, Chem. Rev. **99**, 1787 (1999). doi: [10.1021/cr970102g](https://doi.org/10.1021/cr970102g)
- M. Law, D.J. Sirbuly, J.C. Johnson, J. Goldberger, R.J. Saykally, P.D. Yang, Science **305**, 1269 (2004). doi: [10.1126/science.1100999](https://doi.org/10.1126/science.1100999)
- E.V. Shevchenko, D.V. Talapin, C.B. Murray, S. O'Brien, J. Am. Chem. Soc. **128**, 3620 (2006). doi: [10.1021/ja0564261](https://doi.org/10.1021/ja0564261)
- E. Lifshitz, M. Bashouti, V. Kloper, A. Kigel, M.S. Eisen, S. Berger, Nano Lett. **3**, 857 (2003). doi: [10.1021/nl0342085](https://doi.org/10.1021/nl0342085)
- Y. Zhang, F. Zhu, J.X. Zhang, Nanoscale Res. Lett. **6**, 201 (2008). doi: [10.1007/s11671-008-9136-2](https://doi.org/10.1007/s11671-008-9136-2)
- L. Vayssieres, Adv. Mater. **15**, 464 (2003). doi: [10.1002/adma.200390108](https://doi.org/10.1002/adma.200390108)
- L.A. Perez-Maqueda, L. Wang, E. Matijevic, Langmuir **14**, 4397 (1998). doi: [10.1021/la980149c](https://doi.org/10.1021/la980149c)
- H.V. Fajardo, E. Longo, L.F.D. Probst, A. Valentini, N.L.V. Carreño, M.R. Nunes, A.P. Maciel, E.R. Leite, Nanoscale Res. Lett. **5**, 194 (2008). doi: [10.1007/s11671-008-9135-3](https://doi.org/10.1007/s11671-008-9135-3)
- N. Pinna, M. Willinger, K. Weiss, J. Urban, R. Schlogl, Nano Lett. **3**, 1131 (2003). doi: [10.1021/nl034326s](https://doi.org/10.1021/nl034326s)
- P.K. Shen, C.W. Xu, Electrochim. Commun. **8**, 184 (2006). doi: [10.1016/j.elecom.2005.11.013](https://doi.org/10.1016/j.elecom.2005.11.013)
- D.H. Lim, W.D. Lee, D.H. Choi, H.H. Kwon, H.I. Lee, Electrochim. Commun. **10**, 592 (2008). doi: [10.1016/j.elecom.2008.02.001](https://doi.org/10.1016/j.elecom.2008.02.001)
- D.M. Lyons, K.M. Ryan, M.A. Morris, J. Mater. Chem. **12**, 1207 (2002). doi: [10.1039/b104677m](https://doi.org/10.1039/b104677m)
- R. Lo Nigro, R.G. Toro, G. Malandrino, I.L. Fragala, J. Mater. Chem. **15**, 2328 (2005). doi: [10.1039/b417292b](https://doi.org/10.1039/b417292b)
- D.S. Zhang, H.X. Fu, L.Y. Shi, C.S. Pan, Q. Li, Y.L. Chu et al., Inorg. Chem. **46**, 2446 (2007). doi: [10.1021/ic061697d](https://doi.org/10.1021/ic061697d)
- C. Sun, H. Li, Z.X. Wang, L. Chen, X. Huang, Chem. Lett. **33**, 662 (2004). doi: [10.1246/cl.2004.662](https://doi.org/10.1246/cl.2004.662)
- K.B. Zhou, Z.Q. Yang, S. Yang, Chem. Mater. **19**, 1215 (2007). doi: [10.1021/cm062886x](https://doi.org/10.1021/cm062886x)
- W.Q. Han, L.J. Wu, Y.M. Zhu, J. Am. Chem. Soc. **127**, 12814 (2005). doi: [10.1021/ja054533p](https://doi.org/10.1021/ja054533p)
- C.C. Tang, Y. Bando, B.D. Liu, D. Golberg, Adv. Mater. **17**, 3005 (2005). doi: [10.1002/adma.200501557](https://doi.org/10.1002/adma.200501557)
- W.B. Yue, W.Z. Zhou, J. Mater. Chem. **17**, 4947 (2007). doi: [10.1039/b709076e](https://doi.org/10.1039/b709076e)
- F. Zhou, X.M. Zhao, H. Xu, C.G. Yuan, J. Phys. Chem. C **111**, 1651 (2007). doi: [10.1021/jp0660435](https://doi.org/10.1021/jp0660435)
- G.R. Li, D.L. Qu, Y.X. Tong, Electrochim. Commun. **10**, 80 (2008). doi: [10.1016/j.elecom.2007.11.003](https://doi.org/10.1016/j.elecom.2007.11.003)
- A. Vantomme, Z.Y. Yuan, G.H. Du, B.L. Su, Langmuir **21**, 1132 (2005). doi: [10.1021/la047751p](https://doi.org/10.1021/la047751p)